

REPORT NUMBER: 208-MGA-2008-016

**VEHICLE SAFETY COMPLIANCE TESTING
FOR
FMVSS 208, OCCUPANT CRASH PROTECTION
FMVSS 212, WINDSHIELD MOUNTING
FMVSS 219, WINDSHIELD INTRUSION (PARTIAL)
FMVSS 301, FUEL SYSTEM INTEGRITY**

**HONDA OF AMERICA MFG.
2008 HONDA ACCORD PASSENGER CAR
NHTSA NO.: C85302**

**PREPARED BY:
MGA RESEARCH CORPORATION
5000 WARREN ROAD
BURLINGTON, WI 53105**



TEST DATES: JUNE 2, 2008 – JULY 31, 2008

FINAL REPORT DATE: NOVEMBER 12, 2008

FINAL REPORT

**PREPARED FOR:
U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
OFFICE OF ENFORCEMENT
OFFICE OF VEHICLE SAFETY COMPLIANCE
1200 NEW JERSEY AVENUE, S.E., NVS-220
WASHINGTON, D.C. 20590**

This final test report was prepared for the U.S. Department of Transportation, National Highway Traffic Safety Administration, in response to Contract Number DTNH22-03-D-11002.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by: Jeff Lewandowski Date: November 12, 2008
Jeff Lewandowski, Project Engineer

Reviewed by: David Winkelbauer Date: November 12, 2008
David Winkelbauer, Facility Director

FINAL REPORT ACCEPTED BY OVSC:

Accepted By: Charles R. Case

Acceptance Date: November 12, 2008

Technical Report Documentation Page

1. Report No. 208-MGA-2008-016	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle Final Report of FMVSS 208 Compliance Testing of a 2008 Honda Accord NHTSA No.: C85302		5. Report Date November 12, 2008	
		6. Performing Organization Code MGA	
7. Author(s) Jeff Lewandowski, Project Engineer		8. Performing Organization Report No. 208-MGA-2008-016	
9. Performing Organization Name and Address MGA Research Corporation 5000 Warren Road Burlington, WI 53105		10. Work Unit No.	
		11. Contract or Grant No. DTNH22-03-D-11002	
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Enforcement Office of Vehicle Safety Compliance 1200 New Jersey Avenue, S.E., NVS-220 Washington, D.C. 20590		13. Type of Report and Period Covered 6/2/08 - 7/31/08	
		14. Sponsoring Agency Code NVS-220	
15. Supplementary Notes			
16. Abstract Compliance tests were conducted on the subject 2008 Honda Accord in accordance with the specifications of the Office of Vehicle Safety Compliance Test Procedure No. TP208-13 for the determination of FMVSS 208 compliance. Test failures identified were as follows: TEST FAILURES: None			
17. Key Words Frontal Impact 40 kmph Vehicle Safety Compliance Testing FMVSS 208, "Occupant Crash Protection" FMVSS 212, "Windshield Mounting" FMVSS 219, (partial), "Windshield Zone Intrusion" FMVSS 301, "Fuel System Integrity"		18. Distribution Statement Copies of this report are available from the following: U.S. Department of Transportation National Highway Traffic Safety Administration Technical Information Services (TIS), NPO-411 1200 New Jersey Avenue, S.E. (Room E12-100) Washington, DC 20590	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 344	22. Price

TABLE OF CONTENTS

<u>Section</u>		<u>Page No</u>
1	Purpose of Compliance Test	1
2	Tests Performed	2
3	Injury Result Summary for FMVSS 208 Tests	4
4	Discussion of Tests (if applicable)	7
5	Test Data Sheets	8
<u>Data Sheet</u>		
1	COTR Vehicle Work Order	9
2	Report of Vehicle Condition	13
3	Certification Label and Tire Placard Information	15
4	Rear Outboard Seating Position Seat Belts	16
5	Air Bag Labels	17
6	FMVSS 208 Readiness Indicator	29
7	Passenger Air Bag Manual Cut-Off Device	30
8	Lap Belt Lockability	33
9	FMVSS 208 Seat Belt Warning System Check	45
10	Belt Contact Force	47
11	Latch Plate Access	53
12	Seat Belt Retraction	55
13	Seat Belt Guides and Hardware	57
14	Marking of Reference Points for Various Test Positions & Points	63
16	Air Bag Suppression Telltale	72
17	Suppression Test Using 12-Month CRABI Dummy	73
18	Suppression Test Using Newborn Infant Dummy	80
19	Suppression Test Using 3-YO Dummy and Booster Seats	81
20	Suppression Test Using 3-YO Dummy and Fwd Facing Restraints	83
21	Suppression Test Using an Unbelted 3-YO Dummy	86
27	Summary of Low Risk Deployment Using an Unbelted 6-YO Dummy Position 1	87
28	Summary of Low Risk Deployment Using an Unbelted 6-YO Dummy Position 2	88
29	Summary of Low Risk Deployment Using an Unbelted 5 th % Dummy Position 1	89
30	Summary of Low Risk Deployment Using an Unbelted 5 th % Dummy Position 2	90
32	Vehicle Weight, Fuel Tank, and Attitude Data	91
33	Vehicle Accelerometer Locations and Measurements	95
34	Photographic Targets	98
35	Camera Locations	104

<u>Data Sheet</u>		<u>Page No</u>
36	Dummy Positioning	106
37	Dummy Measurements	118
38	Crash Test	121
40	Accident Investigation Measurements	123
41	Windshield Mounting (FMVSS 212)	125
42	Windshield Zone Intrusion (FMVSS 219)	127
43	Fuel System Integrity (FMVSS 301)	129
 <u>Appendix</u>		
A	Crash Test Data	A-1
B	Low Risk Test Data	B-1
C	Crash Test Photographs	C-1
D	Low Risk Photographs	D-1
E	Suppression Photographs	E-1
F	Instrumentation Calibration	F-1
G	Notice of Test Failure (If Applicable)	G-1

SECTION 1

PURPOSE OF COMPLIANCE TEST

The tests performed are part of a program conducted for the National Highway Traffic Safety Administration (NHTSA) by MGA Research Corporation (MGA) under Contract No. DTNH22-03-D-11002. The purpose of this test was to determine whether the subject vehicle, a 2008 Honda Accord, NHTSA No. C85302, meets certain performance requirements of FMVSS 208, "Occupant Crash Protection"; FMVSS 212, "Windshield Mounting"; FMVSS 219, "Windshield Zone Intrusion"; and FMVSS 301, "Fuel System Integrity". The compliance test was conducted in accordance with OVSC Laboratory Test Procedure No. TP208-13 dated July 27, 2005.

SECTION 2

TESTS PERFORMED

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance

NHTSA No.: C85302
 Test Dates: 6/2/08 - 7/31/08

The following checked items indicate the tests that were performed:

- | | | |
|-------------------------------------|-----|---|
| <input checked="" type="checkbox"/> | 1. | Rear outboard seating position seat belts (S4.1.1.2(b) & (S4.2.4) |
| <input checked="" type="checkbox"/> | 2. | Air bag labels (S4.5.1) |
| <input checked="" type="checkbox"/> | 3. | Readiness indicator (S4.5.2) |
| <input checked="" type="checkbox"/> | 4. | Passenger air bag manual cut-off device (S4.5.4) |
| <input checked="" type="checkbox"/> | 5. | Lap belt lockability (S7.1.1.5) |
| <input checked="" type="checkbox"/> | 6. | Seat belt warning system (S7.3) |
| <input checked="" type="checkbox"/> | 7. | Seat belt contact force (S7.4.4) |
| <input type="checkbox"/> | 8. | Seat belt latch plate access (S7.4.4) |
| <input type="checkbox"/> | 9. | Seat belt retraction (S7.4.5) |
| <input checked="" type="checkbox"/> | 10. | Seat belt guides and hardware (S7.4.6) |
| <input checked="" type="checkbox"/> | 11. | Suppression tests with 12-month-old CRABI dummy (Part 572, Subpart R) |
| <input checked="" type="checkbox"/> | 12. | Suppression tests with newborn infant (Part 572, Subpart K) |
| <input checked="" type="checkbox"/> | 13. | Suppression tests with 3-year-old dummy (Part 572, Subpart P) |
| <input type="checkbox"/> | 14. | Suppression tests with 6-year-old dummy (Part 572, Subpart N) |
| <input checked="" type="checkbox"/> | 15. | Test of reactivation of the passenger air bag system with an unbelted 5 th percentile female dummy |
| <input type="checkbox"/> | 16. | Low risk deployment test with 12-month-old dummy (Part 572, Subpart R) |
| <input type="checkbox"/> | 17. | Low risk deployment test with 3-year-old dummy (Part 572, Subpart P) |
| <input checked="" type="checkbox"/> | 18. | Low risk deployment test with 6-year-old dummy (Part 572, Subpart N) |
| <input checked="" type="checkbox"/> | 19. | Low risk deployment test with 5 th female dummy (Part 572, Subpart O) |
| <input checked="" type="checkbox"/> | 20. | Impact Tests |
| <input type="checkbox"/> | | Frontal Oblique |
| <input type="checkbox"/> | | Belted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.1(a)) |
| <input type="checkbox"/> | | Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a)(1)) |
| <input type="checkbox"/> | | Unbelted 50 th male dummy driver and passenger (32 to 40 kmph) (S5.1.2(a) (1) or S5.1.2(b)) |
| <input checked="" type="checkbox"/> | | Frontal 0° |
| <input type="checkbox"/> | | Belted 50 th male dummy driver (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a)) |
| <input type="checkbox"/> | | Belted 50 th male dummy passenger (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a)) |
| <input type="checkbox"/> | | Belted 5 th female dummy driver (0 to 48 kmph) (S16.1(a)) |
| <input type="checkbox"/> | | Belted 5 th female dummy passenger (0 to 48 kmph) (S16.1(a)) |
| <input type="checkbox"/> | | Belted 50 th male dummy driver and passenger (0 to 56 kmph) (S5.1.1.(b)(2)) |
| <input type="checkbox"/> | | Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a) (1)) |
| <input type="checkbox"/> | | Unbelted 50 th male dummy driver (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b)) |

		Unbelted 50 th male dummy passenger (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))
	X	Unbelted 5 th female dummy driver (32 to 40 kmph) (S16.1(b))
	X	Unbelted 5 th female dummy passenger (32 to 40 kmph) (S16.1(b))
		40% Offset 0° Belted 5 th female dummy driver and passenger (0 to 40 kmph) (S18.1)
	21.	Sled Test: Unbelted 50 th male dummy driver and passenger (S13)
	22.	FMVSS 204 Indicant Test
X	23.	FMVSS 212 Indicant Test
X	24.	FMVSS 219 Indicant Test
X	25.	FMVSS 301 Frontal Indicant Test

For the crash tests, the vehicle was instrumented with 8 accelerometers. The accelerometer data from the vehicle and dummies were sampled at 10,000 samples per second and processed as specified in SAE J211/1 MAR95 and FMVSS 208, S4.13.

The dynamic tests were recorded using high-speed digital video.

The vehicle appears to meet the performance requirements to which it was tested.

SECTION 3**INJURY RESULT SUMMARY FOR FMVSS 208 TESTS**

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance

NHTSA No.: C85302
 Test Date: 7/7/08

5th Percentile Female Low Risk Deployments**5th Percentile Female SN 511 Position 1 (Chin On Module) 7/7/08**

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	42
Peak Nij (Nte)	1.0	0.3
Time (ms)	NA	65.7
Peak Nij (Ntf)	1.0	0.2
Time (ms)	NA	38.8
Peak Nij (Nce)	1.0	0.3
Time (ms)	NA	160.8
Peak Nij (Ncf)	1.0	0.1
Time (ms)	NA	15.7
Neck Tension	2070 N	728
Neck Compression	2520 N	360
Chest g	60 g	10
Chest Displacement	52 mm	6
Left Femur	6805 N	72
Right Femur	6805 N	94

Second stage fire time of 40 ms; Injuries calculated on 0 ms to 165 ms

5th Percentile Female SN 511 Position 2 (Chin On Rim) 7/7/08

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	5
Peak Nij (Nte)	1.0	0.3
Time (ms)	NA	11.0
Peak Nij (Ntf)	1.0	0.1
Time (ms)	NA	72.3
Peak Nij (Nce)	1.0	0.0
Time (ms)	NA	8.2
Peak Nij (Ncf)	1.0	0.2
Time (ms)	NA	83.7
Neck Tension	2070 N	613
Neck Compression	2520 N	127
Chest g	60 g	27
Chest Displacement	52 mm	16
Left Femur	6805 N	70
Right Femur	6805 N	71

Second stage fire time of 40 ms; Injuries calculated on 0 ms to 165 ms

SECTION 3

INJURY RESULT SUMMARY FOR FMVSS 208 TESTS

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance

NHTSA No.: C85302
Test Dates: 7/7/08 – 7/8/08

6-Year-Old Low Risk Deployments

6-Year-Old SN 155 Position 1 (Chest On Instrument Panel) 7/7/08

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	50
Peak Nij (Nte)	1.0	0.4
Time (ms)	NA	76.9
Peak Nij (Ntf)	1.0	0.5
Time (ms)	NA	22.6
Peak Nij (Nce)	1.0	0.1
Time (ms)	NA	1.5
Peak Nij (Ncf)	1.0	0.5
Time (ms)	NA	25.0
Neck Tension	1490 N	590
Neck Compression	1820 N	447
Chest g	60 g	16
Chest Displacement	40 mm	6

Second stage fire time of 150 ms; Injuries calculated on 0 ms to 100 ms

6-Year-Old SN 155 Position 2 (Head On Instrument Panel) 7/8/08

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	17
Peak Nij (Nte)	1.0	0.3
Time (ms)	NA	68.8
Peak Nij (Ntf)	1.0	0.2
Time (ms)	NA	80.3
Peak Nij (Nce)	1.0	0.5
Time (ms)	NA	46.2
Peak Nij (Ncf)	1.0	0.2
Time (ms)	NA	28.5
Neck Tension	1490 N	584
Neck Compression	1820 N	835
Chest g	60 g	10
Chest Displacement	40 mm	1

Second stage fire time of 150 ms; Injuries calculated on 0 ms to 100 ms

SECTION 3
INJURY RESULT SUMMARY FOR FMVSS 208 TESTS

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance

NHTSA No.: C85302
 Test Date: 7/31/08

40 kmph Frontal Crash

Impact Angle: Zero degrees

Belted Dummies: Yes X No
 Speed Range: 0 to 40 kmph X 32 to 40 kmph
 0 to 48 kmph 0 to 56 kmph

Test Speed: 39.8 kmph Test Weight: 1749.1 kg

Driver Dummy: X 5th female 50th male
 Passenger Dummy: X 5th female 50th male

5th Percentile Female Frontal Crash Test
Vehicles certified to S16.1(a), S16.1(b), or S18.1

Injury Criteria	Max. Allowable Injury Assessment Values	Driver	Passenger
HIC15	700	79	136
N _{te}	1.0	0.5	0.1
N _{tf}	1.0	0.4	0.2
N _{ce}	1.0	0.3	0.2
N _{cf}	1.0	0.2	0.7
Neck Tension	2620 N	1102	507
Neck Compression	2520 N	394	662
Chest g	60 g	44	37
Chest Displacement	52 mm	19	7
Left Femur	6805 N	4265	4286
Right Femur	6805 N	5637	5074

SECTION 4

DISCUSSION OF TESTS

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance

NHTSA No.: C85302
Test Dates: 6/2/08 - 7/31/08

A blanket and visor were not used in the suppression testing because they did not affect the sensing system used on the vehicle.

Due to a software error there was no high speed video for the 5th female driver position 1 low risk deployment test conducted on 7-7-08.

Some pretest photos for the frontal impact conducted on 7-31-08 incorrectly identify the test speed as 30 mph. The test speed was 25 mph.

SECTION 5
TEST DATA SHEETS

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance

NHTSA No.: C85302
Test Dates: 6/2/08 - 7/31/08

DATA SHEET 1

COTR VEHICLE WORK ORDER

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance

NHTSA No.: C85302
 Test Dates: 6/2/08 - 7/31/08

COTR Signature: Charles R. Case

Test to be performed for this vehicle are checked below:

<input checked="" type="checkbox"/>	1. Rear Outboard Seating Position Seat Belts (S4.1.2(b)) & (S4.2.4)
<input checked="" type="checkbox"/>	2. Air Bag Labels (S4.5.1)
<input checked="" type="checkbox"/>	3. Readiness Indicator (S4.5.2)
<input checked="" type="checkbox"/>	4. Passenger Air Bag Manual Cut-off Device (S4.5.4)
<input checked="" type="checkbox"/>	5. Lap Belt Lockability (S7.1.1.5)
<input checked="" type="checkbox"/>	6. Seat Belt Warning System (S7.3)
<input checked="" type="checkbox"/>	7. Seat Belt Contact Force (S7.4.4)
<input type="checkbox"/>	8. Seat Belt Latch Plate Access (S7.4.4)
<input type="checkbox"/>	9. Seat Belt Retraction (S7.4.5)
<input checked="" type="checkbox"/>	10. Seat Belt Guides and Hardware (S7.4.6)
<input checked="" type="checkbox"/>	11. Suppression tests with 12-month-old CRABI dummy (Part 572, Subpart R) using the following indicated child restraints.

Section B

<input checked="" type="checkbox"/>	Britax Handle with Care 191	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Assura 4553	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Avanta SE 41530	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Smart Fit 4543	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Arriva 02727	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Opus 35 02603	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Discovery Adjust Right 212	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Evenflo First Choice 204	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo On My Way Position Right V 282	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Graco Infant 8457	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward

Section C

<input checked="" type="checkbox"/>	Britax Roundabout 161	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Century Encore 4612	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century STE 1000 4416	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Olympian 02803	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Touriva 02519	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Horizon V 425	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Evenflo Medallion 254	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	12. Suppression tests with newborn infant (Part 572, Subpart K) using the following indicated child restraints.						

Section A

<input checked="" type="checkbox"/>	Cosco Dream Ride 02-719	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	13. Suppression tests with 3-year-old dummy (Part 572, Subpart P) using the following indicated child restraints where a child restraint is required.						

Section C

<input checked="" type="checkbox"/>	Britax Roundabout 161	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Century Encore 4612	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century STE 1000 4416	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Olympian 02803	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Touriva 02519	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Horizon V 425	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Evenflo Medallion 254	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward

Section D

<input type="checkbox"/>	Britax Roadster 9004	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Century Next Step 4920	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Cosco High Back Booster 02-442	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Right Fit 245	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward

- ☐ 14. Suppression tests with representative 3-year-old child using the following indicated child restraints where a child restraint is required. (Appendix H, Data Sheet 16H and 17H)

Section C

<input type="checkbox"/>	Britax Roundabout 161	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Encore 4612	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century STE 1000 4416	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Olympian 02803	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Touriva 02519	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Horizon V 425	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Medallion 254	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward

Section D

<input type="checkbox"/>	Britax Roadster 9004	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Next Step 4920	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco High Back Booster 02-442	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Right Fit 245	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward

- ☒ 15. Suppression tests with 3-year-old dummy (Part 572, Subpart P) in the following Forward, Middle, and Rearward seat track positions

<input checked="" type="checkbox"/>	Sitting on seat with back against seat back (S22.2.2.1)
<input checked="" type="checkbox"/>	Sitting on seat with back against reclined seat back (S22.2.2.2)
<input checked="" type="checkbox"/>	Sitting on seat with back not against seat back (S22.2.2.3)
<input checked="" type="checkbox"/>	Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
<input checked="" type="checkbox"/>	Standing on seat, facing forward (S22.2.2.5)
<input checked="" type="checkbox"/>	Kneeling on seat facing forward (S22.2.2.6)
<input checked="" type="checkbox"/>	Kneeling on seat facing rearward (S22.2.2.7)
<input type="checkbox"/>	Lying on seat (S22.2.2.8)

- ☐ 16. Suppression tests with representative 3-year-old child in the following positions

<input type="checkbox"/>	Sitting on seat with back against seat back (S22.2.2.1)
<input type="checkbox"/>	Sitting on seat with back against reclined seat back (S22.2.2.2)
<input type="checkbox"/>	Sitting on seat with back not against seat back (S22.2.2.3)
<input type="checkbox"/>	Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
<input type="checkbox"/>	Standing on seat, facing forward (S22.2.2.5)
<input type="checkbox"/>	Kneeling on seat facing forward (S22.2.2.6)
<input type="checkbox"/>	Kneeling on seat facing rearward (S22.2.2.7)
<input type="checkbox"/>	Lying on seat (S22.2.2.8)

- ☐ 17. Suppression tests with 6-year-old dummy (Part 572, Subpart N) using the following indicated child restraints where a child restraint is required.

Section D

<input type="checkbox"/>	Britax Roadster 9004	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Next Step 4920	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco High Back Booster 02-442	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Right Fit 245	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/> 18.	Suppression tests with representative 6-year-old child using the following indicated child restraints where a child restraint is required.						

Section D

<input type="checkbox"/>	Britax Roadster 9004	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Next Step 4920	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco High Back Booster 02-442	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Right Fit 245	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/> 19.	Suppression tests with 6-year-old dummy (Part 572, Subpart N) in the following Forward, Middle, and Rearward seat track positions						

- ☐ Sitting on seat with back against seat back (S22.2.2.1)
- ☐ Sitting on seat with back against reclined seat back (S22.2.2.2)
- ☐ Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
- ☐ Sitting back in the seat and leaning on the right front passenger door (S24.2.3)

<input type="checkbox"/> 20.	Suppression tests with representative 6-year-old child in the following positions						
<input type="checkbox"/>	Sitting on seat with back against seat back (S22.2.2.1)						
<input type="checkbox"/>	Sitting on seat with back against reclined seat back (S22.2.2.2)						
<input type="checkbox"/>	Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)						
<input type="checkbox"/>	Sitting back in the seat and leaning on the right front passenger door (S24.2.3)						

<input checked="" type="checkbox"/> 21.	Test of Reactivation of the Passenger Air Bag System with an Unbelted 5 th percentile female dummy (S20.3, 22.3, S24.3). Perform this test after the following suppression tests: After each restraint.						
---	--	--	--	--	--	--	--

<input type="checkbox"/> 22.	Test of Reactivation of the passenger air bag system with a representative 5 th percentile female (S20.3, 22.3, S24.3). Perform this test after the following suppression tests:						
------------------------------	---	--	--	--	--	--	--

<input type="checkbox"/> 23.	Low risk deployment test with 12-month-old dummy (Part 572, Subpart R) using the following indicated child restraints.						
------------------------------	--	--	--	--	--	--	--

Section B

<input type="checkbox"/>	Britax Handle with Care 191	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Assura 4553	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Avanta SE 41530	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Smart Fit 4543	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Arriva 02727	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Opus 35 02603	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Discovery Adjust Right 212	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo First Choice 204	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo On My Way Position Right V 282	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Graco Infant 8457	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward

Section C

<input type="checkbox"/>	Britax Roundabout 161	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Encore 4612	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century STE 1000 4416	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Olympian 02803	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Touriva 02519	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Horizon V 425	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Medallion 254	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward

	24.	Low risk deployment test with 3-year-old dummy (Part 572, Subpart P) in the following positions
		Position 1
		Position 2
X	25.	Low risk deployment test with 6-year-old dummy (Part 572, Subpart N) in the following positions
		Position 1
		Position 2
X	26.	Low risk deployment test with 5 th percentile female dummy (Part 572, Subpart O) in the following positions
		Position 1
		Position 2
X	27.	Impact Tests
		Frontal Oblique - Test Speed:
		Belted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.1(a))
		Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a)(1))
		Unbelted 50 th male dummy driver and passenger (32 to 40 kmph) (S5.1.2(a) (1) or S5.1.2(b))
X		Frontal 0° - Test Speed: 39.8 kmph
		Belted 50 th male dummy driver (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))
		Belted 50 th male dummy passenger (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))
		Belted 5 th female dummy driver (0 to 48 kmph) (S16.1(a))
		Belted 5 th female dummy passenger (0 to 48 kmph) (S16.1(a))
		Belted 50 th male dummy driver and passenger (0 to 56 kmph) (S5.1.1.(b)(2))
		Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a) (1))
		Unbelted 50 th male dummy driver (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))
		Unbelted 50 th male dummy passenger (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))
		Unbelted 5 th female dummy driver (32 to 40 kmph) (S16.1(b))
		Unbelted 5 th female dummy passenger (32 to 40 kmph) (S16.1(b))
		40% Offset 0° Belted 5 th female dummy driver and passenger (0 to 40 kmph) (S18.1) - Test Speed:
	28.	Sled Test: Unbelted 50 th male dummy driver and passenger (S13)
	29.	FMVSS 204 Indicant Test
X	30.	FMVSS 212 Indicant Test
X	31.	FMVSS 219 Indicant Test
X	32.	FMVSS 301 Frontal Indicant Test

DATA SHEET 2
REPORT OF VEHICLE CONDITION

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance

NHTSA No.: C85302
Test Dates: 6/2/08 - 7/31/08

CONTRACT NO.: DTNH22-03-D-11002

Date: 8/4/08

FROM (Lab and rep name): MGA Research Corporation

TO: NHTSA, OVSC (NVS-220)

PURPOSE: (X) Initial Receipt () Received via Transfer (X) Present vehicle condition

MODEL YEAR/MAKE/MODEL/BODY STYLE: 2008 Honda Accord 4 Door

MANUFACTURE DATE: 09/07

NHTSA NO. C85302

GVWR: 2075 kg (4575 lbs)

BODY COLOR: Green

GAWR (Fr): 1160 kg (2557 lbs)

VIN: 1HGCP36798A003873

GAWR (Rr): 935 kg (2061 lbs)

ODOMETER READINGS: ARRIVAL (miles): 139 DATE: 4/30/08

COMPLETION (miles): 147 DATE: 7/31/08

PURCHASE PRICE: (\$) 24,000

DEALER'S NAME: Wilde Honda, 1710 Hwy 164, Waukesha, WI 53186

- A. All options listed on window sticker are present on the test vehicle:
X Yes ___ No
- B. Tires and wheel rims are new and the same as listed: X Yes ___ No
- C. There are no dents or other interior or exterior flaws: X Yes ___ No
- D. The vehicle has been properly prepared and is in running condition:
X Yes ___ No
- E. Keyless remote is available and working: X Yes ___ No
- F. The glove box contains an owner's manual, warranty document, consumer information, and extra set of keys: X Yes ___ No
- G. Proper fuel filler cap is supplied on the test vehicle: X Yes ___ No
- H. Using permanent marker, identify vehicle with NHTSA number and FMVSS test type(s) on roof line above driver door or for school buses, place a placard with NHTSA number inside the windshield and to the exterior front and rear side of bus:
X Yes ___ No
- I. Place vehicle in storage area: X Yes ___ No
- J. Inspect the vehicle's interior and exterior, including all windows, seats, doors, etc. to confirm that each system is complete and functional per the manufacturer's specifications. Any damage, misadjustment, or other unusual condition that could influence the test program or test results shall be recorded. Report any abnormal condition to the NHTSA COTR before beginning any test:
X Vehicle OK ___ Conditions reported below

REPORT OF VEHICLE CONDITION AT THE COMPLETION OF TESTING

LIST OF FMVSS TESTS PERFORMED BY THIS LAB: FMVSS 208, 212, 219, 301

VEHICLE: 2008 Honda Accord

NHTSA NO. : C85302

REMARKS:

Equipment that is no longer on the test vehicle as noted on previous page:

Spare tire, jack and tools, and trunk interior

Explanation for equipment removal:

Components removed for instrumentation installation and to meet target weight.

Test Vehicle Condition:

25 mph frontal impact damage- front suspension & structure damaged, hood & front quarter panels damaged, radiator damaged, air bags & pretensioners deployed, Stoddard in fuel system

RECORDED BY: Jeff Lewandowski

DATE: 8/4/2008

APPROVED BY: David Winkelbauer

DATE: 8/4/2008

#####

RELEASE OF TEST VEHICLE

The vehicle described above is released from MGA to be delivered to:

Date:

Time:

Odometer:

Lab Rep's Signature:

Title:

Carrier/Customer Rep:

Date:

DATA SHEET 3**CERTIFICATION LABEL AND TIRE PLACARD INFORMATION**

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Jamie Aide

NHTSA No.: C85302
Test Date: 7/31/08

Certification Label	
Manufacturer:	HONDA OF AMERICA MFG.
Date of Manufacture:	09/07
VIN:	1HGCP36798A003873
Vehicle Certified As (Pass. Car/MPV/Truck/Bus):	Passenger Car
Front Axle GVWR:	1160 kg (2557 lbs)
Rear Axle GVWR:	935 kg (2061 lbs)
Total GVWR:	2075 kg (4575 lbs)

Tire Placard	
Not applicable, vehicle is not a passenger car and does not have a tire placard.	Passenger Car
This is not a passenger car, but all or part of this information is still contained on a vehicle label and is reported here.	Passenger Car
Vehicle Capacity Weight:	385 kg (850 lbs)
Designated Seating Capacity Front:	2
Designated Seating Capacity Rear:	3
Total Designated Seating Capacity:	5
Recommended Cold Tire Inflation Pressure Front:	220 kpa (32 psi)
Recommended Cold Tire Inflation Pressure Rear:	220 kpa (32 psi)
Recommended Tire Size:	P225/50R17

Signature: 

Date: 7/31/08

DATA SHEET 4

REAR OUTBOARD SEATING POSITION SEAT BELTS

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C85302
Test Date: 6/2/08

	Yes	No
Do all rear outboard seating positions have Type 2 seat belts?	X	

If NO, describe the seat belt installed, the seat location, and any other information about the seat that would explain why a Type 2 seat belt was not installed.

REMARKS:

Signature: Wayne Dahlke

Date: 6/2/08

DATA SHEET 5 **AIR BAG LABELS (S4.5.1)**

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C85302
 Test Date: 6/2/08

- | | | |
|-------------------------------------|-----|--|
| <input checked="" type="checkbox"/> | 1. | Air bag maintenance label and owner's manual instructions: (S4.5.1(a)) |
| <input checked="" type="checkbox"/> | 1.1 | Does the manufacturer recommend periodic maintenance or replacement of the air bag? |
| | | <input type="checkbox"/> Yes, go to 1.2 |
| | | <input checked="" type="checkbox"/> No - go to 2 |
| <input type="checkbox"/> | 1.2 | Does the vehicle have a label specifying air bag maintenance or replacement? |
| | | <input type="checkbox"/> Yes - Pass |
| | | <input type="checkbox"/> No - Fail |
| <input type="checkbox"/> | 1.3 | Does the label contain one of the following? |
| | | <input type="checkbox"/> Yes - Pass |
| | | <input type="checkbox"/> No - Fail |
| | | Check applicable schedule: |
| | | ___ Schedule on label specifies month and year (Record date_____) |
| | | ___ Schedule on label specified vehicle mileage (Record mileage_____) |
| | | ___ Schedule on label specifies interval measured from date on certification label (Record interval_____) |
| <input type="checkbox"/> | 1.4 | Is the label permanently affixed within the passenger compartment such that it cannot be removed without destroying or defacing the label or the sunvisor? (3/19/01 legal interpretation to Todd Mitchell) |
| | | <input type="checkbox"/> Yes - Pass |
| | | <input type="checkbox"/> No - Fail |
| <input type="checkbox"/> | 1.5 | Is the label lettered in English? |
| | | <input type="checkbox"/> Yes - Pass |
| | | <input type="checkbox"/> No - Fail |
| <input type="checkbox"/> | 1.6 | Is the label in block capitals and numerals? |
| | | <input type="checkbox"/> Yes - Pass |
| | | <input type="checkbox"/> No - Fail |
| <input type="checkbox"/> | 1.7 | Are the letters and numerals at least 3/32 inches high? |
| | | <input type="checkbox"/> Yes - Pass |
| | | <input type="checkbox"/> No - Fail |
| <input type="checkbox"/> | 1.8 | Does the owner's manual set forth the recommended schedule for maintenance or replacement? |
| <input checked="" type="checkbox"/> | 2. | Does the owner's manual: (S4.5.1(f)) |
| <input checked="" type="checkbox"/> | 2.1 | Include a description of the vehicle's air bag system in an easily understandable format? |
| | | <input checked="" type="checkbox"/> Yes - Pass |
| | | <input type="checkbox"/> No - Fail |
| <input checked="" type="checkbox"/> | 2.2 | Include a statement that the vehicle is equipped with an air bag and a lap/shoulder belt at the front outboard seating position? |
| | | <input checked="" type="checkbox"/> Yes - Pass |
| | | <input type="checkbox"/> No - Fail |

- ☒ 2.3 Include a statement that the air bag is a supplemental restraint at the front outboard seating position?
☒ Yes - Pass
☐ No - Fail
- ☒ 2.4 Emphasize that all occupants, including the driver, should always wear their seat belts whether or not an air bag is also provided at their seating positions to minimize the risk of severe injury or death in the event of a crash?
☒ Yes - Pass
☐ No - Fail
- ☒ 2.5 Provide any necessary precautions regarding the proper positioning of occupants, including children, at seating positions equipped with air bags to ensure maximum safety protection for those occupants?
☒ Yes - Pass
☐ No - Fail
- ☒ 2.6 Explain that no objects should be placed over or near the air bag on the steering wheel or on the instrument panel, because any such objects could cause harm if the vehicle is in a crash severe enough to cause the air bag to inflate?
☒ Yes - Pass
☐ No - Fail
- ☒ 2.7 Is the vehicle certified to meet the requirements of S14.5, S15, S17, S19, S21, S23, and S25? (Obtain answer from COTR) (S4.5.1(f)(2))
☒ Yes - (Go to 2.7.1)
☐ No - (Go to 3.)
- ☒ 2.7.1 Explain the proper functioning of the advanced air bag system? (S4.5.1(f)(2))
☒ Yes - Pass
☐ No - Fail
- ☒ 2.7.2 Provide a summary of the actions that may affect the proper functioning of the system? (S4.5.1(f)(2))
☒ Yes - Pass
☐ No - Fail
- ☒ 2.7.3 Present and explain the main components of the advanced passenger air bag system? (S4.5.1(f)(2)(i))
☒ Yes - Pass
☐ No - Fail
- ☒ 2.7.4 Explain how the components function together as part of the advanced passenger air bag system? (S4.5.1(f)(2)(ii))
☒ Yes - Pass
☐ No - Fail
- ☒ 2.7.5 Contain the basic requirements for proper operation, including an explanation of the actions that may affect the proper functioning of the system? (S4.5.1(f)(2)(iii))
☒ Yes - Pass
☐ No - Fail
- ☒ 2.7.6 Is the vehicle certified to the requirements of S19.2, S21.2, or 23.2 (automatic suppression)?
☒ Yes, continue with 2.7.6
☐ No, go to 2.7.7
- ☒ 2.7.6.1 Contain a complete description of the passenger air bag suppression system installed in the vehicle, including a discussion of any suppression zone? (S4.5.1(f)(2)(iv))
☒ Yes - Pass
☐ No - Fail

<input checked="" type="checkbox"/>	2.7.6.2	Discuss the telltale light, specifying its location in the vehicle and explaining when the light is illuminated?
	<input checked="" type="checkbox"/>	Yes - Pass
	<input type="checkbox"/>	No - Fail
<input checked="" type="checkbox"/>	2.7.7	Explain the interaction of the advanced passenger air bag system with other vehicle components, such as seat belts, seats or other components? (S4.5.1(f)(2)(v))
	<input checked="" type="checkbox"/>	Yes - Pass
	<input type="checkbox"/>	No - Fail
<input checked="" type="checkbox"/>	2.7.8	Summarize the expected outcomes when child restraint systems, children and small teenagers or adults are both properly and improperly positioned in the passenger seat, including cautionary advice against improper placement of child restraint systems? (S4.5.1(f)(2)(vi))
	<input checked="" type="checkbox"/>	Yes - Pass
	<input type="checkbox"/>	No - Fail
<input checked="" type="checkbox"/>	2.7.9	Provide information on how to contact the vehicle manufacturer concerning modifications for persons with disabilities that may affect the advanced air bag system? (S4.5.1(f)(2)(vii))
	<input checked="" type="checkbox"/>	Yes - Pass
	<input type="checkbox"/>	No - Fail
<input checked="" type="checkbox"/>	3.	Sun Visor Air Bag Warning Label (S4.5.1(b)) Check only one of the following:
	<input type="checkbox"/>	The vehicle is not certified to meet the requirements of S19, S21, and S23 (Obtain answer from COTR) (S4.5.1(b)(1)) Go to 3.1 and skip 3.2
	<input checked="" type="checkbox"/>	The vehicle is certified to meet the requirements of S19, S21, and S23 on 9/1/03 or later. (Obtain answer from COTR) (S4.5.1(b)(3)) Go to 3.2 and skip 3.1
<input type="checkbox"/>	3.1	Vehicles not certified to meet the requirements of S19, S21, and S23.
<input type="checkbox"/>	3.1.1	Is the label permanently affixed (including permanent marking on the visor material or molding into the visor material) to either side of the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing the label or sun visor? (S4.5.1(b)(1)) (3/19/01 legal interpretation to Todd Mitchell)
	<input type="checkbox"/>	Driver Side, Yes - Pass
	<input type="checkbox"/>	Driver Side, No - Fail
	<input type="checkbox"/>	Passenger Side, Yes - Pass
	<input type="checkbox"/>	Passenger Side, No - Fail



3.1.2

Does the label conform in content to the label shown in either Figure 6A or 6B (Figure 6b is for vehicles with passenger air bag on-off switches), as appropriate, at each front outboard seating position? (S4.5.1(b)(1)) (Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(b)(1)(iv))



Figure 6a. Sun Visor Label Visible When Visor is in Down Position.



Figure 6b. Sun Visor Label Visible When Visor is in Down Position.



- Driver Side, Yes - Pass
- Driver Side, No - Fail
- Passenger Side, Yes - Pass
- Passenger Side, No - Fail



3.1.3

Is the label heading area yellow with the word "WARNING" and the alert symbol in black? (S4.5.1(b)(1)(i))



- Driver Side, Yes - Pass
- Driver Side, No - Fail
- Passenger Side, Yes - Pass
- Passenger Side, No - Fail



3.1.4

Is the message area white with black text? (S4.5.1(b)(1)(ii))



- Driver Side, Yes - Pass
- Driver Side, No - Fail
- Passenger Side, Yes - Pass
- Passenger Side, No - Fail

<input type="checkbox"/>	3.1.5	Is the message area at least 30 cm ² ? (S4.5.1(b)(1)(ii)) The message area consists of the total label area minus the yellow heading area and the pictogram. The pictogram is enclosed on the left side and bottom by the edge of the label and on the top by line that borders the yellow heading area. The right side of the pictogram is defined by a vertical line midway between the rightmost edge of the pictogram and the left most edge of the text, including any bullets. (See 5/6/03 interpretation to Gerald Plante on behalf of Subaru) Driver Side: Length_____, Width_____ Passenger Side: Length_____, Width_____ Actual message area _____ cm ²
<input type="checkbox"/>		<input type="checkbox"/> Driver Side, Yes - Pass
<input type="checkbox"/>		<input type="checkbox"/> Driver Side, No - Fail
<input type="checkbox"/>		<input type="checkbox"/> Passenger Side, Yes - Pass
<input type="checkbox"/>		<input type="checkbox"/> Passenger Side, No - Fail
<input type="checkbox"/>	3.1.6	Is the pictogram black with a red circle and slash on a white background? (S4.5.1(b)(2)(iii))
<input type="checkbox"/>		<input type="checkbox"/> Driver Side, Yes - Pass
<input type="checkbox"/>		<input type="checkbox"/> Driver Side, No - Fail
<input type="checkbox"/>		<input type="checkbox"/> Passenger Side, Yes - Pass
<input type="checkbox"/>		<input type="checkbox"/> Passenger Side, No - Fail
<input type="checkbox"/>	3.1.7	Is the pictogram at least 30 mm in diameter? (S4.5.1(b)(2)(iii)) Actual diameter_____mm
<input type="checkbox"/>		<input type="checkbox"/> Driver Side, Yes - Pass
<input type="checkbox"/>		<input type="checkbox"/> Driver Side, No - Fail
<input type="checkbox"/>		<input type="checkbox"/> Passenger Side, Yes - Pass
<input type="checkbox"/>		<input type="checkbox"/> Passenger Side, No - Fail
<input checked="" type="checkbox"/>	3.2	Vehicles certified to meet the requirements of S19, S21, and S23 on 9/1/03 and later. (S4.5.1(b)(3))
<input checked="" type="checkbox"/>	3.2.1	Is the label permanently affixed (including permanent marking on the visor material or molding into the visor material) to either side of the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing the label or the sun visor? (S4.5.1(b)(3)) (3/19/01 legal interpretation to Todd Mitchell)
<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/> Driver Side, Yes - Pass
<input type="checkbox"/>		<input type="checkbox"/> Driver Side, No - Fail
<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/> Passenger Side, Yes - Pass
<input type="checkbox"/>		<input type="checkbox"/> Passenger Side, No - Fail

X

3.2.2

Does the label conform in content to the label shown in Figure 11 at each front outboard seating position? (S4.5.1(b)(2)) (Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(b)(3)(iv)) Vehicles without back seats or the back seat is too small to accommodate a rear-facing child restraint may omit the statement "Never put a rear-facing child seat in the front."(S4.5.1(b)(3)(v))



Figure 11. Sun Visor Label Visible when Visor is in Down Position.

X

X

Driver Side, Yes - Pass

Driver Side, No - Fail

Passenger Side, Yes - Pass

Passenger Side, No - Fail

X

3.2.3

Is the label heading area yellow with the word "WARNING" and the alert symbol in black? (S4.5.1(b)(3)(i))

X

X

Driver Side, Yes - Pass

Driver Side, No - Fail

Passenger Side, Yes - Pass

Passenger Side, No - Fail

X

3.2.4

Is the message area white with black text? (S4.5.1(b)(3)(ii))

X

X

Driver Side, Yes - Pass

Driver Side, No - Fail

Passenger Side, Yes - Pass

Passenger Side, No - Fail

<input checked="" type="checkbox"/>	3.2.5	Is the message area at least 30 cm ² ? (S4.5.1(b)(3)(ii)) The message area consists of the total label area minus the yellow heading area and the pictogram. The pictogram is enclosed on the left side and bottom by the edge of the label. The top edge of the pictogram area is defined by a horizontal line midway between the uppermost edge of the pictogram and the lowermost edge of the text. The right side of the pictogram is defined by a vertical line midway between the rightmost edge of the pictogram and the left most edge of the text, including any bullets. (See 5/6/03 interpretation to Gerald Plante on behalf of Subaru) Driver Side: Length <u>8.7 cm</u> , Width <u>3.5 cm</u> Passenger Side: Length <u>8.7 cm</u> , Width <u>3.5 cm</u> Actual message area: <u>30.5 cm²</u>
	<input checked="" type="checkbox"/>	Driver Side, Yes - Pass
	<input type="checkbox"/>	Driver Side, No - Fail
	<input checked="" type="checkbox"/>	Passenger Side, Yes - Pass
	<input type="checkbox"/>	Passenger Side, No - Fail
<input checked="" type="checkbox"/>	3.2.6	Is the pictogram black on a white background? (S4.5.1(b)(3)(iii))
	<input checked="" type="checkbox"/>	Driver Side, Yes - Pass
	<input type="checkbox"/>	Driver Side, No - Fail
	<input checked="" type="checkbox"/>	Passenger Side, Yes - Pass
	<input type="checkbox"/>	Passenger Side, No - Fail
<input checked="" type="checkbox"/>	3.2.7	Is the pictogram at least 30 mm (1.2 inches) in length? (S4.5.1(b)(3)(iii)) Driver Side: Length <u>32 mm</u> Passenger Side: Length <u>32 mm</u>
	<input checked="" type="checkbox"/>	Driver Side, Yes - Pass
	<input type="checkbox"/>	Driver Side, No - Fail
	<input checked="" type="checkbox"/>	Passenger Side, Yes - Pass
	<input type="checkbox"/>	Passenger Side, No - Fail
<input checked="" type="checkbox"/>	3.3	Is the same side of the sun visor that contains the air bag warning label free of other information with the exception of the air bag maintenance label and/or the rollover-warning label? (S4.5.1(b)(5)(i))
	<input checked="" type="checkbox"/>	Driver Side, Yes - Pass
	<input type="checkbox"/>	Driver Side, No - Fail
	<input checked="" type="checkbox"/>	Passenger Side, Yes - Pass
	<input type="checkbox"/>	Passenger Side, No - Fail
<input checked="" type="checkbox"/>	3.4	Is the sun visor free of other information about air bags or the need to wear seat belts with the exception of the air bag alert label and/or the rollover-warning label? (S4.5.1(b)(5)(ii))
	<input checked="" type="checkbox"/>	Driver Side, Yes - Pass
	<input type="checkbox"/>	Driver Side, No - Fail
	<input checked="" type="checkbox"/>	Passenger Side, Yes - Pass
	<input type="checkbox"/>	Passenger Side, No - Fail

- ☒ 3.5 Does the driver side visor contain a rollover-warning label on the same side of the visor as the air bag warning label?
 __ Yes, go to 3.5.1
☒ No, go to 4 (skipping 3.5.1 through 3.5.3)
- ☐ 3.5.1 Are both the rollover-warning label and the air bag warning label surrounded by a continuous solid-lined border?
 __ Yes, go to 3.5.2 and skip 3.5.3
 __ No, go to 3.5.3 and skip 3.5.2
- ☐ 3.5.2 Is the shortest distance from the border of the rollover label to the border of the air bag warning label at least 1 cm? (575.105 (d)(1)(iv)(B)) actual distance
- ☐ 3.5.3 Is the shortest distance from any of the lettering or graphics on the rollover-warning label to any of the lettering or graphics of the air bag warning label at least 3 cm? (575.105 (d)(1)(iv)(A))
 ____ actual distance
 __ Yes-Pass __ No-FAIL
- ☒ 4. Air Bag Alert Label (S4.5.1(c) (A "Rollover Warning Label" or "Rollover Alert Label" may be on the same side of the driver's sun visor as the "Air Bag Alert Label." 575.105(d))
- ☒ 4.1 Is the sun visor warning label visible when the sun visor is in the stowed position?
☐ If yes for driver and passenger, go to 5.
☐ Driver Side, Yes
☒ Driver Side, No
☐ Passenger Side, Yes
☒ Passenger Side, No
- ☒ 4.2 Is the air bag alert label permanently affixed (including permanent marking on the visor material or molding into the visor material) to the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing the label or the sun visor? (S4.5.1(c)) (3/19/01 legal interpretation to Todd Mitchell)
☒ Driver Side, Yes - Pass
☐ Driver Side, No - Fail
☒ Passenger Side, Yes - Pass
☐ Passenger Side, No - Fail
- ☒ 4.3 Is the air bag alert label visible when the visor is in the stowed position? (S4.5.1(c))
☒ Driver Side, Yes - Pass
☐ Driver Side, No - Fail
☒ Passenger Side, Yes - Pass
☐ Passenger Side, No - Fail

X

4.4 Does the label conform in content to the label shown in Figure 6C? (S4.5.1(c))




Figure 6C. Sun Visor Label Visible When Visor is in Up Position.

X

Driver Side, Yes - Pass

Driver Side, No - Fail

X

Passenger Side, Yes - Pass

Passenger Side, No - Fail

X

4.5 Is the message area black with yellow text? (S4.5.1(c)(1))

X

Driver Side, Yes - Pass

Driver Side, No - Fail

X

Passenger Side, Yes - Pass

Passenger Side, No - Fail

X

4.6 Is the message area at least 20 cm²? (S4.5.1(c)(1)) The message area consists of the black part of the label.

Driver Side: Length 8.4 cm, Width 2.5 cm

Passenger Side: Length 8.4 cm, Width 2.5 cm

Actual message area 21 cm²

X

Driver Side, Yes - Pass

Driver Side, No - Fail

X

Passenger Side, Yes - Pass

Passenger Side, No - Fail

X

4.7 Is the pictogram black with a red circle and slash on a white background? (S4.5.1(c)(2))

X

Driver Side, Yes - Pass

Driver Side, No - Fail

X

Passenger Side, Yes - Pass

Passenger Side, No - Fail

X

4.8 Is the pictogram at least 20 mm in diameter? (S4.5.1(c)(2))

Driver Side Diameter: 21 mm

Passenger Side Diameter: 21 mm

X

Driver Side, Yes - Pass

Driver Side, No - Fail

X

Passenger Side, Yes - Pass

Passenger Side, No - Fail

- ☒ 5. Label on the Dashboard
- ☒ 5.1 Is the vehicle certified to meet the requirements of S19, S21, and S23? (Obtain answer from COTR) (S4.5.1(e)(3))
- ☒ Yes, go to 5.1.1 and skip 5.2
- ☐ No, go to 5.2, skipping 5.1.1 through 5.1.6
- ☒ 5.1.1 Does the vehicle have a label on the dash or steering wheel hub? (S4.5.1(e)(3))
- ☒ Yes - Pass
- ☐ No - Fail
- ☒ 5.1.2 Is the label clearly visible from all front seating positions? (S4.5.1(e)(3))
- ☒ Yes - Pass
- ☐ No - Fail
- ☒ 5.1.3 Does the label conform in content to the label shown in Figure 12? (S4.5.1(e)(3))
Vehicles without back seats may omit the statement: "The back seat is the safest place for children." Vehicles without back seats or too small to accommodate a rear-facing child restraint consistent with S4.5.4.1 as determined in DATA SHEET 7 may omit the statement "Never put a rear-facing child seat in the front." (S4.5.1(e)(3)(iii))
- ☒ Yes - Pass
- ☐ No - Fail




Figure 12. Removable Label on Dash.

- ☒ 5.1.4 Is the heading area yellow with black text? (S4.5.1(e)(3)(i))
- ☒ Yes - Pass
- ☐ No - Fail
- ☒ 5.1.5 Is the message white with black text? (S4.5.1(e)(3)(ii))
- ☒ Yes - Pass
- ☐ No - Fail

☒ 5.1.6 Is the message area at least 30 cm²? (S4.5.1(e)(3)(ii)) The message area consists of the total label area minus the yellow heading area. (See 5/6/03 interpretation to Gerald Plante on behalf of Subaru)
 Length: 10.5 cm Width: 4.5 cm
 Actual message area: 47.3 cm²

☒ Yes - Pass
☐ No - Fail

☐ 5.2 Does the vehicle have a label on the dash or steering wheel hub? (S4.5.1(e)(1))

☐ Yes - Pass
☐ No - Fail

☐ 5.2.1 Is the label clearly visible from all front seating positions? (S4.5.1(e)(1))

☐ Yes - Pass
☐ No - Fail

☐ 5.2.2 Does the label conform in content to the label shown in Figure 7? (S4.5.1(e)(1)(iii))
 Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(e)(1)(iii))

☐ Yes - Pass
☐ No - Fail




Figure 7. Removable Label on Dash.

☐ 5.2.3 Is the heading area yellow with the word "WARNING" and the alert symbol in black? (S4.5.1(e)(1)(i))

☐ Yes - Pass
☐ No - Fail

☐ 5.2.4 Is the message white with black text? (S4.5.1(e)(1)(ii))

☐ Yes - Pass
☐ No - Fail

☐ 5.2.5 Is the message area at least 30 cm²? (S4.5.1(e)(1)(ii)) The message area consists of the total label area minus the yellow heading area. (See 5/6/03 interpretation to Gerald Plante on behalf of Subaru)

Length_____, Width_____

Actual message area _____ cm²

☐ Yes - Pass
☐ No - Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 6/2/08

DATA SHEET 6
FMVSS 208 READINESS INDICATOR (S4.5.2)

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C85302
Test Date: 6/2/08

An occupant restraint system that deploys in the event of a crash shall have a monitoring system with a readiness indicator. A totally mechanical system is exempt from this requirement. (11/8/94 legal interpretation to Lawrence F. Hennegerger on behalf of Breed)

- ☒ 1. Is the system totally mechanical? If Yes, this data sheet is complete.
☐ Yes
☒ No
- ☒ 2. Describe the location of the readiness indicator: *Bottom right of cluster*
- ☒ 3. Is the readiness indicator clearly visible to the driver?
☒ Yes – Pass
☐ No – Fail
- ☒ 4. Is a list of the elements in the occupant restraint system, being monitored by the readiness indicator, provided on a label or in the owner's manual?
☒ Yes – Pass
☐ No – Fail
- ☒ 5. Does the vehicle have an on-off switch for the passenger air bag?
☐ If Yes, go to 6
☒ If No, this form is complete.
- ☐ 6. Is the air bag readiness indicator off when the passenger air bag switch is in the off position?
☐ Yes – Pass
☐ No – Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Dahlke

Date: 6/2/08

DATA SHEET 7

PASSENGER AIR BAG MANUAL CUT-OFF DEVICE (S4.5.4)

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C85302
 Test Date: 6/2/08

- | | | | |
|---|---------|---|--|
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;">X</div> | 1. | Is the vehicle equipped with an on-off switch that deactivates the air bag installed at the right front outboard seating position? | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;"></div> Yes, go to 2 | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;">X</div> No, this sheet is complete | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | 2. | Does the vehicle have any forward-facing rear designated seating positions? (S4.5.4.1(a)) | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;"></div> Yes, go to 3 | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;"></div> No, go to 4 | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | 3. | Verification there is room for a child restraint in the rear seat behind the driver's seat. (S4.5.4.1(b)) | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | 3.1 | Using all the controls that affect the fore-aft movement of the seat, move the seat to the rearmost position. Mark this position. | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;"></div> N/A, the seat does not have fore-aft adjustment | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | 3.2 | Using all the controls that affect the fore-aft movement of the seat, move the seat to the foremost position. Mark this position. | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;"></div> N/A, the seat does not have fore-aft adjustment | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | 3.3 | Move the seat to the middle of the foremost and rearmost positions. (S8.1.2) | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;"></div> N/A, the seat does not have a fore-aft adjustment | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | 3.4 | If the driver's seat height is adjustable, use all the controls that affect height to put it in the lowest position while maintaining the middle fore-aft position. (S8.1.2) | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;"></div> N/A, No seat height adjustment | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | 3.5 | Position the driver's seat adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3) | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;"></div> N/A, No lumbar adjustment | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | 3.6 | The driver's seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1(b) and S8.1.3) | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;"></div> N/A, No seat back angle adjustment | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;"></div> Manufacturer's design driver's seat back angle _____ | |
| | | <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px; display: flex; align-items: center; justify-content: center;"></div> Tested driver's seat back angle _____ | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | 3.7 | Is the driver seat a bucket seat? | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | | ___ Yes, go to 3.7.1 and skip 3.7.2. | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | | ___ No, go to 3.7.2 and skip 3.7.1. | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | 3.7.1 | Bucket seats: | |
| <div style="background-color: yellow; border: 1px solid black; width: 30px; height: 20px;"></div> | 3.7.1.1 | Locate and mark a vertical Plane B through the longitudinal centerline of the driver's seat cushion. The longitudinal centerline of a bucket seat cushion is determined at SgRP. (S16.3.1.10) (S4.5.4.1(b)(1)) | |

<input type="checkbox"/>	3.7.1.2	Locate the longitudinal horizontal line in plane B that is tangent to the highest point of the rear seat cushion behind the driver's seat. Measure along this line from the front of the seat back of the rear seat to the rear of the seat back of the driver's seat. ___ mm distance ___ less than 720 mm - Pass ___ more than 720 mm - FAIL Go to 4
<input type="checkbox"/>	3.2	Bench seats (including split bench seats):
<input type="checkbox"/>	3.7.2.1	Locate and mark a vertical Plane B through the center of the steering wheel parallel to the vehicle longitudinal centerline. (S4.5.4.1(b)(2))
<input type="checkbox"/>	3.7.2.2	Locate the longitudinal horizontal line in plane B that is tangent to the highest point of the rear seat cushion. Measure along this line from the front of the seat back of the rear seat to the rear of the seat back of the front seat. ___ mm distance ___ less than 720 mm - Pass ___ more than 720 mm - FAIL Go to 4
<input type="checkbox"/>	4.	Does the device turn the air bag on and off using the vehicle's ignition key? (S4.5.4.2) <input type="checkbox"/> Yes - Pass <input type="checkbox"/> No - Fail
<input type="checkbox"/>	5.	Is the on-off device separate from the ignition switch? (S4.5.4.2) <input type="checkbox"/> Yes - Pass <input type="checkbox"/> No - Fail
<input type="checkbox"/>	6.	Is there a telltale light that comes on when the passenger air bag is turned off? (S4.5.4.2) <input type="checkbox"/> Yes - Pass <input type="checkbox"/> No - Fail
<input type="checkbox"/>	7.	Telltale light (S4.5.4.3)
<input type="checkbox"/>	7.1	Is the light yellow? S4.5.4.3(a) <input type="checkbox"/> Yes - Pass <input type="checkbox"/> No - Fail
<input type="checkbox"/>	7.2	Are the words "PASSENGER AIR BAG OFF" or "PASS AIR BAG OFF" (S4.5.4.3(b))
<input type="checkbox"/>	7.2.1	on the telltale? <input type="checkbox"/> Yes - Pass, go to 7.3 <input type="checkbox"/> No - go to 7.2.2
<input type="checkbox"/>	7.2.2	within 25 mm of the telltale? Measurement from the edge of the telltale light (mm): <input type="checkbox"/> Yes - Pass <input type="checkbox"/> No - Fail

<input type="checkbox"/>	7.3	Does the telltale remain illuminated while the air bag is turned off? (S4.5.4.3c) (Leave the air bag off for 5 minutes.)
	<input type="checkbox"/>	Yes - Pass
	<input type="checkbox"/>	No - Fail
<input type="checkbox"/>	7.4	Is the telltale illuminated while the air bag is turned on? (S4.5.4.3(d))
	<input type="checkbox"/>	Yes - Fail
	<input type="checkbox"/>	No - Pass
<input type="checkbox"/>	7.5	Is the telltale combined with the air bag readiness indicator? (S4.5.4.3(e))
	<input type="checkbox"/>	Yes - Fail
	<input type="checkbox"/>	No - Pass
<input type="checkbox"/>	8.	Owner's Manual
<input type="checkbox"/>	8.1	Does the owner's manual contain complete instructions on the operation of the on-off switch? (S4.5.4.4(a))
	<input type="checkbox"/>	Yes - Pass
	<input type="checkbox"/>	No - Fail
<input type="checkbox"/>	8.2	Does the owner's manual contain a statement that the on-off switch should only be used when a member of one of the following risk groups is occupying the right front passenger seating position? (S4.5.4.4(b))
	Infants:	there is no back seat
		the rear seat is too small to accommodate a child restraint
		there is a medical condition that must be monitored constantly
	Children	there is no back seat
	aged	space is not always available in the rear seat
	1 to 12:	there is a medical condition that must be monitored constantly
	Medical	medical risk causes special risk for passenger
	condition:	greater risk for harm than with the air bag on
	<input type="checkbox"/>	Yes - Pass
	<input type="checkbox"/>	No - Fail
<input type="checkbox"/>	8.3	Does the owner's manual contain a warning about the safety consequences of using the on-off switch at other times?
	<input type="checkbox"/>	Yes - Pass
	<input type="checkbox"/>	No - Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne J. Ahl

Date: 6/2/08

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C85302
Test Date: 6/2/08

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Front Passenger
------------------------------	-----------------

<input type="checkbox"/>		N/A - no retractor is at this position	
<input type="checkbox"/>		N/A - the retractor is an automatic locking retractor ONLY	
<input checked="" type="checkbox"/>	1.	Record test fore-aft seat position: FULL AFT (S7.1.1.5(c)(1)) (Any position is acceptable)	
<input checked="" type="checkbox"/>	2.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes - Pass	
		<input type="checkbox"/> No - Fail	
<input checked="" type="checkbox"/>	3.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes - Pass	
		<input type="checkbox"/> No - Fail	
<input checked="" type="checkbox"/>	4.	Place any adjustable seat belt anchorage in the lowest adjustment position.	
		<input type="checkbox"/> N/A The anchorage is not adjustable.	
<input checked="" type="checkbox"/>	5.	Buckle the seat belt. (S7.1.1.5(c)(1))	
<input checked="" type="checkbox"/>	6.	Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	7.	Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	8.	Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?	
		<input checked="" type="checkbox"/> Yes, go to 8.1	
		<input type="checkbox"/> No, go to 9.	
<input checked="" type="checkbox"/>	8.1	Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))	
		<input checked="" type="checkbox"/> Yes - Pass	
		<input type="checkbox"/> No - Fail	

- | | |
|--|--|
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>9. Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>10. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>Measured distance between A and B (inches): <u>74 ¾ inches</u></p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>11. Readjust the belt system so that the webbing between points A and B is at 1/2 the maximum length of the webbing. (S7.1.1.5(c)(3))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>12. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>Measured force application angle (Spec. 5-15 degrees): <u>10°</u></p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>13. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>Measured distance between A and B (inches): <u>35 ½ inches</u></p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>14. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): <u>20 lbs./sec</u></p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>Measured distance between A and B (inches) (S7.1.1.5(c)(6)): <u>36 inches</u></p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>15. Let the seat belt webbing retract to its minimum length with the seat belt still buckled</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>16. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))</p> |
| | <p>Measured force application angle <u>10°</u> spec. 5 - 15 degrees)</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | <p>17. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))</p> |
| | <p>Measured distance between A and B <u>20 ½ inches</u></p> |

- ☒ 18. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
Record onset rate 20 lb/sec (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
Measured distance between A and B 20 3/4 inches (S7.1.1.5(c)(6))
- ☒ 19. Subtract the measurement in 13 from the measurement in 14 and the measurement in 17 from the measurement in 18. Is the difference 2 inches or less for both? (S7.1.1.5(c)(7))
 $14-13 = 36 - 35 \frac{1}{2} = \frac{1}{2} \text{ inch}$
 $18-17 = 20 \frac{3}{4} - 20 \frac{1}{2} = \frac{1}{4} \text{ inch}$
- ☒ Yes – Pass
☐ No - Fail
- ☒ 20. Subtract the measurement in 14 from the measurement in 10 and the measurement in 18 from the measurement in 10. Is the difference 3 inches or more for both? (S7.1.1.5(c)(8))
 $10-14 = 74 \frac{3}{4} - 36 = 38 \frac{3}{4} \text{ inches}$
 $10-18 = 74 \frac{3}{4} - 20 \frac{3}{4} = 54 \text{ inches}$
- ☒ Yes – Pass
☐ No - Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 6/2/08




Figure 5. - Webbing Tension Pull Device

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C85302
Test Date: 6/2/08

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Left Rear Passenger
------------------------------	---------------------

<input type="checkbox"/>		N/A - no retractor is at this position	
<input type="checkbox"/>		N/A - the retractor is an automatic locking retractor ONLY	
<input checked="" type="checkbox"/>	1.	Record test fore-aft seat position: (S7.1.1.5(c)(1)) (Any position is acceptable) FIXED	
<input checked="" type="checkbox"/>	2.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))	
<input checked="" type="checkbox"/>		Yes - Pass	
<input type="checkbox"/>		No - Fail	
<input checked="" type="checkbox"/>	3.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))	
<input checked="" type="checkbox"/>		Yes - Pass	
<input type="checkbox"/>		No - Fail	
<input checked="" type="checkbox"/>	4.	Place any adjustable seat belt anchorage in the lowest adjustment position.	
<input checked="" type="checkbox"/>		N/A The anchorage is not adjustable.	
<input checked="" type="checkbox"/>	5.	Buckle the seat belt. (S7.1.1.5(c)(1))	
<input checked="" type="checkbox"/>	6.	Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	7.	Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	8.	Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?	
<input checked="" type="checkbox"/>		Yes, go to 8.1	
<input type="checkbox"/>		No, go to 9.	
<input checked="" type="checkbox"/>	8.1	Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))	
<input checked="" type="checkbox"/>		Yes - Pass	
<input type="checkbox"/>		No - Fail	

- ☒ 9. Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1))
- ☒ 10. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
Measured distance between A and B (inches): 69 ½ inches
- ☒ 11. Readjust the belt system so that the webbing between points A and B is at 1/2 the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 12. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
Measured force application angle (Spec. 5-15 degrees): 10°
- ☒ 13. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
Measured distance between A and B (inches): 29 inches
- ☒ 14. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): 20 lbs/sec
Measured distance between A and B (inches) (S7.1.1.5(c)(6)): 29 ½ inches
- ☒ 15. Let the seat belt webbing retract to its minimum length with the seat belt still buckled
- ☒ 16. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
Measured force application angle 10° (spec. 5 - 15 degrees)
- ☒ 17. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
Measured distance between A and B: 10 ½ inches
- ☒ 18. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
Record onset rate 20 lbs/sec (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
Measured distance between A and B: 11 ¼ inches (S7.1.1.5(c)(6))

19. Subtract the measurement in 13 from the measurement in 14 and the measurement in 17 from the measurement in 18. Is the difference 2 inches or less for both? (S7.1.1.5(c)(7))
- 14-13 = $29 \frac{1}{2} - 29 = \frac{1}{2}$ inches
- 18-17 = $11 \frac{1}{4} - 10 \frac{1}{2} = \frac{3}{4}$ inches
- ☒ Yes - Pass
- ☐ No - Fail
20. Subtract the measurement in 14 from the measurement in 10 and the measurement in 18 from the measurement in 10. Is the difference 3 inches or more for both? (S7.1.1.5(c)(8))
- 10-14 = $69 \frac{1}{2} - 29 \frac{1}{2} = 40$ inches
- 10-18 = $69 \frac{1}{2} - 11 \frac{1}{4} = 58 \frac{1}{4}$ inches
- ☒ Yes - Pass
- ☐ No - Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 6/2/08




Figure 5. - Webbing Tension Pull Device

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C85302
Test Date: 6/2/08

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Center Rear Passenger
------------------------------	-----------------------

<input type="checkbox"/>		N/A - no retractor is at this position
<input type="checkbox"/>		N/A - the retractor is an automatic locking retractor ONLY
<input checked="" type="checkbox"/>	1.	Record test fore-aft seat position: FIXED (S7.1.1.5(c)(1)) (Any position is acceptable)
<input checked="" type="checkbox"/>	2.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))
		<input checked="" type="checkbox"/> Yes - Pass
		<input type="checkbox"/> No - Fail
<input checked="" type="checkbox"/>	3.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))
		<input checked="" type="checkbox"/> Yes - Pass
		<input type="checkbox"/> No - Fail
<input checked="" type="checkbox"/>	4.	Place any adjustable seat belt anchorage in the lowest adjustment position.
		<input checked="" type="checkbox"/> N/A The anchorage is not adjustable.
<input checked="" type="checkbox"/>	5.	Buckle the seat belt. (S7.1.1.5(c)(1))
<input checked="" type="checkbox"/>	6.	Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))
<input checked="" type="checkbox"/>	7.	Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
<input checked="" type="checkbox"/>	8.	Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?
		<input checked="" type="checkbox"/> Yes, go to 8.1
		<input type="checkbox"/> No, go to 9
<input checked="" type="checkbox"/>	8.1	Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))
		<input checked="" type="checkbox"/> Yes - Pass
		<input type="checkbox"/> No - Fail

- | | |
|---|---|
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin-bottom: 5px;">X</div> | <p>9. Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin-bottom: 5px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin-bottom: 5px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> | <p>10. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
Measured distance between A and B (inches): <u>73 ¼ inches</u></p> <p>11. Readjust the belt system so that the webbing between points A and B is at 1/2 the maximum length of the webbing. (S7.1.1.5(c)(3))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> | <p>12. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
Measured force application angle (Spec. 5-15 degrees): <u>10°</u></p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> | <p>13. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
Measured distance between A and B (inches): <u>36 ¾ inches</u></p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> | <p>14. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> | <p>Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): <u>20lbs/sec</u>
Measured distance between A and B (inches) (S7.1.1.5(c)(6)): <u>37 ½ inches</u></p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> | <p>15. Let the seat belt webbing retract to its minimum length with the seat belt still buckled</p> <p>16. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
Measured force application angle: <u>10°</u> (spec. 5 - 15 degrees)</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> | <p>17. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
Measured distance between A and B: <u>13 inches</u></p> |

- | | |
|--|--|
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin-bottom: 2px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> | <p>18. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
 Record onset rate: <u>20 lb/sec</u> (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
 Measured distance between A and B: <u>13 1/2 inches</u> (S7.1.1.5(c)(6))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin-bottom: 2px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin-bottom: 2px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> | <p>19. Subtract the measurement in 13 from the measurement in 14 and the measurement in 17 from the measurement in 18. Is the difference 2 inches or less for both? (S7.1.1.5(c)(7))
 14-13 = <u>37 1/2 - 36 3/4 = 3/4 inches</u>
 18-17 = <u>13 1/2 - 13 = 1/2 inch</u></p> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin-bottom: 2px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">No - Fail</div> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin-bottom: 2px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin-bottom: 2px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">X</div> | <p>20. Subtract the measurement in 14 from the measurement in 10 and the measurement in 18 from the measurement in 10. Is the difference 3 inches or more for both? (S7.1.1.5(c)(8))
 10-14 = <u>73 1/4 - 37 1/2 = 35 3/4 inches</u>
 10-18 = <u>73 1/4 - 13 1/2 = 59 3/4 inches</u></p> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin-bottom: 2px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px;">No - Fail</div> |

I certify that I have read and performed each instruction.

Signature:

Wayne Gahl

Date:

6/2/08




Figure 5. - Webbing Tension Pull Device

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C85302
Test Date: 6/2/08

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Right Rear Passenger
------------------------------	----------------------

<input type="checkbox"/>		N/A - no retractor is at this position
<input type="checkbox"/>		N/A - the retractor is an automatic locking retractor ONLY
<input checked="" type="checkbox"/>	1.	Record test fore-aft seat position: FIXED (S7.1.1.5(c)(1)) (Any position is acceptable)
<input checked="" type="checkbox"/>	2.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))
<input checked="" type="checkbox"/>		Yes - Pass
<input type="checkbox"/>		No - Fail
<input checked="" type="checkbox"/>	3.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))
<input checked="" type="checkbox"/>		Yes - Pass
<input type="checkbox"/>		No - Fail
<input checked="" type="checkbox"/>	4.	Place any adjustable seat belt anchorage in the lowest adjustment position.
<input checked="" type="checkbox"/>		N/A The anchorage is not adjustable.
<input checked="" type="checkbox"/>	5.	Buckle the seat belt. (S7.1.1.5(c)(1))
<input checked="" type="checkbox"/>	6.	Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))
<input checked="" type="checkbox"/>	7.	Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
<input checked="" type="checkbox"/>	8.	Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?
<input checked="" type="checkbox"/>		Yes, go to 8.1
<input type="checkbox"/>		No, go to 9.
<input checked="" type="checkbox"/>	8.1	Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))
<input checked="" type="checkbox"/>		Yes - Pass
<input type="checkbox"/>		No - Fail

- | | |
|---|--|
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> | <p>9. Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> | <p>10. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> | <p>Measured distance between A and B (inches): <u>68 inches</u></p> <p>11. Readjust the belt system so that the webbing between points A and B is at 1/2 the maximum length of the webbing. (S7.1.1.5(c)(3))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> | <p>12. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> | <p>Measured force application angle (Spec. 5-15 degrees): <u>10°</u></p> <p>13. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> | <p>Measured distance between A and B (inches): <u>30 inches</u></p> <p>14. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> | <p>Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): <u>20 lbs/sec</u></p> <p>Measured distance between A and B (inches) (S7.1.1.5(c)(6)): <u>31 inches</u></p> <p>15. Let the seat belt webbing retract to its minimum length with the seat belt still buckled</p> <p>16. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))</p> |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; margin-bottom: 10px;">X</div> | <p>Measured force application angle: <u>10°</u> (spec. 5 - 15 degrees)</p> <p>17. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))</p> |
| | <p>Measured distance between A and B: <u>10 ½ inches</u></p> |

- ☒ 18. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
Record onset rate 20 lbs/sec (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5))
Measured distance between A and B 11 1/4 inches (S7.1.1.5(c)(6))
- ☒ 19. Subtract the measurement in 13 from the measurement in 14 and the measurement in 17 from the measurement in 18. Is the difference 2 inches or less for both?
(S7.1.1.5(c)(7))
 $14-13 = 31 - 30 = 1 \text{ inch}$
 $18-17 = 11 \frac{1}{4} - 10 \frac{1}{2} = \frac{3}{4} \text{ inch}$
- ☒ Yes – Pass
☐ No – Fail
- ☒ 20. Subtract the measurement in 14 from the measurement in 10 and the measurement in 18 from the measurement in 10. Is the difference 3 inches or more for both?
(S7.1.1.5(c)(8))
 $10-14 = 68 - 31 = 37 \text{ inches}$
 $10-18 = 68 - 11 \frac{1}{4} = 56 \frac{3}{4} \text{ inches}$
- ☒ Yes – Pass
☐ No – Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 6/2/08




Figure 5. - Webbing Tension Pull Device

DATA SHEET 9

FMVSS 208 SEAT BELT WARNING SYSTEM CHECK (S7.3)


Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C85302
 Test Date: 6/2/08

- | | | |
|---|-----|---|
| X | 1. | The occupant is in the driver's seat. |
| X | 2. | The seat belt is in the stowed position. |
| X | 3. | The key is in the "on" or "start" position. |
| X | 4. | The time duration of the audible signal beginning with key "on" or "start" is |
| X | | Seconds: 6 |
| X | 5. | The occupant is in the driver's seat. |
| X | 6. | The seat belt is in the stowed position. |
| X | 7. | The key is in the "on" or "start" position. |
| X | 8. | The time duration of the warning light beginning with key "on" or "start" is |
| X | | Seconds: Stays On |
| X | 9. | The occupant is in the driver's seat. |
| X | 10. | The seat belt is in the latched position and with at least 4 inches of belt webbing extended. |
| X | 11. | The key is in the "on" or "start" position. |
| X | 12. | The time duration of the warning light beginning with key "on" or "start" is |
| X | | Seconds: 0 |
| X | 13. | Complete the following table with the data from 4, 8, and 12 to determine which option is used. |

		Warning light	Warning light specification	Audible signal	Audible signal specification*
S7.3 (a)(1)	Belt stowed & key on or start	Item 8: Stays On	60 seconds minimum	Item 4: 6	4 to 8 seconds
S7.3 (a)(2)	Belt latched & key on or start	Item 12: 0	4 to 8 seconds		
	Belt stowed & key on or start	Item 8: Stays On	4 to 8 seconds	Item 4: 6	4 to 8 seconds

* 49 USCS @ 30124 does NOT allow an audible signal to operate for more than 8 seconds.
 A voluntary audible signal after the 4 to 8 second required signal may be provided. It must be differentiated from the required signal (5/25/2001 legal interpretation to Longacre and Associates).

- ☒ 14. The seat belt warning system meets the requirements of (manufacturers may comply with either section)
- ☒ S7.3 (a)(1)
- ☐ S7.3 (a)(2)
- ☐ FAIL - does not meet the requirements of either option
- ☒ 15. Note wording of visual warning: (S7.3(a)(1) and S7.3(a)(2))
- ☐ Fasten seat belts
- ☐ Fasten belts
- ☒ Symbol 101 - 
- ☐ FAIL - does not use any of the above wording or symbol

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zahl

Date: 6/2/08

DATA SHEET 10

BELT CONTACT FORCE (S7.4.3)

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C85302
 Test Date: 6/2/08

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Left Rear Passenger
------------------------------	---------------------

- | | | | | |
|--|----|---|--|--|
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 1. | Does the vehicle incorporate a webbing tension-relieving device? | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">Yes, this form is complete</div> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X No, continue with this check sheet</div> |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 2. | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3) | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X N/A, no lumbar adjustment</div> |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 3. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2) | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X N/A, no additional support adjustment</div> |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 4. | Is the fore-aft position of the seat adjustable? | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X No- go to 5</div> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">Yes - Put the seat in the mid fore-aft and full down height position determined in Data Sheet 14.2</div> |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 5. | Is the seat back angle adjustable? | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X No- go to 6</div> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">Yes-Use the seat back angle determined in Data Sheet 14.2</div> |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 6. | Position the test dummies according to dummy position placement instructions in Appendix F. Complete the Appendix F check sheets, but include them in the test report ONLY if there is a test failure. | | |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 7. | Fasten the seat belt latch. | | |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 8. | Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest. | | |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 9. | Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing. | | |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | | Contact Force (lb): <u>0.5</u> | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X 0.0 to 0.7 pounds - Pass</div> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">Greater than 0.7 pounds - Fail</div> |

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 6/2/08

DATA SHEET 10

BELT CONTACT FORCE (\$7.4.3)

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C85302
 Test Date: 6/2/08

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Center Rear Passenger
------------------------------	-----------------------

- | | | |
|--|----|---|
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 1. | Does the vehicle incorporate a webbing tension-relieving device? |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;"></div> Yes, this form is complete |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> No, continue with this check sheet |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 2. | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3) |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> N/A, no lumbar adjustment |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 3. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2) |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> N/A, no additional support adjustment |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 4. | Is the fore-aft position of the seat adjustable? |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> No- go to 5 |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;"></div> Yes - Put the seat in the mid fore-aft and full down height position determined in Data Sheet 14.2 |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 5. | Is the seat back angle adjustable? |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> No- go to 6 |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;"></div> Yes-Use the seat back angle determined in Data Sheet 14.2 |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 6. | Position the test dummies according to dummy position placement instructions in Appendix F. Complete the Appendix F check sheets, but include them in the test report ONLY if there is a test failure. |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 7. | Fasten the seat belt latch. |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 8. | Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest. |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 9. | Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing. |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | | Contact Force (lb): <u>0.6</u> |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> 0.0 to 0.7 pounds - Pass |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;"></div> Greater than 0.7 pounds - Fail |

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zable

Date: 6/2/08

DATA SHEET 10
BELT CONTACT FORCE (S7.4.3)

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C85302
 Test Date: 6/2/08

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Right Rear Passenger
------------------------------	----------------------

- | | | |
|--|----|---|
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 1. | Does the vehicle incorporate a webbing tension-relieving device? |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; display: inline-block;"> </div> Yes, this form is complete |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; display: inline-block;">X</div> No, continue with this check sheet |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 2. | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3) |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; display: inline-block;">X</div> N/A, no lumbar adjustment |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 3. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2) |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; display: inline-block;">X</div> N/A, no additional support adjustment |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 4. | Is the fore-aft position of the seat adjustable? |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; display: inline-block;">X</div> No- go to 5 |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; display: inline-block;"> </div> Yes – Put the seat in the mid fore-aft and full down height position determined in Data Sheet 14.2 |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 5. | Is the seat back angle adjustable? |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; display: inline-block;">X</div> No- go to 6 |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; display: inline-block;"> </div> Yes-Use the seat back angle determined in Data Sheet 14.2 |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 6. | Position the test dummies according to dummy position placement instructions in Appendix F. Complete the Appendix F check sheets, but include them in the test report ONLY if there is a test failure. |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 7. | Fasten the seat belt latch. |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 8. | Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest. |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | 9. | Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing. |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; margin: 0 auto;">X</div> | | Contact Force (lb): <u>0.5</u> |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; display: inline-block;">X</div> 0.0 to 0.7 pounds – Pass |
| | | <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 20px; display: inline-block;"> </div> Greater than 0.7 pounds - Fail |

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 6/2/08

DATA SHEET 11

LATCH PLATE ACCESS (S7.4.4)

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C85302
 Test Date: 6/2/08

Test all front outboard seat belts **other than those in** walk-in van-type vehicles and those at front outboard designated seating positions in **passenger cars**. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Not Applicable For Any Position - Passenger Car
------------------------------	---

- | | | |
|---|-----|--|
| <input style="width: 30px; height: 20px;" type="checkbox"/> | 1. | Put the seat in the forwardmost fore-aft and full down height position determined in Data Sheet 14.2. (S10.7) |
| <input style="width: 30px; height: 20px;" type="checkbox"/> | 2. | Put the seat back angle in the position determined in Data Sheet 14.2. |
| <input style="width: 30px; height: 20px;" type="checkbox"/> | 3. | Position the test dummy using the procedures in Appendix F. (Some modifications to the positioning procedure may need to be made because the seat is in its forward most position. Note on the Appendix F positioning check sheet any deviations necessary to position the Part 572, Subpart E dummy.) Complete the Appendix F check sheets, but include them in the test report ONLY if there is a test failure. |
| <input style="width: 30px; height: 20px;" type="checkbox"/> | 4. | Position the adjustable seat belt anchorage in the manufacturer's nominal design position for a 50 th percentile adult male occupant. |
| <input style="width: 30px; height: 20px;" type="checkbox"/> | 5. | Attach the inboard reach string to the base of the head following the instructions on Figure 3. |
| <input style="width: 30px; height: 20px;" type="checkbox"/> | 6. | Attach the outboard reach string to the torso sheath following the instructions on Figure 3. |
| <input style="width: 30px; height: 20px;" type="checkbox"/> | 7. | Place the latch plate in the stowed position. |
| <input style="width: 30px; height: 20px;" type="checkbox"/> | 8. | Extend inboard reach string in front of the dummy and then backward and outboard to the latch plate to generate an arc of the reach envelope of the test dummy's arms. Is the latch plate within the reach envelope? |
| | | <input style="width: 30px; height: 20px;" type="checkbox"/> Yes - Pass |
| | | <input style="width: 30px; height: 20px;" type="checkbox"/> No |
| <input style="width: 30px; height: 20px;" type="checkbox"/> | 9. | Extend outboard reach string in front of the dummy and then backward and outboard to the latch plate to generate arcs of the reach envelope of the test dummy's arms. Is the latch plate within the reach envelope? |
| | | <input style="width: 30px; height: 20px;" type="checkbox"/> Yes - Pass |
| | | <input style="width: 30px; height: 20px;" type="checkbox"/> No |
| <input style="width: 30px; height: 20px;" type="checkbox"/> | 10. | Is the latch plate within the inboard (item 10) or outboard (item 11) reach envelope? |
| | | <input style="width: 30px; height: 20px;" type="checkbox"/> Yes - Pass |
| | | <input style="width: 30px; height: 20px;" type="checkbox"/> No - Fail |
| <input style="width: 30px; height: 20px;" type="checkbox"/> | 11. | Using the clearance test block, specified in Figure 4, is there sufficient clearance between the vehicle seat and the side of vehicle interior to allow the test block to move unhindered to the latch plate or buckle? |
| | | <input style="width: 30px; height: 20px;" type="checkbox"/> Yes - Pass |
| | | <input style="width: 30px; height: 20px;" type="checkbox"/> No - Fail |




Figure 3. Location of Anchoring Points for Latchplate Reach Limiting Chains or Strings to Test for Latchplate Accessibility Using Subpart E Test Device




Figure 4—USE OF CLEARANCE TEST BLOCK TO DETERMINE HAND/ARM ACCESS

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zahle

Date: 6/2/08

DATA SHEET 12

SEAT BELT RETRACTION (S7.4.5)

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C85302
 Test Date: 6/2/08

Test all front outboard seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Not Applicable For Any Position - Passenger Car
------------------------------	---

<input checked="" type="checkbox"/>		1.	Is the vehicle a passenger car or walk-in van-type vehicle?
			<input checked="" type="checkbox"/> Yes, this form is complete
			<input type="checkbox"/> No
<input type="checkbox"/>		2.	Put the seat in the mid fore-aft and full down height position determined in Data Sheet 14.2. (S8.1.2)
<input type="checkbox"/>		3.	Put the seat back angle in the position determined in Data Sheet 14.2. (8.1.3)
<input type="checkbox"/>		4.	Position the Part 572 Subpart E test dummy according to dummy position placement instructions in Appendix F. Complete the Appendix F check sheets, but include them in the test report ONLY if there is a test failure.
<input type="checkbox"/>		5.	Fasten the seat belt around the dummy.
<input type="checkbox"/>		6.	Remove all slack from the lap belt portion. (S10.9)
			<input type="checkbox"/> N/A, the seat does not have a fore-aft adjustment
<input type="checkbox"/>		7.	Pull the upper torso webbing out of the retractor and allow it to retract; repeat this four times. (S10.9)
<input type="checkbox"/>		8.	Apply a 2 to 4 pound tension load to the lap belt. (S10.9)
<input type="checkbox"/>			Pound load applied:
<input type="checkbox"/>		9.	Is the belt system equipped with a tension relieving device?
			<input type="checkbox"/> Yes, continue
			<input type="checkbox"/> No, go to 12
<input type="checkbox"/>		10.	Introduce the maximum amount of slack into the upper torso belt that is recommended by the vehicle manufacturer in the vehicle owner's manual. (S10.9).
<input type="checkbox"/>		11.	Check the statement that applies to this test vehicle:
<input type="checkbox"/>		11.1	The torso and lap belt webbing of the seat belt system automatically retracts to a stowed position when the adjacent vehicle door is in an open position and the seat belt latch plate is released.
			<input type="checkbox"/> Yes - Pass go to 12
			<input type="checkbox"/> No - go to 11.2
		11.2	The torso and lap belt webbing of the seat belt system automatically retracts when the seat belt latch plate is released.
			<input type="checkbox"/> Yes - Pass go to 12
			<input type="checkbox"/> No - go to 11.3
		11.3	Neither 11.1 nor 11.2 apply.
			<input type="checkbox"/> Fail

- ☐ 12. With the webbing and hardware in the stowed position are the webbing and hardware prevented from being pinched when the door is closed?
- ☐ Yes - Pass
- ☐ No - Fail
- ☐ 13. If this test vehicle has an open body (without doors) and has a belt system with a tension-relieving device, does the belt system fully retract when the tension-relieving device is deactivated?
- ☐ N/A - Not an open body vehicle
- ☐ Yes - Pass
- ☐ No - Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 6/2/08

DATA SHEET 13

SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C85302
 Test Date: 6/2/08

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION: **Left Rear Passenger**

- | | | |
|-------------------------------------|----|--|
| <input checked="" type="checkbox"/> | 1. | Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1 (b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 2 |
| <input checked="" type="checkbox"/> | 2. | Is the seat removable? (S7.4.6.1(b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 3 |
| <input checked="" type="checkbox"/> | 3. | Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 4 |
| <input checked="" type="checkbox"/> | 4. | Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a)) |
| | | <input checked="" type="checkbox"/> Yes, go to 5 |
| | | <input type="checkbox"/> No, this form is complete |
| <input checked="" type="checkbox"/> | 5. | Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a)) |
| | | <input checked="" type="checkbox"/> Yes - Pass |
| | | <input type="checkbox"/> No - Fail |
| | | Identify the part(s) on top or above the seat. |
| | | <input checked="" type="checkbox"/> Seat belt latch plate |
| | | <input checked="" type="checkbox"/> Buckle |
| | | <input checked="" type="checkbox"/> Seat belt webbing |
| <input checked="" type="checkbox"/> | 6. | Are the remaining two seat belt parts accessible under normal conditions? |
| | | <input checked="" type="checkbox"/> Yes - Pass |
| | | <input type="checkbox"/> No - Fail |
| <input checked="" type="checkbox"/> | 7. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2) |
| | | <input checked="" type="checkbox"/> Yes - Pass |
| | | <input type="checkbox"/> No - Fail |

- ☒ 8. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2)
- ☒ Yes - Pass
☐ No - Fail
- ☒ 9. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2)
- ☒ Yes - Pass
☐ No - Fail
- ☒ 10. Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2)
- ☐ Yes - Pass
☐ No - Fail
☒ N/A - Rear seat

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 6/2/08

DATA SHEET 13

SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C85302
 Test Date: 6/2/08

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Center Rear Passenger
------------------------------	-----------------------

- | | | |
|--|----|--|
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 1. | Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1 (b))
<div style="margin-left: 20px;"> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;"></div> Yes, this form is complete
 <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;">X</div> No, go to 2 </div> |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 2. | Is the seat removable? (S7.4.6.1(b))
<div style="margin-left: 20px;"> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;"></div> Yes, this form is complete
 <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;">X</div> No, go to 3 </div> |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 3. | Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b))
<div style="margin-left: 20px;"> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;"></div> Yes, this form is complete
 <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;">X</div> No, go to 4 </div> |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 4. | Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a))
<div style="margin-left: 20px;"> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;">X</div> Yes, go to 5
 <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;"></div> No, this form is complete </div> |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 5. | Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a))
<div style="margin-left: 20px;"> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;">X</div> Yes - Pass
 <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;"></div> No - Fail
 Identify the part(s) on top or above the seat.
 <div style="margin-left: 20px;"> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;">X</div> Seat belt latch plate
 <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;">X</div> Buckle
 <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;">X</div> Seat belt webbing </div> </div> |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 6. | Are the remaining two seat belt parts accessible under normal conditions?
<div style="margin-left: 20px;"> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;">X</div> Yes - Pass
 <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;"></div> No - Fail </div> |
| <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; margin: 0 auto;">X</div> | 7. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2)
<div style="margin-left: 20px;"> <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;">X</div> Yes - Pass
 <div style="background-color: yellow; border: 1px solid black; padding: 2px; width: 30px; display: inline-block;"></div> No - Fail </div> |

- ☒ 8. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2)
- ☒ Yes - Pass
☐ No - Fail
- ☒ 9. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2)
- ☒ Yes - Pass
☐ No - Fail
- ☒ 10. Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2)
- ☐ Yes - Pass
☐ No - Fail
☒ N/A - Rear seat

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 6/2/08

DATA SHEET 13

SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C85302
 Test Date: 6/2/08

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION: **Right Rear Passenger**

- X

1. Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1 (b))

Yes, this form is complete

X

 No, go to 2
- X

2. Is the seat removable? (S7.4.6.1(b))

Yes, this form is complete

X

 No, go to 3
- X

3. Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b))

Yes, this form is complete

X

 No, go to 4
- X

4. Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a))

X

 Yes, go to 5
 No, this form is complete
- X

5. Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a))

X

 Yes - Pass
 No - Fail

Identify the part(s) on top or above the seat.

X

 Seat belt latch plate

X

 Buckle

X

 Seat belt webbing
- X

6. Are the remaining two seat belt parts accessible under normal conditions?

X

 Yes - Pass
 No - Fail
- X

7. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2)

X

 Yes - Pass
 No - Fail

- ☒ 8. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2)
- ☒ Yes - Pass
☐ No - Fail
- ☒ 9. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2)
- ☒ Yes - Pass
☐ No - Fail
- ☒ 10. Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2)
- ☐ Yes - Pass
☐ No - Fail
☒ N/A - Rear seat

REMARKS:

I certify that I have read and performed each instruction.

Signature: Wayne J. Ahl

Date: 6/2/08

DATA SHEET 14

MARKING OF REFERENCE POINTS FOR VARIOUS TEST POSITIONS AND POINTS

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C85302
Test Date: 7/7/08

DATA SHEET 14.1

MARKING OF REFERENCE POINTS FOR 5th FEMALE

☒ Driver Seat ☐ Passenger Seat

1. Seat Position

- ☒ 1.1 Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment positions. (S16.2.10.1, S20.1.9.1, S20.4.1, S22.1.7.1)
☐ N/A - No lumbar adjustment
- ☒ 1.2 Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2, S20.1.9.2, S20.4.1, S22.1.7.1, S22.4.2.1, S22.4.3.1, S24.4.2.1, S26.2.3, S26.3.1)
☒ N/A - No additional support adjustment
- ☒ 1.3 Position an adjustable leg support system in its rearmost position. (8/27/04 interpretation to Toyota)
☒ N/A - No adjustable leg support system
- ☒ 1.4 **Mark** a point (seat cushion reference point) on the side of the seat cushion that is between 150 mm and 250 mm from the front edge of the seat cushion. (S16.3.1.12)
- ☒ 1.5 Draw a line (seat cushion reference line) through the seat cushion reference point. (S16.3.1.13)
- ☒ 1.6 Use only the controls that primarily move the seat in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S22.1.7.3)
- ☒ 1.7 If the seat cushion adjusts fore-aft, independent of the seat back, use only the controls that primarily move the seat cushion in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S20.1.9.3)
☒ N/A - No independent fore-aft seat cushion adjustment
- ☒ 1.8 Use any part of any control, other than the parts just used for fore-aft positioning, to determine the range of angles of the seat cushion reference line and to set the seat cushion reference line at the mid-angle. (S16.2.10.3.1)
Maximum angle 7.0°
Minimum angle Zero
Mid-angle 3.5°
- ☒ 1.9 If the seat and/or seat cushion height is adjustable, use any part of any control other than the parts which primarily move the seat or seat cushion fore-aft, to put the seat cushion reference point in its lowest position with the seat cushion reference line angle at the mid-angle found in 1.8. (S16.2.10.3.1)
☐ N/A - No seat height adjustment
- ☒ 1.10 Use only the controls that primarily move the seat in the fore-aft direction to verify the seat is in the rearmost position.

- ☒ 1.11 Use only the controls that primarily move the seat in the fore-aft direction to **mark** for future reference the fore-aft seat positions. **Mark** each position so that there is a visual indication when the seat is at a particular position. For manual seats, move the seat forward one detent at a time and **mark** each detent. For power seats, **mark** only the rearmost, middle, and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost.
- ☒ 1.12 Use only the controls that primarily move the seat in the fore-aft direction to place the seat in the rearmost position.
- ☒ 1.13 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S22.4.3.1, S24.1.2, S24.3.1, S24.4.3.1, S26.2.3, S26.3.1)
☐ N/A - No seat height adjustment. Go to 1.18
- ☒ 1.14 Use only the controls that primarily move the seat and/or seat cushion in the fore-aft direction to place the seat in the mid-fore-aft position.
- ☒ 1.15 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)
- ☒ 1.16 Use only the control that change the seat in the fore-aft direction to place the seat in the foremost position. (S16.2.10.3.2)
- ☒ 1.17 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S16.2.10.3.3, S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)
- ☒ 1.18. Visually **mark** for future reference the seat back angle at the manufacturer's nominal design riding position for a **50th percentile adult male** in the manner specified by the manufacturer for the rearmost, mid, and foremost seat positions. (S20.1.9.5, S22.1.7.5, S22.4.2.1, S22.4.3.1, S24.1.2, S24.4.2.1, S26.2.3, S26.3.1)
☐ N/A - No seat back angle adjustment
 Manufacturer's design seat back angle 4th Detent from forward most locking
- ☒ 1.19. Is the seat a bucket seat?
☒ Yes, go to 1.20 and skip 1.21
☐ No, go to 1.21 and skip 1.20
- ☒ 1.20 Bucket seats:
 Locate and **mark** for future reference the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline of a bucket seat cushion. (S16.3.1.10 & S20.1.10)
- ☐ 1.21 Bench seats (complete ONLY the one that is applicable to the seat being marked):
☐ 1.21.1 Driver Seat
 Locate and **mark** for future reference the longitudinal line on the seat cushion that marks the intersection of the vertical longitudinal plane through the centerline of the steering wheel and the seat cushion upper surface.

___ 1.21.2 Passenger Seat

Locate and **mark** for future reference the longitudinal centerline of the passenger seat cushion. The longitudinal centerline is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel. (S20.2.1.3, S22.2.1.3, S24.2.3, S20.4.4, S22.2.2.1(b), S22.2.2.3(b), S22.2.2.4(a), S22.2.2.5(a), S22.2.2.6(a), S22.2.2.7(a), S24.2.3(a))

Record the distance from the longitudinal centerline of the vehicle to the center of the steering wheel. _____

Record the distance from the longitudinal centerline of the vehicle to the longitudinal centerline of the seat cushion. (The vertical plane through this longitudinal centerline is Plane B for suppression.) _____

2. Head Restraint Position

___ N/A Vehicle contains automatic head restraints.

___ N/A, there is no head restraint adjustment

☒ 2.1 Adjust the head restraint to its lowest position. (S16.2.10.2, S20.1.9.6 S20.4.1, S22.1.7.6, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)

☒ 2.2 All adjustments of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible. **Mark** the foremost position. (S16.2.10.2 & S16.3.4.4 & S20.1.9.6, S20.4.1, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)

☒ 2.3 Measure the vertical distance from the top most point of the head restraint to the bottom most point. Locate and **mark** a horizontal plane through the midpoint of this distance. (S16.3.4.3)

Vertical height of head restraint 205 mm

Mid-point height 102 mm

Wayne J. Ahl
I certify that I have read and performed each instruction.

7/7/08
Date

DATA SHEET 14.1

MARKING OF REFERENCE POINTS FOR 5th FEMALE

☐ Driver Seat ☒ Passenger Seat

1. Seat Position

- ☒ 1.1 Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment positions. (S16.2.10.1, S20.1.9.1, S20.4.1, S22.1.7.1)
☒ N/A - No lumbar adjustment
- ☒ 1.2 Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2, S20.1.9.2, S20.4.1, S22.1.7.1, S22.4.2.1, S22.4.3.1, S24.4.2.1, S26.2.3, S26.3.1)
☒ N/A - No additional support adjustment
- ☒ 1.3 Position an adjustable leg support system in its rearmost position. (8/27/04 interpretation to Toyota)
☒ N/A - No adjustable leg support system
- ☒ 1.4 **Mark** a point (seat cushion reference point) on the side of the seat cushion that is between 150 mm and 250 mm from the front edge of the seat cushion. (S16.3.1.12)
- ☒ 1.5 Draw a line (seat cushion reference line) through the seat cushion reference point. (S16.3.1.13)
- ☒ 1.6 Use only the controls that primarily move the seat in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S22.1.7.3)
- ☒ 1.7 If the seat cushion adjusts fore-aft, independent of the seat back, use only the controls that primarily move the seat cushion in the fore-aft direction to move the seat cushion reference point to the rearmost position. (S16.2.10.3.1, S20.1.9.3)
☐ N/A - No independent fore-aft seat cushion adjustment
- ☒ 1.8 Use any part of any control, other than the parts just used for fore-aft positioning, to determine the range of angles of the seat cushion reference line and to set the seat cushion reference line at the mid-angle. (S16.2.10.3.1) NO ADJUSTMENT
Maximum angle: Zero
Minimum angle: Zero
Mid-angle: Zero
- ☒ 1.9 If the seat and/or seat cushion height is adjustable, use any part of any control other than the parts which primarily move the seat or seat cushion fore-aft, to put the seat cushion reference point in its lowest position with the seat cushion reference line angle at the mid-angle found in 1.8. (S16.2.10.3.1)
☒ N/A - No seat height adjustment
- ☒ 1.10 Use only the controls that primarily move the seat in the fore-aft direction to verify the seat is in the rearmost position.
- ☒ 1.11 Use only the controls that primarily move the seat in the fore-aft direction to **mark** for future reference the fore-aft seat positions. **Mark** each position so that there is a visual indication when the seat is at a particular position. For manual seats, move the seat forward one detent at a time and **mark** each detent. For power seats, **mark** only the rearmost, middle, and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost.
- ☒ 1.12 Use only the controls that primarily move the seat in the fore-aft direction to place the seat in the rearmost position.

- ☒ 1.13 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S22.4.3.1, S24.1.2, S24.3.1, S24.4.3.1, S26.2.3, S26.3.1)
☒ N/A - No seat height adjustment. Go to 1.18
- ☐ 1.14 Use only the controls that primarily move the seat and/or seat cushion in the fore-aft direction to place the seat in the mid-fore-aft position.
- ☐ 1.15 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)
- ☐ 1.16 Use only the control that change the seat in the fore-aft direction to place the seat in the foremost position. (S16.2.10.3.2)
- ☐ 1.17 Use any part of any control, other than the parts which primarily move the seat or seat cushion fore-aft, to find and visually **mark** for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.8. (S16.2.10.3.3, S20.1.9.4, S22.1.2, S22.1.7.4, S22.3.1, S24.1.2, S24.3.1)
- ☒ 1.18. Visually **mark** for future reference the seat back angle at the manufacturer's nominal design riding position for a **50th percentile adult male** in the manner specified by the manufacturer for the rearmost, mid, and foremost seat positions. (S20.1.9.5, S22.1.7.5, S22.4.2.1, S22.4.3.1, S24.1.2, S24.4.2.1, S26.2.3, S26.3.1)
☐ N/A - No seat back angle adjustment
 Manufacturer's design seat back angle 4th Detent from forward most locking
- ☒ 1.19. Is the seat a bucket seat?
☒ Yes, go to 1.20 and skip 1.21
☐ No, go to 1.21 and skip 1.20
- ☒ 1.20 Bucket seats:
 Locate and **mark** for future reference the longitudinal centerline of the seat cushion. The intersection of the vertical longitudinal plane that passes through the SgRP and the seat cushion upper surface determines the longitudinal centerline of a bucket seat cushion. (S16.3.1.10 & S20.1.10)
- ☐ 1.21 Bench seats (complete ONLY the one that is applicable to the seat being marked):
- ☐ 1.21.1 Driver Seat
 Locate and **mark** for future reference the longitudinal line on the seat cushion that marks the intersection of the vertical longitudinal plane through the centerline of the steering wheel and the seat cushion upper surface.
- ☐ 1.21.2 Passenger Seat
 Locate and **mark** for future reference the longitudinal centerline of the passenger seat cushion. The longitudinal centerline is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel. (S20.2.1.3, S22.2.1.3, S24.2.3, S20.4.4, S22.2.2.1(b), S22.2.2.3(b), S22.2.2.4(a), S22.2.2.5(a), S22.2.2.6(a), S22.2.2.7(a), S24.2.3(a))
 Record the distance from the longitudinal centerline of the vehicle to the center of the steering wheel. _____
 Record the distance from the longitudinal centerline of the vehicle to the longitudinal centerline of the seat cushion. (The vertical plane through this longitudinal centerline is Plane B for suppression.) _____

2. Head Restraint Position

☐ N/A Vehicle contains automatic head restraints.

☐ N/A, there is no head restraint adjustment

☒ 2.1 Adjust the head restraint to its lowest position. (S16.2.10.2, S20.1.9.6 S20.4.1, S22.1.7.6, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)

☒ 2.2 All adjustments of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible. **Mark** the foremost position. (S16.2.10.2 & S16.3.4.4 & S20.1.9.6, S20.4.1, S22.4.2.1, S22.4.3.1, S24.4.3.1, S26.2.3, S26.3.1)

☒ 2.3 Measure the vertical distance from the top most point of the head restraint to the bottom most point. Locate and **mark** a horizontal plane through the midpoint of this distance. (S16.3.4.3)

Vertical height of head restraint 205 mm

Mid-point height 102 mm



I certify that I have read and performed each instruction.

6/6/08

Date

DATA SHEET 14.3

MARKING OF REFERENCE POINTS FOR STEERING WHEEL

- X 1. Is the steering wheel adjustable up and down and/or in and out?
X Yes - go to 2
___ No - this form is complete
- X 2. Find and **mark** for future reference each up and down position. Label three of the positions with the following: H for Top of 4, M for mid-position (if there is no mid-position, label the next lowest adjustment position), and L for lowest.
___ N/A - steering wheel is not adjustable up and down
- X 3. Find and **mark** for future references each in and out position. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the next rearmost adjustment position), and R for rearmost.
___ N/A - steering wheel is not adjustable in and out.

Wayne Zahle

I certify that I have read and performed each instruction.

7/7/08

Date

DATA SHEET 14.4

MARKING OF REFERENCE POINTS FOR DRIVER LOW RISK DEPLOYMENT

X Position 1 X Position 2

- X 1. Position the steering wheel so the front wheels are in the straight-ahead position. (S26.2.1)
- X 2. Position any adjustable parts of the steering controls to the mid-position as determined in Data Sheet 14.3 above. If a mid-position adjustment is not achievable, position the controls to the next lowest detent position. (S26.2.1)
- X 3. Locate and **mark** the point that is defined by the intersection of the steering wheel cover and a line between the volumetric center of the smallest volume that can encompass the folded undeployed air bag and the volumetric center of the static fully inflated air bag. The vertical plane parallel to the vehicle longitudinal centerline through this point is referred to as "Plane E." (Check determination method below.) (S26.2.2)
Measurements with respect to measurement reference points:

The longitudinal centerline of the air bag was used.

__ Point determined using manufacturer's information supplied by the COTR .
(Include manufacturer's information in the test report.)

OR

X Point determined by test lab personnel and approved by the COTR.
(Include supporting documentation in the test report.)

- X 4. Locate the Top of 4 point of the air bag module cover. The horizontal plane through this point is referred to as "Plane F." (Check determination method below.) (S26.2.6)
Measurements with respect to measurement reference points:

The top of the air bag module cover was used.

__ Point determined using manufacturer's information supplied by the COTR .
(Include manufacturer's information in the test report.)

OR

X Point determined by test lab personnel and approved by the COTR.
(Include manufacturer's information in the test report.)

Wayne Zahler

I certify that I have read and performed each instruction.

7/7/08

Date

DATA SHEET 14.5

MARKING OF REFERENCE POINTS FOR PASSENGER LOW RISK DEPLOYMENT

X Position 1 X Position 2

- X Locate and **mark** the point that is defined by the intersection of the instrument panel and a line between the volumetric center of the smallest volume that can encompass the folded undeployed air bag and the volumetric center of the static fully inflated air bag. (S22.4.1.2, S24.4.1.2) The horizontal plane thru this point is referred to as "Plane C" (S22.4.1.4 and S24.4.1.4). The vertical plane parallel to the vehicle longitudinal centerline and through this point is referred to as "Plane D" (S22.4.1.3 and S24.4.1.3). (Check determination method below.)
Measurements with respect to measurement reference points:
-
-

- X Point determined using manufacturer's information supplied by the COTR .
(Include manufacturer's information in the test report.) See Appendix D-27
OR
___ Point determined by test lab personnel and approved by the COTR.
(Include manufacturer's information in the test report.)

Wayne Stahl
I certify that I have read and performed each instruction.

7/7/08
Date

DATA SHEET 16

AIR BAG SUPPRESSION TELLTALE (S19.2.2)

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C85302
Test Date: 6/6/08

- ☒ 1. Is the vehicle certified to any suppression performance standards of FMVSS 208?
☒ Yes - go to 2
☐ No - this form is complete
- ☒ 2. Does telltale emit yellow light when the air bag is suppressed? (S19.2.2(a))
☒ Yes - Pass **NO - FAIL**
- ☒ 3. Are the words "PASSENGER AIR BAG OFF" or "PASS AIR BAG OFF" (S19.2.2(b))
☒ 3.1 on the telltale? (S19.2.2(b))
☒ Yes - Pass, go to 4
☐ No - go to 3.2
- ☐ 3.2 Within 25 mm of the telltale? (S19.2.2(b)) _____ mm from the edge of the telltale light
☐ Yes - Pass **NO - FAIL**
- ☒ 4. Is the telltale separate from the air bag readiness indicator? (S19.2.2(c))
☒ Yes - Pass **NO - FAIL**
- ☒ 5. Is the telltale within the interior of the vehicle? (S19.2.2(d))
☒ Yes - Pass **NO - FAIL**
- ☒ 6. Is the telltale forward of and above the design H-point of both the driver's and the front outboard passenger's seat when the seats are in their forwardmost seating positions? (S19.2.2(d))
☒ Yes - Pass **NO - FAIL**
- ☒ 7. Is the telltale away from surfaces that can be used for temporary or permanent storage of objects that could obscure the telltale from either the driver's or front outboard passenger's view? (S19.2.2(d))
☒ Yes - Pass **NO - FAIL**
- ☒ 8. Is the telltale located so that it is not obscured from the driver or front outboard passenger by a rear-facing child restraint in Appendix A installed in the front outboard passenger seat? (S19.2.2(d))
☒ Yes - Pass **NO - FAIL**
- ☒ 9. Is the telltale visible or recognizable during the night? (S19.2.2(e))
☒ Yes - Pass **NO - FAIL**
- ☒ 10. Is the telltale visible or recognizable during the day? (S19.2.2(e))
☒ Yes - Pass **NO - FAIL**
- ☒ 11. If there is a visibility adjustment, do all the adjustment levels make the telltale visible and recognizable? (S19.2.2(g))
☒ N/A-No visibility adjustment
☐ Yes - Pass **NO - FAIL**
- ☒ 12. Does the telltale remain illuminated while the air bag is suppressed? (S19.2.2(h)) (Leave the air bag suppressed for 5 minutes.)
☒ Yes - Pass **NO - FAIL**
- ☒ 13. Is the telltale off while the air bag is activated? (S19.2.2(h)) (Leave the air bag activated for 5 minutes.)
☒ Yes - Pass **NO - FAIL**

Wayne Dahlke
I certify that I have read and performed each instruction.

6/6/08
Date

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section B Rear Facing CRS

NHTSA NO.:	C85302	TEST DATE:	6/6/08
LABORATORY:	MGA	TECHNICIANS:	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Britax
CHILD RESTRAINT MODEL:	Handle With Care 191
DATE OF MANUFACTURE:	5-26-2000

Base: __On __Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 4th Detent from forward most locking
Tested seat back angle: 4th Detent from forward most locking
Manufacturer's specified anchorage position: Top/Highest
Tested anchorage position: Top/Highest

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Rear Facing	Forward 4 *	132	Suppressed
	Middle	130	Suppressed
	Rearward	127	Suppressed
Unbelted Rear Facing	Forward 5 *	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Forward Facing	Forward 6 *	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 25 = Full Rearward; 25 total Seat Slide detents)

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Forward position. (SN506)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section B Rear Facing CRS

NHTSA NO.:	C85302	TEST DATE:	6/6/08
LABORATORY:	MGA	TECHNICIANS:	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Evenflo
CHILD RESTRAINT MODEL:	First Choice 204
DATE OF MANUFACTURE:	6-20-2000

Base: __On __Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 4th Detent from forward most locking
 Tested seat back angle: 4th Detent from forward most locking
 Manufacturer's specified anchorage position: Top/Highest
 Tested anchorage position: Top/Highest

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Rear Facing	Forward	N/A	Won't Fit
	Middle	130	Suppressed
	Rearward	127	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Forward Facing	Forward 6 *	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 25 = Full Rearward; 25 total Seat Slide detents)

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section B Rear Facing CRS

NHTSA NO.:	C85302	TEST DATE:	6/6/08
LABORATORY:	MGA	TECHNICIANS:	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Graco
CHILD RESTRAINT MODEL:	Infant 8457
DATE OF MANUFACTURE:	8-31-2000

Base: ☒ On ☐ Off ☐ N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 4th Detent from forward most locking
 Tested seat back angle: 4th Detent from forward most locking
 Manufacturer's specified anchorage position: Top/Highest
 Tested anchorage position: Top/Highest

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Rear Facing	Forward 5 *	133	Suppressed
	Middle	131	Suppressed
	Rearward	130	Suppressed
Unbelted Rear Facing	Forward 7 *	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Forward Facing	Forward 6 *	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 25 = Full Rearward; 25 total Seat Slide detents)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section B Rear Facing CRS

NHTSA NO.:	C85302	TEST DATE:	6/6/08
LABORATORY:	MGA	TECHNICIANS:	WD
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Graco
CHILD RESTRAINT MODEL:	Infant 8457
DATE OF MANUFACTURE:	8-31-2000

Base: ☐ On ☒ Off ☐ N/A-Constraint does not have a removable base

Manufacturer's design seat back angle: 4th Detent from forward most locking
Tested seat back angle: 4th Detent from forward most locking
Manufacturer's specified anchorage position: Top/Highest
Tested anchorage position: Top/Highest

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Rear Facing	Forward 10 *	130	Suppressed
	Middle	130	Suppressed
	Rearward	127	Suppressed
Unbelted Rear Facing	Forward	N/A	Won't Fit
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Unbelted Forward Facing	Forward 3 *	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 25 = Full Rearward; 25 total Seat Slide detents)

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN506)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section C Forward Facing Convertible CRS

NHTSA NO.:	C85302	TEST DATE:	6/10/08
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Britax
CHILD RESTRAINT MODEL:	Roundabout 161
DATE OF MANUFACTURE:	7-21-2000

Base: __On __Off X N/A-Constraint does not have a removable base

Manufacturer's design seat back angle: 4th Detent from forward most locking
Tested seat back angle: 4th Detent from forward most locking
Manufacturer's specified anchorage position: Top/Highest
Tested anchorage position: Top/Highest

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing	Forward	133	Suppressed
	Middle	129	Suppressed
	Rearward	129	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Belted Rear Facing	Forward	130	Suppressed
	Middle	127	Suppressed
	Rearward	127	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Forward position. (SN506)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section C Forward Facing Convertible CRS

NHTSA NO.:	C85302	TEST DATE:	6/10/08
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Century
CHILD RESTRAINT MODEL:	Encore 4612
DATE OF MANUFACTURE:	8-16-2000

Base: __On __Off X N/A-Constraint does not have a removable base

Manufacturer's design seat back angle: 4th Detent from forward most locking
Tested seat back angle: 4th Detent from forward most locking
Manufacturer's specified anchorage position: Top/Highest
Tested anchorage position: Top/Highest

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing	Forward	130	Suppressed
	Middle	130	Suppressed
	Rearward	131	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Belted Rear Facing	Forward 4 *	127	Suppressed
	Middle	131	Suppressed
	Rearward	131	Suppressed
Unbelted Rear Facing	Forward 6 *	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 25 = Full Rearward; 25 total Seat Slide detents)

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

DATA SHEET 17 SUMMARY

Suppression Test Using 12-Month-Old CRABI Dummy (Part 572, Subpart R) Section C Forward Facing Convertible CRS

NHTSA NO.:	C85302	TEST DATE:	6/10/08
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	062

CHILD RESTRAINT NAME:	Evenflo
CHILD RESTRAINT MODEL:	Medallion 254
DATE OF MANUFACTURE:	6-1-2000

Base: ☐ On ☐ Off ☒ N/A-Constraint does not have a removable base

Manufacturer's design seat back angle: 4th Detent from forward most locking
 Tested seat back angle: 4th Detent from forward most locking
 Manufacturer's specified anchorage position: Top/Highest
 Tested anchorage position: Top/Highest

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing	Forward	130	Suppressed
	Middle	133	Suppressed
	Rearward	129	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Belted Rear Facing	Forward 3 *	127	Suppressed
	Middle	132	Suppressed
	Rearward	132	Suppressed
Unbelted Rear Facing	Forward 5 *	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 25 = Full Rearward; 25 total Seat Slide detents)

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN506)

DATA SHEET 18 SUMMARY

Suppression Test Using Newborn Infant Dummy (Part 572, Subpart K) Section A Car Bed

NHTSA NO.:	C85302	TEST DATE:	6/6/08
LABORATORY:	MGA	TECHNICIANS:	WD
DUMMY TYPE:	Newborn Infant	DUMMY SERIAL NO.:	003

CAR BED NAME:	Cosco
CAR BED MODEL:	Dream Ride 02-719
DATE OF MANUFACTURE:	6-16-2000

Base: ☐ On ☐ Off ☒ N/A-Constraint does not have a removable base
(A car bed with a removable base shall be treated as two separate models, i.e. this form and test procedure will be completed with the base on and then repeated on a new form with the base off.)

Manufacturer's design seat back angle: 4th Detent from forward most locking
Tested seat back angle: 4th Detent from forward most locking
Manufacturer's specified anchorage position: Top/Highest
Tested anchorage position: Top/Highest

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Result
Belted	Forward	Suppressed
	Middle	Suppressed
	Rearward	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Forward position. (SN506)

DATA SHEET 19 SUMMARY

Suppression Test Using 3 Year Old Dummy And Booster Seats (Part 572, Subpart P)
Section D Forward Facing Belt Positioning Booster

NHTSA NO.:	C85302	TEST DATE:	6/10/08
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

BOOSTER SEAT NAME:	Century
BOOSTER SEAT MODEL:	Next Step 4920
DATE OF MANUFACTURE:	8-16-2000

Manufacturer's design seat back angle:	<u>4th Detent from forward most locking</u>
Tested seat back angle:	<u>4th Detent from forward most locking</u>
Manufacturer's specified anchorage position:	<u>Top/Highest</u>
Tested anchorage position:	<u>Top/Highest</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing Without Harness	Forward	17	Suppressed
	Middle	14	Suppressed
	Rearward	11	Suppressed
Belted Forward Facing Cinched With Harness	Forward	130	Suppressed
	Middle	127	Suppressed
	Rearward	128	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Forward position. (SN506)

DATA SHEET 19 SUMMARY

Suppression Test Using 3 Year Old Dummy And Booster Seats (Part 572, Subpart P)
Section D Forward Facing Toddler Belt Positioning Booster Seat

NHTSA NO.:	C85302	TEST DATE:	6/10/08
LABORATORY:	MGA	TECHNICIANS:	JL
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

BOOSTER SEAT NAME:	Cosco
BOOSTER SEAT MODEL:	High Back Booster 02-442
DATE OF MANUFACTURE:	4-28-2000

Manufacturer's design seat back angle:	<u>4th Detent from forward most locking</u>
Tested seat back angle:	<u>4th Detent from forward most locking</u>
Manufacturer's specified anchorage position:	<u>Top/Highest</u>
Tested anchorage position:	<u>Top/Highest</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted Forward Facing Without Harness	Forward	15	Suppressed
	Middle	14	Suppressed
	Rearward	12	Suppressed
Belted Forward Facing Cinched With Harness	Forward	131	Suppressed
	Middle	131	Suppressed
	Rearward	127	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

DATA SHEET 20 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)
Section C Forward Facing Convertible CRS

NHTSA NO.:	C85302	TEST DATE:	6/6/08
LABORATORY:	MGA	TECHNICIANS:	WD
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

CHILD RESTRAINT NAME:	Britax
CHILD RESTRAINT MODEL:	Roundabout 161
DATE OF MANUFACTURE:	7-21-2000

Manufacturer's design seat back angle:	<u>4th Detent from forward most locking</u>
Tested seat back angle:	<u>4th Detent from forward most locking</u>
Manufacturer's specified anchorage position:	<u>Top/Highest</u>
Tested anchorage position:	<u>Top/Highest</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward 6 *	130	Suppressed
	Middle	131	Suppressed
	Rearward	127	Suppressed

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 25 = Full Rearward; 25 total Seat Slide detents)

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

DATA SHEET 20 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)
Section C Forward Facing Convertible CRS

NHTSA NO.:	C85302	TEST DATE:	6/6/08
LABORATORY:	MGA	TECHNICIANS:	WD
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

CHILD RESTRAINT NAME:	Century
CHILD RESTRAINT MODEL:	Encore 4612
DATE OF MANUFACTURE:	8-16-2000

Manufacturer's design seat back angle:	<u>4th Detent from forward most locking</u>
Tested seat back angle:	<u>4th Detent from forward most locking</u>
Manufacturer's specified anchorage position:	<u>Top/Highest</u>
Tested anchorage position:	<u>Top/Highest</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward 4 *	130	Suppressed
	Middle	133	Suppressed
	Rearward	131	Suppressed

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 25 = Full Rearward; 25 total Seat Slide detents)

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN506)

DATA SHEET 20 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)
Section C Forward Facing Convertible CRS

NHTSA NO.:	C85302	TEST DATE:	6/6/08
LABORATORY:	MGA	TECHNICIANS:	WD
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

CHILD RESTRAINT NAME:	Evenflo
CHILD RESTRAINT MODEL:	Medallion 254
DATE OF MANUFACTURE:	6-1-2000

Manufacturer's design seat back angle:	<u>4th Detent from forward most locking</u>
Tested seat back angle:	<u>4th Detent from forward most locking</u>
Manufacturer's specified anchorage position:	<u>Top/Highest</u>
Tested anchorage position:	<u>Top/Highest</u>

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward 8 *	129	Suppressed
	Middle	128	Suppressed
	Rearward	128	Suppressed

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 25 = Full Rearward; 25 total Seat Slide detents)

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN506)

DATA SHEET 21 SUMMARY

Suppression Test Using An Unbelted 3 Year Old Dummy (Part 572, Subpart P)
No CRS

NHTSA NO.:	C85302	TEST DATE:	6/10/08
LABORATORY:	MGA	TECHNICIANS:	AP
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

Test Summary

Position	Seat Slide	Seat Back Angle *	Result
Position 1 Sitting on seat with back against seat back	Forward	9.5° on HRP (4th Detent)	Suppressed
	Middle	9.5° on HRP (4th Detent)	Suppressed
	Rearward	9.5° on HRP (4th Detent)	Suppressed
Position 2 Sitting on seat with back against reclined seat back	Forward	33.7° on HRP	Suppressed
	Middle	33.7° on HRP	Suppressed
	Rearward	33.7° on HRP	Suppressed
Position 3 Sitting on seat with back not against seat back	Forward	9.5° on HRP (4th Detent)	Suppressed
	Middle	9.5° on HRP (4th Detent)	Suppressed
	Rearward	9.5° on HRP (4th Detent)	Suppressed
Position 4 Sitting on seat edge, spine vertical, hands at dummy's sides	Forward	9.5° on HRP (4th Detent)	Suppressed
	Middle	9.5° on HRP (4th Detent)	Suppressed
	Rearward	9.5° on HRP (4th Detent)	Suppressed
Position 5 Standing on seat, facing forward	Forward	9.5° on HRP (4th Detent)	Suppressed
	Middle	9.5° on HRP (4th Detent)	Suppressed
	Rearward	9.5° on HRP (4th Detent)	Suppressed
Position 6 Kneeling on seat, facing forward	Forward	9.5° on HRP (4th Detent)	Suppressed
	Middle	9.5° on HRP (4th Detent)	Suppressed
	Rearward	9.5° on HRP (4th Detent)	Suppressed
Position 7 Kneeling on seat, facing rearward	Forward	9.5° on HRP (4th Detent)	Suppressed
	Middle	9.5° on HRP (4th Detent)	Suppressed
	Rearward	9.5° on HRP (4th Detent)	Suppressed
Position 8 Lying on seat. (Three designated seating positions only)	Forward	N/A	N/A
	Middle	N/A	N/A
	Rearward	N/A	N/A

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN506)

* The manufacturer's design seat back angle is the 4th Detent from forward most locking. The equated to 9.5° on the Headrest Post (HRP).

DATA SHEET 27 SUMMARY

Low Risk Deployment Tests Using an Unbelted 6 Year Old
Dummy (Part 572, Subpart P) (S24) Position 1 – Chest On Instrument Panel (S24.4.2)

NHTSA NO.:	C85302	TEST DATE:	7/7/08
LABORATORY:	MGA	TECHNICIANS:	AP/WD
DUMMY TYPE:	6-Year-Old	DUMMY SERIAL NO.:	155

Manufacturer's design seat back angle: 4th Detent from forward most locking
Tested seat back angle: 4th Detent from forward most locking
Tested seat position: Full Aft

Thorax cavity angle: 5.7°
Point 1 height: 58 mm Below Plane C

Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.3
2	150.0	150.3

6-Year-Old SN 155 Position 1 (Chest on Instrument Panel) 7/7/08

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	50
Peak Nij (Nte)	1.0	0.4
Time (ms)	NA	76.9
Peak Nij (Ntf)	1.0	0.5
Time (ms)	NA	22.6
Peak Nij (Nce)	1.0	0.1
Time (ms)	NA	1.5
Peak Nij (Ncf)	1.0	0.5
Time (ms)	NA	25.0
Neck Tension	1490 N	590
Neck Compression	1820 N	447
Chest g	60 g	16
Chest Displacement	40 mm	6

Calculated on data recorded for 100 ms after the initial deployment of the air bag. (S4.11(b))

The original equipment parts were used for this deployment.

DATA SHEET 28 SUMMARY

Low Risk Deployment Tests Using an Unbelted 6 Year Old
Dummy (Part 572, Subpart N) (S24) Position 2 – Head On Instrument Panel (S24.4.3)

NHTSA NO.:	C85303	TEST DATE:	7/8/08
LABORATORY:	MGA	TECHNICIANS:	AP/WD
DUMMY TYPE:	6-Year-Old	DUMMY SERIAL NO.:	155

Manufacturer's design seat back angle: 4th Detent from forward most locking
Tested seat back angle: 4th Detent from forward most locking
Tested seat position: Full Forward

Thorax cavity angle: 31.0°
Thigh angle: 11.1°

Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.3
2	150.0	150.3

6-Year-Old SN 155 Position 2 (Head on Instrument Panel) 7/8/08

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	17
Peak Nij (Nte)	1.0	0.3
Time (ms)	NA	68.8
Peak Nij (Ntf)	1.0	0.2
Time (ms)	NA	80.3
Peak Nij (Nce)	1.0	0.5
Time (ms)	NA	46.2
Peak Nij (Ncf)	1.0	0.2
Time (ms)	NA	28.5
Neck Tension	1490 N	584
Neck Compression	1820 N	835
Chest g	60 g	10
Chest Displacement	40 mm	1

Calculated on data recorded for 100 ms after the initial deployment of the air bag. (S4.11(b))

A new air bag and instrument panel cover were used for this deployment.

DATA SHEET 29 SUMMARY

Low Risk Deployment Tests Using an Unbelted 5th Percentile Female
Dummy (Part 572, Subpart O) (S26) Position 1 - Chin On Module (S26.2)

NHTSA NO.:	C85302	TEST DATE:	7/7/08
LABORATORY:	MGA	TECHNICIANS:	WD/AP
DUMMY TYPE:	5 th Percentile Female	DUMMY SERIAL NO.:	511

Manufacturer's design seat back angle:	4th Detent from forward most locking
Tested seat back angle:	4th Detent from forward most locking
Tested seat position:	Full Aft
Tested steering wheel angle:	22.7°
Thorax cavity angle:	28.8°
Bottom of chin height:	1 mm Below Plane F Module Height

Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.3
2	40.0	40.3

5th Percentile Female SN 511 Position 1 (Chin On Module) 7/7/08

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	42
Peak Nij (Nte)	1.0	0.3
Time (ms)	NA	65.7
Peak Nij (Ntf)	1.0	0.2
Time (ms)	NA	38.8
Peak Nij (Nce)	1.0	0.3
Time (ms)	NA	160.8
Peak Nij (Ncf)	1.0	0.1
Time (ms)	NA	15.7
Neck Tension	2070 N	728
Neck Compression	2520 N	360
Chest g	60 g	10
Chest Displacement	52 mm	6
Left Femur	6805 N	72
Right Femur	6805 N	94

Calculated on data recorded for 125 ms after the initiation of the final stage of air bag deployment designed to deploy in any full frontal rigid barrier crash up to 26 km/h. (S4.11(d))
Second stage fire time of 40 ms; Injuries calculated on 0 ms to 165 ms

The original equipment parts were used for this deployment.

DATA SHEET 30 SUMMARY

Low Risk Deployment Tests Using an Unbelted 5th Percentile Female Dummy (Part 572, Subpart O) (S26) Position 2 - Chin On Rim (S26.3)

NHTSA NO.:	C85302	TEST DATE:	7/7/08
LABORATORY:	MGA	TECHNICIANS:	WD/AP
DUMMY TYPE:	5 th Percentile Female	DUMMY SERIAL NO.:	511

Manufacturer's design seat back angle: 4th Detent from forward most locking
 Tested seat back angle: 4th Detent from forward most locking
 Tested seat position: Full Aft

Tested steering wheel angle: 19.3° *
 Thorax cavity angle: 25.8°
 Chin Point height: 2 mm Below Steering Wheel Target
 Note: The chin on rim steering wheel target is 10 mm below the highest point on the steering wheel

*The dummy contacted the windshield with the steering wheel at mid position. The steering controls were adjusted to lower the upper steering wheel rim the necessary amount to bring the Chin Point coincident with the upper steering wheel rim. The rear thorax cavity was adjusted along with the steering wheel angle.

Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.3
2	40.0	40.3

5th Percentile Female SN 511 Position 2 (Chin On Rim) 7/7/08

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	5
Peak Nij (Nte)	1.0	0.3
Time (ms)	NA	11.0
Peak Nij (Ntf)	1.0	0.1
Time (ms)	NA	72.3
Peak Nij (Nce)	1.0	0.0
Time (ms)	NA	8.2
Peak Nij (Ncf)	1.0	0.2
Time (ms)	NA	83.7
Neck Tension	2070 N	613
Neck Compression	2520 N	127
Chest g	60 g	27
Chest Displacement	52 mm	16
Left Femur	6805 N	70
Right Femur	6805 N	71

Calculated on data recorded for 125ms after the initiation of the final stage of air bag deployment designed to deploy in any full frontal rigid barrier crash up to 26 km/h. (S4.11(d))
 Second stage fire time of 40 ms; Injuries calculated on 0 ms to 165 ms

A new air bag; and original equipment steering column and steering wheel were used for this deployment.

DATA SHEET 32

VEHICLE WEIGHT, FUEL TANK, AND ATTITUDE DATA

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Jamie Aide

NHTSA No.: C85302
 Test Date: 7/31/08

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u> </u> 0 to 48 kmph	<u> </u> 0 to 56 kmph
DRIVER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	
PASSENGER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	

- | | | |
|----------|-----|---|
| <u>X</u> | 1. | Fill the transmission with transmission fluid to the satisfactory range. |
| <u>X</u> | 2. | Drain fuel from vehicle |
| <u>X</u> | 3. | Run the engine until fuel remaining in the fuel delivery system is used and the engine stops. |
| <u>X</u> | 4. | Record the useable fuel tank capacity supplied by the COTR |
| <u>X</u> | | Useable Fuel Tank Capacity supplied by COTR: 70.0 liters (18.5 gallons) |
| <u>X</u> | 5. | Record the fuel tank capacity supplied in the owner's manual. |
| <u>X</u> | | Useable Fuel Tank Capacity in owner's manual: 70.0 liters (18.5 gallons) |
| <u>X</u> | 6. | Using purple dyed Stoddard solvent having the physical and chemical properties of Type 1 solvent or cleaning fluid, Table 1, ASTM Standard D484-71, "Standard Specifications for Hydrocarbon Dry-cleaning Solvents," or gasoline, fill the fuel tank. |
| <u>X</u> | | Amount Added: 70.0 liters (18.5 gallons) |
| <u>X</u> | 7. | Fill the coolant system to capacity. |
| <u>X</u> | 8. | Fill the engine with motor oil to the Max. mark on the dip stick. |
| <u>X</u> | 9. | Fill the brake reservoir with brake fluid to its normal level. |
| <u>X</u> | 10. | Fill the windshield washer reservoir to capacity. |
| <u>X</u> | 11. | Inflate the tires to the tire pressure on the tire placard. If no tire placard is available, inflate the tires to the recommended pressure in the owner's manual. |

Tire placard pressure:	RF:	32 psi	LF:	32 psi	RR:	32 psi	LR:	32 psi
Owner's manual pressure:	RF:	32 psi	LF:	32 psi	RR:	32 psi	LR:	32 psi
Actual inflated pressure:	RF:	32 psi	LF:	32 psi	RR:	32 psi	LR:	32 psi

- | | | |
|----------|-----|--|
| <u>X</u> | 12. | Record the vehicle weight at each wheel to determine the unloaded vehicle weight (UVW), i.e. "as delivered" weight). |
|----------|-----|--|

Right Front (kg):	491.2	Right Rear (kg):	302.1
Left Front (kg):	505.3	Left Rear (kg):	313.9
Total Front (kg):	996.5	Total Rear (kg):	616.0
% Total Weight:	61.8	% Total Weight:	38.2
UVW = TOTAL FRONT PLUS TOTAL REAR (KG):		1612.5	

- | | | |
|----------|------|---|
| <u>X</u> | 13. | UVW Test Vehicle Attitude: (All dimensions in millimeters) |
| <u>X</u> | 13.1 | Mark a point on the vehicle above the center of each wheel. |
| <u>X</u> | 13.2 | Place the vehicle on a level surface. |

<input checked="" type="checkbox"/>	13.3	Measure perpendicular to the level surface to the 4 points marked on the body and record the measurements																												
		<table border="1"> <tr> <td>RF:</td> <td>699</td> <td>LF:</td> <td>699</td> <td>RR:</td> <td>714</td> <td>LR:</td> <td>708</td> </tr> </table>	RF:	699	LF:	699	RR:	714	LR:	708																				
RF:	699	LF:	699	RR:	714	LR:	708																							
<input checked="" type="checkbox"/>	14.	Calculate the Rated Cargo and Luggage Weight (RCLW): 45 kg																												
<input checked="" type="checkbox"/>	14.1	Does the vehicle have the vehicle capacity weight (VCW) on the certification label or tire placard?																												
<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/> Yes, go to 14.3																												
		<input type="checkbox"/> No, go to 14.2																												
	14.2	VCW = Gross Vehicle Weight - UVW																												
		VCW = _____ - _____ = _____																												
<input checked="" type="checkbox"/>	14.3	VCW = <u>385 kg (850 lbs)</u>																												
<input checked="" type="checkbox"/>	14.4	Does the certification or tire placard contain the Designated Seating Capacity (DSC)?																												
		<input checked="" type="checkbox"/> Yes, go to 14.6																												
		<input type="checkbox"/> No, go to 14.5 and skip 14.6																												
	14.5	DSC = Total number of seat belt assemblies = _____																												
<input checked="" type="checkbox"/>	14.6	DSC = <u>5</u>																												
<input checked="" type="checkbox"/>	14.7	RCLW = VCW - (68 kg x DSC) = <u>385 kg</u> - (68 kg x <u>5</u>) = <u>45 kg</u>																												
<input checked="" type="checkbox"/>	14.8	Is the vehicle certified as a truck, MPV or bus (see the certification label on the door jamb)?																												
		<input type="checkbox"/> Yes, if the calculated RCLW is greater than 136 kg, use 136 kg as the RCLW. (S8.1.1)																												
<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/> No, use the RCLW calculated in 14.7																												
<input checked="" type="checkbox"/>	15.	Fully Loaded Weight (100% fuel fill): 1755.9 kg																												
<input checked="" type="checkbox"/>	15.1	Place the appropriate test dummy in both front outboard seating positions.																												
		Driver: <input checked="" type="checkbox"/> 5 th female <input type="checkbox"/> 50 th male																												
		Passenger: <input checked="" type="checkbox"/> 5 th female <input type="checkbox"/> 50 th male																												
<input checked="" type="checkbox"/>	15.2	Load the vehicle with the RCLW from 14.7 or 14.8 whichever is applicable.																												
<input checked="" type="checkbox"/>	15.3	Place the RCLW in the cargo area. Center the load over the longitudinal centerline of the vehicle. (S8.1.1 (d))																												
<input checked="" type="checkbox"/>	15.4	Record the vehicle weight at each wheel to determine the Fully Loaded Weight.																												
		<table border="1"> <tr> <td>Right Front (kg):</td> <td>520.3</td> <td>Right Rear (kg):</td> <td>345.2</td> </tr> <tr> <td>Left Front (kg):</td> <td>529.8</td> <td>Left Rear (kg):</td> <td>360.6</td> </tr> <tr> <td>Total Front (kg):</td> <td>1050.1</td> <td>Total Rear (kg):</td> <td>705.8</td> </tr> <tr> <td>% Total Weight:</td> <td>59.8</td> <td>% Total Weight:</td> <td>40.2</td> </tr> <tr> <td>% GVW</td> <td>55.9</td> <td>% GVW</td> <td>45.1</td> </tr> <tr> <td colspan="4">(% GVW = Axle GVW divided by Vehicle GVW)</td> </tr> <tr> <td colspan="3">Fully Loaded Weight = Total Front Plus Total Rear (kg):</td> <td>1755.9</td> </tr> </table>	Right Front (kg):	520.3	Right Rear (kg):	345.2	Left Front (kg):	529.8	Left Rear (kg):	360.6	Total Front (kg):	1050.1	Total Rear (kg):	705.8	% Total Weight:	59.8	% Total Weight:	40.2	% GVW	55.9	% GVW	45.1	(% GVW = Axle GVW divided by Vehicle GVW)				Fully Loaded Weight = Total Front Plus Total Rear (kg):			1755.9
Right Front (kg):	520.3	Right Rear (kg):	345.2																											
Left Front (kg):	529.8	Left Rear (kg):	360.6																											
Total Front (kg):	1050.1	Total Rear (kg):	705.8																											
% Total Weight:	59.8	% Total Weight:	40.2																											
% GVW	55.9	% GVW	45.1																											
(% GVW = Axle GVW divided by Vehicle GVW)																														
Fully Loaded Weight = Total Front Plus Total Rear (kg):			1755.9																											
<input checked="" type="checkbox"/>	16.	Fully Loaded Test Vehicle Attitude: (All dimensions in millimeters)																												
<input checked="" type="checkbox"/>	16.1	Place the vehicle on a level surface.																												

- ☒ 16.2 Measure perpendicular to the level surface to the 4 points marked on the body (see 13.1 above) and record the measurements

RF:	689	LF:	688	RR:	698	LR:	694
-----	-----	-----	-----	-----	-----	-----	-----

- ☒ 17. Drain the fuel system
- ☒ 18. Using purple dyed Stoddard solvent having the physical and chemical properties of Type 1 solvent or cleaning fluid, Table 1, ASTM Standard D484-71, "Standard Specifications for Hydrocarbon Dry-cleaning Solvents," fill the fuel tank to 92 - 94 percent of useable capacity.

☒ Fuel tank capacity x .94 = 70.0 liters (18.5 gallons) x .94 = 65.8 liters (17.4 gallons)

☒ Amount added 65.1 liters (17.2 gallons) 93.0%

- ☒ 19. Crank the engine to fill the fuel delivery system with Stoddard solvent
- ☒ 20. Calculate the test weight range.
- ☒ 20.1 Calculated Weight = UVW (see 12 above) + RCLW (see 14 above) + 2x(dummy weight)

$$1755.5 \text{ kg} = 1612.5 \text{ kg} + 45.0 \text{ kg} + 98.0 \text{ kg}$$

- ☒ 20.2 Test Weight Range = Calculated Weight (- 4.5 kg, - 9 kg.)
 Max. Test Weight = Calculated Test Weight - 4.5 kg = 1751.0 kg
 Min. Test Weight = Calculated Test Weight - 9 kg = 1746.5 kg

- ☒ 21. Remove the RCLW from the cargo area.
- ☒ 22. Drain transmission fluid, engine coolant, motor oil, and windshield washer fluid from the test vehicle so that Stoddard solvent leakage from the fuel system will be evident.
- ☒ 23. Vehicle Components Removed For Weight Reduction:
Spare tire, jack and tools, and trunk interior
- ☒ 24. Secure the equipment and ballast in the load carrying area and distribute it, as nearly as possible, to obtain the proportion of axle weight indicated by the gross axle weight ratings and center it over the longitudinal centerline of the vehicle.

- ☒ 25. If necessary, add ballast to achieve the actual test weight.

☐ N/A

☒ Weight of Ballast: 10.0 kg

- ☒ 26. Ballast, including test equipment, must be contained so that it will not shift during the impact event or interfere with data collection or interfere with high-speed film recordings or affect the structural integrity of the vehicle or do anything else to affect test results. Care must be taken to assure that any attachment hardware added to the vehicle is not in the vicinity of the fuel tank or lines.

- ☒ 27. Record the vehicle weight at each wheel to determine the actual test weight.

Right Front (kg):	520.3	Right Rear (kg):	342.5
Left Front (kg):	534.3	Left Rear (kg):	352.0
Total Front (kg):	1054.6	Total Rear (kg):	694.5
% Total Weight:	60.3	% Total Weight:	39.7
% GVW	55.9	% GVW	45.1
(% GVW = Axle GVW divided by Vehicle GVW)			
TOTAL FRONT PLUS TOTAL REAR (kg):			1749.1

<input checked="" type="checkbox"/>	28.	Is the test weight between the Max. Weight and the Min. Weight (See 20.2)?								
	<input checked="" type="checkbox"/>	Yes								
	<input type="checkbox"/>	No, explain why not.								
<input checked="" type="checkbox"/>	29.	Test Weight Vehicle Attitude: (all dimensions in millimeters)								
<input checked="" type="checkbox"/>	29.1	Place the vehicle on a level surface								
<input checked="" type="checkbox"/>	29.2	Measure perpendicular to the level surface to the 4 points marked on the body (see 13 above) and record the measurements								
<table border="1"> <tr> <td>RF:</td> <td>690</td> <td>LF:</td> <td>689</td> <td>RR:</td> <td>703</td> <td>LR:</td> <td>699</td> </tr> </table>			RF:	690	LF:	689	RR:	703	LR:	699
RF:	690	LF:	689	RR:	703	LR:	699			
<input checked="" type="checkbox"/>	30.	Summary of test attitude								
<input checked="" type="checkbox"/>	30.1	AS DELIVERED:								
<table border="1"> <tr> <td>RF:</td> <td>699</td> <td>LF:</td> <td>699</td> <td>RR:</td> <td>714</td> <td>LR:</td> <td>708</td> </tr> </table>			RF:	699	LF:	699	RR:	714	LR:	708
RF:	699	LF:	699	RR:	714	LR:	708			
AS TESTED:										
<table border="1"> <tr> <td>RF:</td> <td>690</td> <td>LF:</td> <td>689</td> <td>RR:</td> <td>703</td> <td>LR:</td> <td>699</td> </tr> </table>			RF:	690	LF:	689	RR:	703	LR:	699
RF:	690	LF:	689	RR:	703	LR:	699			
FULLY LOADED:										
<table border="1"> <tr> <td>RF:</td> <td>689</td> <td>LF:</td> <td>688</td> <td>RR:</td> <td>698</td> <td>LR:</td> <td>694</td> </tr> </table>			RF:	689	LF:	688	RR:	698	LR:	694
RF:	689	LF:	688	RR:	698	LR:	694			
<input checked="" type="checkbox"/>	30.2	Is the "as tested" test attitude equal to or between the "fully loaded" and "as delivered" attitude?								
	<input checked="" type="checkbox"/>	Yes								
	<input type="checkbox"/>	No, explain why not.								

REMARKS:

I certify that I have read and performed each instruction.

Signature:



Date:

7/31/08

DATA SHEET 33

VEHICLE ACCELEROMETER LOCATION AND MEASUREMENT

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Jamie Aide

NHTSA No.: C85302
 Test Date: 7/31/08

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u> </u> 0 to 48 kmph	<u> </u> 0 to 56 kmph
DRIVER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	
PASSENGER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	

- ☒ 1. Find the location where the vertical plane parallel to the longitudinal centerline of the vehicle and through the center of the left front outboard seating position intersects the left rear seat cross member. Install an accelerometer at this intersection on the rear seat cross member to record x-direction accelerations. Record the location on the following chart.
- ☒ 2. Find the location where the vertical plane parallel to the longitudinal centerline of the vehicle and through the center of the right front outboard seating position intersects the right rear seat cross member. Install an accelerometer at this intersection on the rear seat cross member to record x-direction accelerations. Record the location on the following chart.
- ☒ 3. Find the location where a vertical plane through the longitudinal centerline of the vehicle and a vertical transverse plane through the center of the two wheels on opposite sides of the engine intersect at the top of the engine. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- ☒ 4. Find the location where a vertical plane through the longitudinal centerline of the vehicle and a vertical transverse plane through the center of the two wheels on opposite sides of the engine intersect the bottom of the engine. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- ☒ 5. Install an accelerometer on the right front brake caliper to record x-direction accelerations. Record the location on the following chart.
- ☒ 6. Find the location where a vertical plane through the longitudinal centerline of the vehicle intersects the top of the instrument panel. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- ☒ 7. Install an accelerometer on the left front brake caliper to record x-direction accelerations. Record the location on the following chart.
- ☒ 8. Find the location where a vertical plane through the longitudinal centerline of the vehicle intersects the floor of the trunk. Install an accelerometer on the trunk floor at this intersection to record z-direction accelerations. Record the location on the following chart.

REMARKS:

I certify that I have read and performed each instruction.

Signature: _____




Date: _____

7/31/08


VEHICLE ACCELEROMETER LOCATION AND DATA SUMMARY

CENTERLINE OF
FRONT WHEELS



ACCELEROMETER
COORDINATE SYSTEM
(POSITIVE DIRECTION SHOWN)

REAR SEAT CUSHION
ASSY. FRONT ATTACHMENT
BRACKET SUPPORT



Dimensions Corresponding To The Letters "A" Through "K" (Excluding "I") Are
Recorded In The Table On The Following Page.
Accelerometers Corresponding To The Numbers 1 Through 8 Are Specified On The
Preceding Page.

DATA SHEET 33
VEHICLE ACCELEROMETER LOCATION AND MEASUREMENTS

<u>DIMENSION</u>	<u>LENGTH (mm)</u>	
<u>PRETEST VALUES</u>		
<u>A</u> (LH Rear Seat Xmbr)	394	
<u>B</u> (RH Rear Seat Xmbr)	405	
<u>C</u> (Engine Top)	4047	
<u>D</u> (Engine Bottom)	4149	
<u>E</u> (Caliper)	Right Side: 4068	Left Side: 4068
<u>F</u> (Left Caliper)	705	
<u>G</u> (IP)	3136	
<u>H</u> (Seat)	1997	
<u>J</u> (Right Caliper)	705	
<u>K</u> (Trunk)	1183	
<u>POST TEST VALUES</u>		
<u>A</u> (LH Rear Seat Xmbr)	394	
<u>B</u> (RH Rear Seat Xmbr)	405	
<u>C</u> (Engine Top)	4003	
<u>D</u> (Engine Bottom)	4108	
<u>E</u> (Caliper)	Right Side: 4048	Left Side: 4046
<u>F</u> (Left Caliper)	711	
<u>G</u> (IP)	3104	
<u>H</u> (Seat)	1997	
<u>J</u> (Right Caliper)	711	
<u>K</u> (Trunk)	1183	

DATA SHEET 34

PHOTOGRAPHIC TARGETS





Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Jamie Aide

NHTSA No.: C85302
 Test Date: 7/31/08

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u> </u> 0 to 48 kmph	<u> </u> 0 to 56 kmph
DRIVER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	
PASSENGER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	

- | | | |
|-------------------------------------|------|--|
| <input checked="" type="checkbox"/> | 1. | FMVSS 208 vehicle targeting requirements (See Figures 28A and 28B) |
| <input checked="" type="checkbox"/> | 1.1 | Targets A1 and A2 are on flat rectangular panels. |
| <input checked="" type="checkbox"/> | 1.2 | Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted at the front on the outboard sides of A1 and A2. The center of each circular target is 100 mm from the one next to it. |
| <input checked="" type="checkbox"/> | | Distance between targets (mm): <u>100 mm</u> |
| <input checked="" type="checkbox"/> | 1.3 | Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted at the back on the outboard sides of on A1 and A2. The center of each circular target is 100 mm from the one next to it. |
| <input checked="" type="checkbox"/> | | Distance between targets (mm): <u>100 mm</u> |
| <input checked="" type="checkbox"/> | 1.4 | The distance between the first circular target at the front of A1 and A2 and the last circular target at the back of A1 and A2 is at least 915 mm. |
| <input checked="" type="checkbox"/> | | Distance between the first and last circular targets (mm): <u>915 mm</u> |
| <input checked="" type="checkbox"/> | 1.5 | Firmly fix target A1 on the vehicle roof in the vertical longitudinal plane that is coincident with the midsagittal plane of the driver dummy. |
| <input checked="" type="checkbox"/> | 1.6 | Firmly fix target A2 on the vehicle roof in the vertical longitudinal plane that is coincident with the midsagittal plane of the passenger dummy. |
| <input checked="" type="checkbox"/> | 1.7 | Two circular targets (C1 and C2) at least 90 mm in diameter and with black and yellow quadrants are mounted on the outside of the driver door. The centers of each circular target are at least 610 mm apart. |
| <input checked="" type="checkbox"/> | | Distance between targets (mm): <u>610 mm</u> |
| <input checked="" type="checkbox"/> | 1.8 | Two circular targets (C1 and C2) at least 90 mm in diameter and with black and yellow quadrants are mounted on the outside of the passenger door. The centers of each circular target are at least 610 mm apart. |
| <input checked="" type="checkbox"/> | | Distance between targets (mm): <u>610 mm</u> |
| <input checked="" type="checkbox"/> | 1.9 | Place tape with squares having alternating colors on the top portion of the steering wheel. |
| <input checked="" type="checkbox"/> | 1.10 | Chalk the bottom portion of the steering wheel |
| <input checked="" type="checkbox"/> | 1.11 | Is this an offset test? |
| | | <input type="checkbox"/> Yes, continue with this section |
| | | <input checked="" type="checkbox"/> No, go to 2. |

<input type="checkbox"/>	1.12	Measure the width of the vehicle.
<input type="checkbox"/>		Vehicle width (mm):
<input type="checkbox"/>	1.13	Find the centerline of the vehicle. ($\frac{1}{2}$ of the vehicle width)
<input type="checkbox"/>	1.14	Find the line parallel to the centerline of the vehicle and 0.1 x vehicle width from the centerline of the vehicle.
<input type="checkbox"/>	1.15	Apply 25 mm wide tape with alternating black and yellow squares parallel to and on each side of the line found in 1.14. The edge of each tape shall be 50 mm from the line found in 1.14. The tape shall extend from the bottom of the bumper to the front edge of the windshield. (Figure 28D)
<input checked="" type="checkbox"/>	2.	Barrier Targeting
<input checked="" type="checkbox"/>	2.1	Fix two stationary targets D1 and D2 to the barrier as shown in the Figure 28A. One target is in the vertical longitudinal plane that is coincident with the midsagittal plane of the driver dummy. The other is in the vertical longitudinal plane that is coincident with the midsagittal plane of the passenger dummy
<input checked="" type="checkbox"/>	2.2	Targets D1 and D2 are on a rectangular panel.
<input checked="" type="checkbox"/>	2.3	Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted on the sides of the rectangular panel away from the longitudinal centerline of the vehicle. The center of each circular target is 100 mm from the one next to it.
<input checked="" type="checkbox"/>		Distance between circular targets on D1 (mm): <u>100 mm</u>
<input checked="" type="checkbox"/>		Distance between circular targets on D2 (mm): <u>100 mm</u>
<input checked="" type="checkbox"/>	3.	FMVSS 208 Dummy Targeting Requirements
<input checked="" type="checkbox"/>	3.1	Place a circular target with black and yellow quadrants on both sides of the driver dummy head as close as possible to the center of gravity of the head in the x and z direction (relative to the measuring directions of the accelerometers).
<input checked="" type="checkbox"/>	3.2	Place a circular target with black and yellow quadrants on both sides of the passenger dummy head as close as possible to the center of gravity of the head in the x and z direction (relative to the measuring directions of the accelerometers).
<input checked="" type="checkbox"/>	3.3	Place a circular target with black and yellow quadrants on the outboard shoulder of the driver dummy. Place the target as high up on the arm as possible at the intersection of the arm and shoulder. The sleeve of the shirt on the dummy may be cut to make the target visible, but do not remove any material.
<input checked="" type="checkbox"/>	3.4	Place a circular target with black and yellow quadrants on the outboard shoulder of the passenger dummy. Place the target as high up on the arm as possible at the intersection of the arm and shoulder. The sleeve of the shirt on the dummy may be cut to make the target visible, but do not remove any material.
<input checked="" type="checkbox"/>	4.	FMVSS 204 Targeting Requirements
<input checked="" type="checkbox"/>	4.1	Is an FMVSS 204 indicant test ordered on the "COTR Vehicle Work Order?"
<input type="checkbox"/>		Yes, continue with this form.
<input checked="" type="checkbox"/>		No, this form is complete.
<input type="checkbox"/>	4.2	Resection panel (Figure 28C)
<input type="checkbox"/>	4.2.1	The panel deviates no more than 6 mm from perfect flatness when suspended vertically
<input type="checkbox"/>	4.2.2	The 8 targets on the panel are circular targets at least 90 mm in diameter and with black and yellow quadrants.
<input type="checkbox"/>	4.2.3	The center of each of the 4 outer targets are placed within 1 mm of the corners of a square measuring 914 mm on each side.

-  4.2.4 Locate another square with 228 mm sides and with the center of this square coincident with the center of the 914 mm square.
-  4.2.5 The center of the 4 inner targets are placed at the midpoints of each of the 228 mm sides.
-  4.3 Place a circular target at least 90 mm in diameter and with black and yellow quadrants on a material (cardboard, metal, etc.) that can be taped to the top of the steering column.
-  4.4 Tape the target from 4.3 to the top of the steering column in a manner that does not interfere with the movement of the steering column in a crash

I certify that I have read and performed each instruction.


Signature:




Date:

7/31/08


REFERENCE PHOTO TARGETS




RESECTION PANEL TARGETING ALIGNMENT



TEST RUN STEERING COLUMN CAMERA VIEW OF TYPICAL TIME ZERO VEHICLE POSITION



PRE-RUN STEERING COLUMN HIGH SPEED CAMERA VIEW



LEFT SIDE VIEW

DATA SHEET 35
CAMERA LOCATIONS

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance


NHTSA No.: C85302
Test Date: 7/31/08
Time: 10:45 am

CAMERA NO.	VIEW	CAMERA POSITIONS (mm) *			LENS (mm)	SPEED (fps)
		X	Y	Z		
1	Real Time Left Side View				13	24
2	Left Side View (Barrier face to front seat backs)	1265	-5145	1225	24	1000
3	Left Side View (Driver)	1505	-5500	1490	35	1000
4	Left Side View (B-post aimed toward center of steering wheel)	6015	-4995	2085	50	1000
5	Left Side View (Steering Column)	775	-5580	1230	25	1000
6	Left Side View (Steering Column)	770	-5590	880	25	1000
7	Right Side View (Overall)	775	-5580	1230	25	1000
8	Right Side View (Passenger)	1505	5490	1490	35	1000
9	Right Side View (Angle)	770	-5590	880	25	1000
10	Right Side View (Front door)	1270	5150	1215	24	1000
11	Front View Windshield	-315	0	2830	12.5	1000
12	Front View Driver	-135	-395	2240	24	1000
13	Front View Passenger	-110	505	2240	24	1000
14	Overhead Barrier Impact View	1190	0	5050	14	1000
15	Pit Camera Engine View	1675	0	-3150	24	1000
16	Pit Camera Fuel Tank View	3345	0	-3150	24	1000

***COORDINATES:**

+X - forward of impact plane
+Y - right of monorail centerline
+Z - above ground level

CAMERA POSITIONS FOR FMVSS 208



DATA SHEET 36
APPENDIX G
DUMMY POSITIONING PROCEDURES
FOR 5th% DRIVER TEST DUMMY CONFORMING TO SUBPART O OF PART 572

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Jordan Haynes

NHTSA No.: C85302
 Test Date: 7/31/08

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u> </u> 0 to 48 kmph	<u> </u> 0 to 56 kmph
DRIVER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	
PASSENGER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	

- X 1. Using the markings made from data sheet 14.3 (If not done previously or steering repairs have been made, complete data sheet 14.3 at this time.) to position the steering controls in the mid-position or if applicable next lowest detent position. (S16.2.9)
- X 2. Place the SCRP in the full rearward, mid-height position, and mid-seat cushion angle, determined during the completion of Data Sheet 14.1. (S16.3.2.1.1)
- X 3. If the vehicle has an adjustable accelerator pedal, place it in the full forward position. (S16.3.2.2.1)
X N/A accelerator pedal not adjustable
- X 4. Fully recline the seat back. (S16.3.2.1.2)
 N/A seat back not adjustable.
- X 5. Place the dummy in the seat with the legs at an angle of 120 degrees to the thighs. The calves should not be touching the seat cushion. (S16.3.2.1.2)
- X 6. Position the dummy in the seat such that the midsagittal plane is coincident with the longitudinal seat cushion markings as determined in Data Sheet 14.1. (S16.3.2.1.3 and S16.3.2.1.4)
- X 7. Hold down the dummy's thighs and push rearward on the upper torso to maximize the pelvic angle. (S16.3.2.1.5)
- X 8. Set the angle between the legs and the thighs to 120 degrees. (S16.3.2.1.6)
- X 9. Set the transverse distance between the centers of the front of the knees at 160 to 170 mm. (6.3 to 6.7 inches) Center the knee separation with respect to the longitudinal seat cushion marking as determined Data Sheet 14.1. (S16.3.2.1.6)
 Record Knee Separation 165
- X 10. Push rearward on the dummy's knees until the pelvis contacts the seat back, or the backs of the calves contact the seat cushion, whichever occurs first. (S16.3.2.1.6)
 Pelvis contacted seat back.
X Calves contacted seat cushion.

- X 11. Gently rock the upper torso ± 5 degrees (approximately 51 mm (2 inches)) side-to-side three time. (S16.3.2.1.7)
- X 12. If needed, extend the legs until the feet do not contact the floor pan. The thighs should be resting on the seat cushion. (S16.3.2.1.8)
- X 13. Position the right foot until the foot is in line with a longitudinal vertical plane passing through the center of the accelerator pedal. Maintain the leg and thigh in a vertical plane. (S16.3.2.1.8)
- X 14. Rotate the left leg and thigh laterally to equalize the distance between each knee and the longitudinal seat cushion marking as determined in Data Sheet 14.1. (S16.3.2.1.8)
- X 15. Attempt to return the seat to the foremost fore-aft position, mid-height, and seat cushion mid-angle as determined in Data Sheet 14.2. The foot may contact and depress the accelerator and/or change the angle of the foot with respect to the leg. (S16.3.2.1.8)
- X Foremost position achieved. Proceed to step 20.
- ___ Foremost not achieved because of foot interference. Proceed to step 17.
- ___ Foremost not achieved because of steering wheel contact.
- ___ 16. If either of the dummy's legs contact the steering wheel, move the steering wheel up the minimum amount required to avoid contact. If the steering wheel is not adjustable separate the knees the minimum required to avoid contact. (S16.3.2.1.8)
- ___ N/A- there was no leg contact
- ___ Steering wheel repositioned
- ___ Knees separated
- ___ 17. If the left foot interferes with the clutch or brake pedals, rotate the left foot about the leg to provide clearance. If this is not sufficient, rotate the thigh outboard at the hip the minimum amount required for clearance. (S16.3.2.1.8)
- ___ N/A, No foot interference with pedals.
- ___ Foot adjusted to provide clearance.
- ___ Foot and Thigh adjusted to provide clearance.
- ___ 18. Continue to move the seat. Use seat controls to line up the seat markings determined during the completion of Data Sheet 14.1 to set the foremost fore-aft position, mid-height position and the seat cushion mid-angle. If the dummy contacts the interior move the seat rearward until a maximum clearance of 5 mm (0.2 inches) is achieved or the seat is in the closest detent position that does not cause dummy contact. (S16.3.2.1.8)
- ___ Foremost, mid-height position and the seat cushion mid-angle reached
- ___ Dummy contact. Clearance set at maximum of 5mm
- Measured Clearance _____
- ___ Dummy Contact. Seat set at nearest detent position.
- Seat position ___ detent positions rearward of foremost
(foremost is position zero)

- ☐ 19. If the steering wheel was repositioned in step 16, return the steering wheel to the original position. If the steering wheel contacts the dummy before reaching the original position, position the wheel until a maximum clearance of 5mm (.2 inches) is achieved, or the steering wheel is in the closest detent position that does not cause dummy contact. (S16.3.2.1.8)
- ☐ N/A Steering wheel was not repositioned.
- ☐ Original position achieved.
- ☐ Dummy contact. Clearance set at maximum of 5mm
Measured Clearance _____
- ☐ Dummy Contact. Steering wheel set at nearest detent position.
Steering wheel position _____ detent positions upward of original position.
(Original position is position zero)
- ☒ 20. If the seat back is adjustable, rotate the seat back forward while holding the thighs in place. Continue rotating the seat back forward until the transverse instrument platform of the dummy head is level ± 0.5 degrees. If the head cannot be leveled using the seat back adjustment, or the seat back is not adjustable, use the lower neck bracket adjustment to level the head. If a level position cannot be achieved, minimize the angle. (S16.3.2.1.9)
- ☒ Head Level Achieved. (Check all that apply)
- ☒ Head leveled using the adjustable seat back
- ☐ Head leveled using the neck bracket.
Head Angle 0.1 degrees
- ☐ Head Level NOT Achieved. (Check all that apply)
- ☐ Head adjusted using the adjustable seat back
- ☐ Head adjusted using the neck bracket.
Head Angle _____ degrees
- ☒ 21. Verify the pelvis is not interfering with the seat bight. (S16.3.2.1.9)
- ☒ No interference
- ☐ Pelvis moved forward the minimum amount so that it is not caught in the seat bight.
- ☒ 22. Verify the dummy abdomen is properly installed. (S16.3.2.1.9)
- ☒ Abdomen still seated properly into dummy
- ☐ Abdomen was adjusted because it was not seated properly into dummy
- ☒ 23. Head Angle
- ☒ N/A, neither the pelvis nor the abdomen were adjusted.
- ☒ 23.1 Head still level (Go to 24)
- ☐ 23.2 Head level adjusted
- ☐ Head Level Achieved. (Check all that apply)
- ☐ Head leveled using the adjustable seat back
- ☐ Head leveled using the neck bracket.
Head Angle _____ degrees
- ☐ Head Level NOT Achieved. (Check all that apply)
- ☐ Head level adjusted using the adjustable seat back
- ☐ Head level adjusted using the neck bracket.
Head Angle _____ degrees

- ☒ 24. If the dummy torso contacts the steering wheel while performing step 20, reposition the steering wheel in the following order to eliminate contact. (S16.3.2.1.9)
☒ N/A, No dummy torso contact with the steering wheel.
- ☐ 24.1 Adjust telescoping mechanism.
☐ N/A No telescoping adjustment.
☐ Adjustment performed (fill in appropriate change)
Steering wheel moved _____ detent positions in the forward direction.
Steering wheel moved _____ mm in the forward direction.
- ☐ 24.2 Adjust tilt mechanism.
☐ N/A No tilt adjustment.
☐ No adjustment performed.
☐ Adjustment performed.
Steering wheel moved _____ detent positions Upward/Downward.
(circle one)
Steering wheel moved _____ degrees Upward/Downward
- ☐ 24.3 Adjust Seat in the aft direction.
☐ No Adjustment performed.
☐ Seat moved aft _____ mm from original position.
☐ Seat moved aft _____ detent positions from the original position.
- ☒ 25. Measure and set the pelvic angle using the pelvic angle gage TE-2504. The pelvic angle should be 20.0 degrees \pm 2.5 degrees. If the pelvic angle cannot be set to the specified range because the head will not be level or because the dummy will have need major repositioning, adjust the pelvis as closely as possible to the angle range, but keep the head level. (S16.3.2.1.11)
☒ Pelvic angle set to 20.0 degrees \pm 2.5 degrees.
☐ Pelvic angle of 20.0 degrees not achieved, the angular difference was minimized.
☒ Record the pelvic angle. 21.8 degrees
- ☒ 26. Check the dummy for contact with the interior after completing adjustments. (S16.3.2.1.12)
☒ No contact.
☐ Dummy in contact with interior.
☐ Seat moved aft _____ mm from the previous position.
☐ Seat moved aft _____ detent positions from the previous position.
- ☒ 27. Check the dummy to see if additional interior clearance is obtained, allowing the seat to be moved forward. (S16.3.2.1.12)
☒ N/A, Seat already at foremost position.
☐ Clearance unchanged. No adjustments required.
☐ Additional clearance available
☐ Seat moved Forward _____ mm from the previous position.
☐ Seat moved Forward _____ detent positions from the previous position.
- ☒ 28. Driver's foot positioning, right foot. Place the foot perpendicular to the leg and determine if the heel contacts the floor pan at any leg position. If the heel contacts the floor pan proceed to step 29 otherwise, proceed to step 30. (S16.3.2.2.1)
- ☒ 29. Perform the following steps until either all steps are completed, or the foot contacts the accelerator pedal. Step 29.6 shall be completed in all cases. (S16.3.2.2.1(a))

X 29.1 With the rear of the heel contacting the floor pan, move the foot forward until pedal contact occurs or the foot is at the full forward position.

___ 29.2 If the vehicle has an adjustable accelerator pedal, move the pedals rearward until pedal contact occurs or the pedals reach the full rearward position.

___ 29.3 Extend the leg, allowing the heel to lose contact with the floor until the foot contacts the pedal. Do not raise the toe of the foot higher than the top of the accelerator pedal. If the foot does not contact the pedal, proceed to the next step. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)

___ 29.4 Angle the foot to achieve contact between the foot and the pedal. If the foot does not contact the pedal, return the foot to the perpendicular orientation. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)

___ 29.5 Align the centerline of the foot with the vertical-longitudinal plane passing through the center of the accelerator pedal. Place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)

X 29.6 Record foot position

X Pedal Contact achieved. Contact occurred at step 29.1.

X Heel contacts floor pan

___ Heel set _____ mm from floor pan.

___ Pedal Contact not achieved. Heel set _____ mm from the floor pan.




FIGURE G1

- ___30. Perform the following steps until either all steps are completed, or the foot contacts the accelerator pedal. Step 30.5 shall be completed in all cases.
 - ___30.1 Extend the leg until the foot contacts the pedal. Do not raise the toe of the foot higher than the top of the accelerator pedal. If the foot does not contact the pedal, proceed to the next step. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.1(b) & S16.3.2.2.3)
 - ___30.2 If the vehicle has an adjustable accelerator pedal, move the pedals rearward until pedal contact occurs or the pedals reach the full rearward position. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.1(b) & S16.3.2.2.3)
 - ___N/A No pedal adjustment
 - ___30.3 Angle the foot to achieve contact between the foot and the pedal. If the foot does not contact the pedal, return the foot to the perpendicular orientation. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.2 & S16.3.2.2.3)
 - ___30.4 Align the centerline of the foot in the same horizontal plane as the centerline of the accelerator pedal. Place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward. (S16.3.2.2.3)

30.5 Record foot position

 Pedal Contact achieved. Contact occurred at step .

 Heel set mm from floor pan.

 Pedal Contact not achieved. Heel set mm from the floor pan.

X31. Driver's foot positioning, left foot.

X31.1 Place the foot perpendicular to the leg and determine if the heel contacts the floor pan at any leg position. If the heel contacts the floor pan proceed to step 31.2, otherwise position the leg as perpendicular to the thigh as possible with the foot parallel to the floor pan. (S16.2.2.6)

X31.2 Place the foot on the toe board with the heel resting on the floor pan as close to the intersection of the floor pan and the toe board as possible. Adjust the angle of the foot if necessary to contact the toe board. If the foot will not contact the toe board, set the foot perpendicular to the leg, and set the heel on the floor pan as far forward as possible. Avoid contact with the brake pedal, clutch pedal, wheel well projection, and footrest. To avoid this contact use the following three manipulations in the order listed, with each subsequent option incorporating the previous, until contact is avoided: rotate the foot about the lower leg (abduction/adduction), plantar flex the foot, rotate the leg outboard about the hip. Movement should be the minimum amount necessary. If it is not possible to avoid all foot contact, give priority to avoiding brake or clutch pedal contact. (S16.2.2.4 & S16.2.2.5 & S16.2.2.7)

 No contact

XFoot rotated about the leg (abduction/adduction)

 Foot rotated about the leg, and foot plantar flexed

 Foot rotated about the leg, foot plantar flexed, and the leg rotated about the hip.

X31.3 Record foot position.

 Heel does not contact floor pan.

 Heel on floor pan and foot on toe board.

XHeel on floor pan and foot not on toe board.

X32. Driver arm/hand positioning.

X32.1 Place the dummy's upper arms adjacent to the torso with the arm centerlines as close to a vertical longitudinal plane as possible. (S16.3.2.3.1)

X32.2 Place the palms of the dummy in contact with the outer part of the steering wheel rim at its horizontal centerline with the thumbs over the steering wheel rim. (S16.3.2.3.2)

X32.3 If it is not possible to position the thumbs inside the steering wheel rim at its horizontal centerline, then position them above and as close to the horizontal centerline of the steering wheel rim as possible. (S16.3.2.3.3)

X32.4 Lightly tape the hands to the steering wheel rim so that if the hand of the test dummy is pushed upward by a force of not less than 9 N (2 lb) and not more than 22 N (5 lb), the tape releases the hand from the steering wheel rim. S16.3.2.3.4

X33. Adjustable head restraints

 N/A, there is no head restraint adjustment

- ☐ 33.1 If the head restraint has an automatic adjustment, leave it where the system positions the restraint after the dummy is placed in the seat. (S16.3.4.1) Go to 34.
- ☐ 33.2 Adjust each head restraint vertically so that the mid-horizontal plane determined in Data Sheet 14.1 is aligned with the center of gravity (CG) of the dummy head. (S16.3.4.3)
- ☒ 33.3 If the above position is not attainable, move the vertical center of the head restraint to the closest detent below the center of the head CG. (S16.3.4.3)
☐ N/A midpoint position attained in previous step
☒ Headrest set at nearest detent below the head CG
- ☐ 33.4 If the head restraint has a fore and aft adjustment, place the restraint in the foremost position or until contact with the head is made, whichever occurs first. (S16.3.4.4)
- ☒ 34. Driver and passenger manual belt adjustment (for tests conducted with a belted dummy). (S16.3.5) Unbelted Test
- ☒ 34.1 If an adjustable seat belt D-ring anchorage exists, place it in the manufacturer's design position for a 5th percentile adult female. (S16.3.5.1) **This information will be supplied by the COTR.**
- | | |
|-----------------------------------|----------------------|
| Manufacturer's specified position | <u>Unbelted Test</u> |
| Actual Position | <u>Unbelted Test</u> |
- ☐ 34.2 Place the Type 2 manual belt around the test dummy and fasten the latch. (S16.3.5.2)
- ☒ 34.3 Ensure that the dummy's head remains as level as possible. (S16.3.5.3)
- ☐ 34.4 Remove all slack from the lap belt. Pull the upper torso webbing out of the retractor and allow it to retract; repeat this operation four times. Apply a 9 N (2 lbf) to 18 N (4 lbf) tension load to the lap belt. If the belt system is equipped with a tension-relieving device, introduce the maximum amount of slack into the upper torso belt that is recommended by the manufacturer. If the belt system is not equipped with a tension-relieving device, allow the excess webbing in the shoulder belt to be retracted by the retractive force of the retractor. (S16.3.5.4)

REMARKS:

I certify that I have read and performed each instruction.

Signature: Jordan Haynes Date: 7/31/08

APPENDIX G

DUMMY POSITIONING PROCEDURES FOR 5th% PASSENGER TEST DUMMY CONFORMING TO SUBPART O OF PART 572

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Tim Bratz

NHTSA No.: C85302
Test Date: 7/31/08

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u> </u> 0 to 48 kmph	<u> </u> 0 to 56 kmph
DRIVER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	
PASSENGER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	

(Check this item ONLY if it applies to this vehicle.)

 The passenger seat adjustments are controlled by the adjustments made to the driver's seat. Therefore, positioning of the passenger dummy is made simultaneously with the driver dummy. Adjustments made to the seat to position the driver will over ride any adjustments that would normally be made to position the passenger. (S16.2.10.3)

- X 1. Place the SCRP in the full rearward, mid-height position, and mid-seat cushion angle, determined during the completion of Data Sheet 14.1. (S16.3.3.1.1)
- X 2. Fully recline the seat back. (S16.3.3.1.2)
 N/A seat back not adjustable.
- X 3. Place the dummy in the seat with the legs at an angle of 120 degrees to the thighs. The calves should not be touching the seat cushion. (S16.3.3.1.2)
- X 4. Position the dummy in the seat such that the midsagittal plane is coincident with the longitudinal seat cushion marking that was determined in Data Sheet 14.1. (S16.3.3.1.3 and S16.3.3.1.4)
- X 5. Hold down the dummy's thighs and push rearward on the upper torso to maximize the pelvic angle. (S16.3.3.1.5)
- X 6. Set the angle between the legs and the thighs to 120 degrees. (S16.3.3.1.6)
- X 7. Set the transverse distance between the centers of the front of the knees at 160 to 170 mm. (6.3 to 6.7 inches). Center the knee separation with respect to the longitudinal seat cushion marking that was determined Data Sheet 14.1. (S16.3.3.1.6)
Record Knee Separation 166
- X 8. Push rearward on the dummy's knees until the pelvis contacts the seat back, or the backs of the calves contact the seat cushion, whichever occurs first. (S16.3.3.1.6)
 Pelvis contacted seat back.
X Calves contacted seat cushion.
- X 9. Gently rock the upper torso \pm 5 degrees (approximately 51 mm (2 inches)) side-to-side three times. (S16.3.3.1.7)

- ☐ 15.2 Head level adjusted
- ☐ Head Level Achieved. (Check all that apply)
- ☐ Head leveled using the adjustable seat back
- ☐ Head leveled using the neck bracket.
- Head Angle _____ degrees
- ☐ Head Level NOT Achieved. (Check all that apply)
- ☐ Head adjusted using the adjustable seat back
- ☐ Head adjusted using the neck bracket.
- Head Angle _____ degrees
- ☒ 16. Measure and set the pelvic angle using the pelvic angle gage TE-2504. The pelvic angle should be 20.0 degrees \pm 2.5 degrees. If the pelvic angle cannot be set to the specified range because the head will not be level or because the dummy will have need major repositioning, adjust the pelvis as closely as possible to the angle range, but keep the head level.
- ☒ Pelvic angle set to 20.0 degrees \pm 2.5 degrees.
- ☐ Pelvic angle of 20.0 degrees not achieved, the angular difference was minimized.
- ☒ Record the pelvic angle. 20.1 degrees
- ☒ 17. Check the dummy for contact with the interior after completing adjustments.
- ☒ No contact.
- ☐ Dummy in contact with interior.
- ☐ Seat moved aft _____ mm from the previous position.
- ☐ Seat moved aft _____ detent positions from the previous position.
- ☒ 18. Verify the transverse instrument platform of the dummy head is level +/- 0.5 degrees. Use the lower neck bracket adjustment to level the head. If a level position cannot be achieved, minimize the angle. (S16.3.3.1.9, S16.3.3.1.10, and S16.3.3.1.11)
- ☒ Head Level Achieved
- Head Angle 0.3 degrees
- ☐ Head Level NOT Achieved.
- Head Angle _____ degrees
- ☒ 19. Check the dummy to see if additional interior clearance is obtained, allowing the seat to be moved forward. (S16.3.3.1.12)
- ☐ N/A Bench Seat
- ☒ N/A Seat already at full forward position.
- ☐ Clearance unchanged. No adjustments required.
- ☐ Additional clearance available
- ☐ Seat moved Forward _____ mm from the previous position.
- ☐ Seat moved Forward _____ detent positions from the previous position.
- ☐ Seat moved Forward, Full Forward position reached.
- ☒ 20. Passenger foot positioning. (Indicate final position achieved) (S16.3.3.2)
- ☐ 20.1 Place feet flat on the toe board; OR (S16.3.3.2.1)
- ☒ 20.2 If the feet cannot be placed flat on the toe board, set the feet perpendicular to the lower leg, and rest the heel as far forward on the floor pan as possible; OR (S16.3.3.2.2)
- ☐ 20.3 If the heels do not touch the floor pan, set the legs as perpendicular to the thighs as possible and set the feet parallel to the floor pan. (S16.3.3.2.2)
- ☒ 21. Passenger arm/hand positioning. (S16.3.3.3)

X 21.1 Place the dummy's upper arms adjacent to the torso with the arm centerlines as close to a vertical longitudinal plane as possible. (S16.3.3.3.1)

X 21.2 Place the palms of the dummy in contact with the outer part of the thighs (S16.3.3.3.2)

X 21.3 Place the little fingers in contact with the seat cushion. (S16.3.3.3.3)

X 22. Adjustable head restraints (S16.3.4)

___ N/A, there is no head restraint adjustment

___ 22.1 If the head restraint has an automatic adjustment, leave it where the system positions the restraint after the dummy is placed in the seat. (S16.3.4.1) Go to 23.

___ 22.2 Adjust each head restraint vertically so that the horizontal plane determined in Data Sheet 14.1 is aligned with the center of gravity (CG) of the dummy head. (S16.3.4.3)

X 22.3 If the above position is not attainable, move the vertical center of the head restraint to the closest detent below the center of the head CG. (S16.3.4.3)

___ N/A midpoint position attained in previous step

X Headrest set at nearest detent below the head CG

X 22.4 If the head restraint has a fore and aft adjustment, place the restraint in the foremost position or until contact with the head is made, whichever occurs first. (S16.3.4.4)

X 23. Manual belt adjustment (for tests conducted with a belted dummy) S16.3.5

X N/A, Unbelted test

___ 23.1 If an adjustable seat belt D-ring anchorage exists, place it in the manufacturer's design position for a 5th percentile adult female. (S16.3.5.1) **This information will be supplied by the COTR.**

Manufacturer's specified position	<u>Unbelted Test</u>
Actual Position	<u>Unbelted Test</u>

___ 23.2 Place the Type 2 manual belt around the test dummy and fasten the latch. (S16.3.5.2)

X 23.3 Ensure that the dummy's head remains as level as possible. (S16.3.5.3)

___ 23.4 Remove all slack from the lap belt. Pull the upper torso webbing out of the retractor and allow it to retract; repeat this operation four times. Apply a 9 N (2 lbf) to 18 N (4 lbf) tension load to the lap belt. If the belt system is equipped with a tension-relieving device, introduce the maximum amount of slack into the upper torso belt that is recommended by the manufacturer. If the belt system is not equipped with a tension-relieving device, allow the excess webbing in the shoulder belt to be retracted by the retractive force of the retractor. (S16.3.5.4)

REMARKS:

I certify that I have read and performed each instruction.

Signature:  Date: 7/31/08


DATA SHEET 37

DUMMY MEASUREMENTS

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Jordan Haynes

NHTSA No.: C85302
 Test Date: 7/31/08

DUMMY MEASUREMENTS FOR FRONT SEAT OCCUPANTS



DATA SHEET 37
DUMMY MEASUREMENTS


Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Joe Fleck

NHTSA No.: C85302
Test Date: 7/31/08

TEST DUMMY POSITION MEASUREMENTS

Code	Measurement Description	Driver SN 511		Passenger SN 516	
		Length (mm)	Angle (°)	Length (mm)	Angle (°)
WA	Windshield Angle		28.5		
SWA	Steering Wheel Angle		67.0		
SCA	Steering Column Angle		23.0		
SA	Seat Back Angle (On Headrest Post)		11.6		10.2
HZ	Head to Roof (Z)	238		225	
HH	Head to Header	318	37.5	299	48.7
HW	Head to Windshield	686	0.0	657	0.0
HR	Head to Side Header (Y)	280		253	
NR	Nose to Rim	301	1.6		
CD	Chest to Dash	492		397	
CS	Chest to Steering Hub	251	20.3		
RA	Rim to Abdomen	135	0.0		
KDL	Left Knee to Dash	104	23.4	109	
KDR	Right Knee to Dash	92		111	29.6
PA	Pelvic Angle		21.8		20.1
TA	Tibia Angle		54.3		49.1
KK	Knee to Knee (Y)	245		212	
SK	Striker to Knee	670	93.1	682	100.4
ST	Striker to Head	450	27.2	480	28.1
SH	Striker to H-Point	370	114.4	370	115.3
SHY	Striker to H-Point (Y)	300		304	
HS	Head to Side Window	368		356	
HD	H-Point to Door (Y)	190		195	
AD	Arm to Door (Y)	195		114	
AA	Ankle to Ankle	250		181	

SEAT BELT POSITIONING DATA



FRONT VIEW OF DUMMY

SEAT BELT POSITIONING MEASUREMENTS

Measurement Description	Units	Driver	Passenger
PBU - Top surface of reference to belt upper edge	mm	N/A	N/A
PBL - Top surface of reference to belt lower edge	mm	N/A	N/A

DATA SHEET 38

CRASH TEST

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Jordan Haynes

NHTSA No.: C85302
 Test Date: 7/31/08

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u> </u> 0 to 48 kmph	<u> </u> 0 to 56 kmph
DRIVER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	
PASSENGER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	

- | | |
|----------|---|
| <u>X</u> | 1. Vehicle underbody painted |
| <u>X</u> | 2. The speed measuring devices are in place and functioning. |
| <u>X</u> | 3. The speed measuring devices are <u>1.0</u> m from the barrier (spec. 1.5m) and <u>30</u> cm from the barrier (spec. is 30 cm) |
| <u>X</u> | 4. Convertible top is in the closed position. |
| <u>X</u> | <u>X</u> N/A, not a convertible |
| <u>X</u> | 5. Instrumentation and wires are placed so the motion of the dummies during impact is not affected. |
| <u>X</u> | 6. Tires inflated to pressure on tire placard or if it does not have a tire placard because it is not a passenger car, then inflated to the tire pressure specified in the owner information. |

<u>220 kpa</u> front left tire	<u>220 kpa</u> specified on tire placard or in owner information
<u>220 kpa</u> front right tire	<u>220 kpa</u> specified on tire placard or in owner information
<u>220 kpa</u> rear left tire	<u>220 kpa</u> specified on tire placard or in owner information
<u>220 kpa</u> rear right tire	<u>220 kpa</u> specified on tire placard or in owner information

- | | |
|----------|---|
| <u>X</u> | 7. Time zero contacts on barrier in place. |
| <u>X</u> | 8. Pre test zero and shunt calibration adjustments performed and recorded |
| <u>X</u> | 9. Dummy temperature meets requirements of section 12.2 of the test procedure. |
| <u>X</u> | 10. Vehicle hood closed and latched |
| <u>X</u> | 11. Transmission placed in neutral |
| <u>X</u> | 12. Parking brake off |
| <u>X</u> | 13. Ignition in the ON position |
| <u>X</u> | 14. Doors closed and latched but not locked |
| <u>X</u> | 15. Posttest zero and shunt calibration checks performed and recorded |
| <u>X</u> | 16. Actual test speed <u>39.8 kmph</u> |
| <u>X</u> | 17. Vehicle rebound from the barrier <u>314</u> cm |
| <u>X</u> | 18. Describe whether the doors open after the test and what method is used to open the doors. |
| <u>X</u> | Left Front Door: Door remained closed and latched; Door opened without tools |
| <u>X</u> | Right Front Door: Door remained closed and latched; Door opened without tools |
| <u>X</u> | Left Rear Door: Door remained closed and latched; Door opened without tools |
| <u>X</u> | Right Rear Door: Door remained closed and latched; Door opened without tools |

- ☒ 19. Describe the contact points of the dummy with the interior of the vehicle.
- ☒ Driver Dummy: Head to Air Bag and Headrest; Chest to Air Bag; Knees to Knee Bolster
 - ☒ Passenger Dummy: Head to Air Bag and Headrest; Chest to Air Bag; Knees to Glove Box

REMARKS:

I certify that I have read and performed each instruction.

Signature: *Jordan Haynes* Date: 7/31/08

DATA SHEET NO. 40

ACCIDENT INVESTIGATION MEASUREMENTS

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Jamie Aide

NHTSA No.: C85302
 Test Date: 7/31/08

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u> </u> 0 to 48 kmph	<u> </u> 0 to 56 kmph
DRIVER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	
PASSENGER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	

Vehicle Year/Make/Model/Body Style:	2008 Honda Accord Passenger Car
VIN:	1HGCP36798A003873
Wheelbase:	2797 mm
Build Date:	09/07
Vehicle Size Category:	3
Test Weight:	1749.1kg
Front Overhang:	958mm
Overall Width:	1849 mm
Overall Length Center:	4894 mm


Accelerometer Data	
Location:	As per measurements on Data Sheet 33
Linearity:	>99.9%

Integration Algorithm:	Trapezoidal
Vehicle Impact Speed:	39.8 kmph
Time of Separation:	117.8 ms
Velocity Change:	44.8 kmph

CRUSH PROFILE

Collision Deformation Classification: 12FDEW6
 Midpoint of Damage: Vehicle Longitudinal Centerline
 Damage Region Length (mm): 1140
 Impact Mode: Frontal Barrier

No.	Measurement Description	Units	Pre-Test	Post-Test	Difference
C1	Crush zone 1 at left side	mm	4766	4494	272
C2	Crush zone 2 at left side	mm	4864	4488	376
C3	Crush zone 3 at left side	mm	4886	4499	387
C4	Crush zone 4 at right side	mm	4887	4496	391
C5	Crush zone 5 at right side	mm	4864	4491	373
C6	Crush zone 6 at right side	mm	4766	4482	284



REMARKS:

I certify that I have read and performed each instruction.

Signature: *Janie C. [Signature]*

Date: 7/31/08

DATA SHEET 41
WINDSHIELD MOUNTING (FMVSS 212)

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Jamie Aide

NHTSA No.: C85302
 Test Date: 7/31/08

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u> </u> 0 to 48 kmph	<u> </u> 0 to 56 kmph
DRIVER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	
PASSENGER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	

1. Pre-Crash
 - ☒ 1.1 Describe from visual inspection how the windshield is mounted and describe any trim material.


Retained with glue
Rubber trim
 - ☒ 1.2 Mark the longitudinal centerline of the windshield
 - ☒ 1.3 Measure pre-crash A, B, and C for the left side and record in the chart below.
 - ☒ 1.4 Measure pre-crash C, D, and E for the right side and record in the chart below.
 - ☒ 1.5 Measure from the edge of the retainer or molding to the edge of the windshield.
Dimension G (mm): 16 mm
2. Post Crash
 - ☒ 2.1 Can a single thickness of copier type paper (as small a piece as necessary) slide between the windshield and the vehicle body?
 - ☒ No - Pass. Skip to the table of measurements, complete it by repeating the pre-crash measurements in the post crash column, and calculate the retention percentage, which will be 100%.
 - ☐ Yes, go to 2.2
 - ☐ 2.2 Visibly mark the beginning and end of the portions of the periphery where the paper slides between the windshield and the vehicle body.
 - ☐ 2.3 Measure and record post-crash A, B, C, D, E, and F such that the measurements do not include any of the parts of the windshield where the paper slides between the windshield and the vehicle body.
 - ☐ 2.4 Calculate and record the percent retention for the right and left side of the windshield.
 - ☐ 2.5 Is total right side percent retention less than 75%?
 - ☐ Yes, Fail
 - ☐ No, Pass
 - ☐ 2.6 Is total left side percent retention less than 75%?
 - ☐ Yes, Fail
 - ☐ No, Pass

WINDSHIELD RETENTION MEASUREMENTS

	Dimension	Pre-Crash (mm)	Post-Crash (mm)	Percent Retention (Post-Test ÷ Pre-Crash)
Left Side	A	599	599	100%
	B	811	811	100%
	C	765	765	100%
	Total	2175	2175	100%
Right Side	D	599	599	100%
	E	811	811	100%
	F	765	765	100%
	Total	2175	2175	100%

Indicate area of mounting failure. NONE

FRONT VIEW OF WINDSHIELD



REMARKS:

I certify that I have read and performed each instruction.

Signature:

Jamie Curtis

Date: 7/31/08

DATA SHEET 42
WINDSHIELD ZONE INTRUSION (FMVSS 219)


Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance
 Test Technician: Jamie Aide

NHTSA No.: C85302
 Test Date: 7/31/08

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u> </u> 0 to 48 kmph	<u> </u> 0 to 56 kmph
DRIVER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	
PASSENGER DUMMY:	<u>X</u> 5 th female	<u> </u> 50 th male	

- ☒ 1. Place a 165 mm diameter rigid sphere, with a mass of 6.8 kg on the instrument panel so that it is simultaneously touching the instrument panel and the windshield. (571.219 S6.1(a))
- ☒ 2. Roll the sphere from one side of the windshield to the other while marking on the windshield where the sphere contacts the windshield. (571.219 S6.1(b))
- ☒ 3. From the outermost contactable points on the windshield draw a horizontal line to the edges of the windshield. (571.219 S6.1(b))
- ☒ 4. Draw a line on the inner surface of the windshield that is 13 mm below the line determined in items 2 and 3
- ☒ 5. After the crash test, record any points where a part of the exterior of the vehicle has marked, penetrated, or broken the windshield.

Provide all dimensions necessary to reproduce the protected area.



WINDSHIELD DIMENSIONS

Item	Units	Value
A	mm	1198
B	mm	473
C	mm	1530
D	mm	811
E	mm	560
F	mm	517

AREA OF PROTECTED ZONE FAILURES:

- B. Provide coordinates of the area that the protected zone was penetrated more than 0.25 inches by a vehicle component other than one which is normally in contact with the windshield.

X	Y
NONE	

- C. Provide coordinates of the area beneath the protected zone template that the inner surface of the windshield was penetrated by a vehicle component.

X	Y
NONE	

REMARKS:

I certify that I have read and performed each instruction.

Signature:



Date: 7/31/08

DATA SHEET 43
FUEL SYSTEM INTEGRITY (FMVSS 301)

Test Vehicle: 2008 Honda Accord
Test Program: FMVSS 208 Compliance
Test Technician: Tim Bratz

NHTSA No.: C85302
Test Date: 7/31/08

TYPE OF IMPACT:	25 mph Unbelted Flat Frontal
-----------------	------------------------------

Stoddard Solvent Spillage Measurements


- A. From impact until vehicle motion ceases: 0.0 grams
(Maximum Allowable = 28 grams)
- B. For the 5 minute period after motion ceases: 0.0 grams
(Maximum Allowable = 142 grams)
- C. For the following 25 minutes: 0.0 grams
(Maximum Allowable = 28 grams/minute)
- D. Spillage: NONE

REMARKS: NO SPILLAGE

DATA SHEET NO. 43
FMVSS 301 STATIC ROLLOVER DATA

Test Vehicle: 2008 Honda Accord
 Test Program: FMVSS 208 Compliance

NHTSA No.: C85302
 Test Date: 7/31/08



1. The specified fixture rollover rate for each 90° of rotation is 60 to 180 seconds.
2. The position hold time at each position is 300 seconds (minimum).
3. Details of Stoddard Solvent spillage locations: **None**

Test Phase	Rotation Time (sec.)	Hold Time (sec.)	Spillage (grams)
0° to 90°	119	300	0.0
90° to 180°	114	300	0.0
180° to 270°	116	300	0.0
270° to 360°	114	300	0.0

APPENDIX A
CRASH TEST DATA

TABLE OF DATA PLOTS

		<u>Page No.</u>
Figure No. 1.	Driver Head X Acceleration vs. Time	A-1
Figure No. 2.	Driver Head Y Acceleration vs. Time	A-1
Figure No. 3.	Driver Head Z Acceleration vs. Time	A-1
Figure No. 4.	Driver Head Resultant Acceleration vs. Time	A-1
Figure No. 5.	Driver Head X Velocity vs. Time	A-2
Figure No. 6.	Driver Head Y Velocity vs. Time	A-2
Figure No. 7.	Driver Head Z Velocity vs. Time	A-2
Figure No. 8.	Driver Neck Force X vs. Time	A-3
Figure No. 9.	Driver Neck Force Y vs. Time	A-3
Figure No. 10.	Driver Neck Force Z vs. Time	A-3
Figure No. 11.	Driver Neck Force Resultant vs. Time	A-3
Figure No. 12.	Driver Neck Moment X vs. Time	A-4
Figure No. 13.	Driver Neck Moment Y vs. Time	A-4
Figure No. 14.	Driver Neck Moment Z vs. Time	A-4
Figure No. 15.	Driver Neck Moment Resultant vs. Time	A-4
Figure No. 16.	Driver Chest X Acceleration vs. Time	A-5
Figure No. 17.	Driver Chest Y Acceleration vs. Time	A-5
Figure No. 18.	Driver Chest Z Acceleration vs. Time	A-5
Figure No. 19.	Driver Chest Resultant Acceleration vs. Time	A-5
Figure No. 20.	Driver Chest X Velocity vs. Time	A-6
Figure No. 21.	Driver Chest Y Velocity vs. Time	A-6
Figure No. 22.	Driver Chest Z Velocity vs. Time	A-6
Figure No. 23.	Driver Chest Displacement vs. Time	A-6
Figure No. 24.	Driver Left Femur Force vs. Time	A-7
Figure No. 25.	Driver Right Femur Force vs. Time	A-7
Figure No. 26.	Passenger Head X Acceleration vs. Time	A-8
Figure No. 27.	Passenger Head Y Acceleration vs. Time	A-8
Figure No. 28.	Passenger Head Z Acceleration vs. Time	A-8
Figure No. 29.	Passenger Head Resultant Acceleration vs. Time	A-8





		<u>Page No.</u>
Figure No. 30.	Passenger Head X Velocity vs. Time	A-9
Figure No. 31.	Passenger Head Y Velocity vs. Time	A-9
Figure No. 32.	Passenger Head Z Velocity vs. Time	A-9
Figure No. 33.	Passenger Neck Force X vs. Time	A-10
Figure No. 34.	Passenger Neck Force Y vs. Time	A-10
Figure No. 35.	Passenger Neck Force Z vs. Time	A-10
Figure No. 36.	Passenger Neck Force Resultant vs. Time	A-10
Figure No. 37.	Passenger Neck Moment X vs. Time	A-11
Figure No. 38.	Passenger Neck Moment Y vs. Time	A-11
Figure No. 39.	Passenger Neck Moment Z vs. Time	A-11
Figure No. 40.	Passenger Neck Moment Resultant vs. Time	A-11
Figure No. 41.	Passenger Chest X Acceleration vs. Time	A-12
Figure No. 42.	Passenger Chest Y Acceleration vs. Time	A-12
Figure No. 43.	Passenger Chest Z Acceleration vs. Time	A-12
Figure No. 44.	Passenger Chest Resultant Acceleration vs. Time	A-12
Figure No. 45.	Passenger Chest X Velocity vs. Time	A-13
Figure No. 46.	Passenger Chest Y Velocity vs. Time	A-13
Figure No. 47.	Passenger Chest Z Velocity vs. Time	A-13
Figure No. 48.	Passenger Chest Displacement vs. Time	A-13
Figure No. 49.	Passenger Left Femur Force vs. Time	A-14
Figure No. 50.	Passenger Right Femur Force vs. Time	A-14
Figure No. 51.	Driver Nij (N_{TF}) vs. Time	A-15
Figure No. 52.	Driver Nij (N_{TE}) vs. Time	A-15
Figure No. 53.	Driver Nij (N_{CF}) vs. Time	A-15
Figure No. 54.	Driver Nij (N_{CE}) vs. Time	A-15
Figure No. 55.	Passenger Nij (N_{TF}) vs. Time	A-16
Figure No. 56.	Passenger Nij (N_{TE}) vs. Time	A-16
Figure No. 57.	Passenger Nij (N_{CF}) vs. Time	A-16
Figure No. 58.	Passenger Nij (N_{CE}) vs. Time	A-16
Figure No. 59.	Driver Occipital Condyle Moment vs. Time	A-17

		<u>Page No.</u>
Figure No. 60.	Passenger Occipital Condyle Moment vs. Time	A-17
Figure No. 61.	Left Rear Seat Crossmember X Acceleration vs. Time	A-18
Figure No. 62.	Left Rear Seat Crossmember X Velocity vs. Time	A-18
Figure No. 63.	Right Rear Seat Crossmember X Acceleration vs. Time	A-18
Figure No. 64.	Right Rear Seat Crossmember X Velocity vs. Time	A-18
Figure No. 65.	Top of Engine X Acceleration vs. Time	A-19
Figure No. 66.	Top of Engine X Velocity vs. Time	A-19
Figure No. 67.	Bottom of Engine X Acceleration vs. Time	A-19
Figure No. 68.	Bottom of Engine X Velocity vs. Time	A-19
Figure No. 69.	Left Brake Caliper X Acceleration vs. Time	A-20
Figure No. 70.	Left Brake Caliper X Velocity vs. Time	A-20
Figure No. 71.	Right Brake Caliper X Acceleration vs. Time	A-20
Figure No. 72.	Right Brake Caliper X Velocity vs. Time	A-20
Figure No. 73.	Instrument Panel X Acceleration vs. Time	A-21
Figure No. 74.	Instrument Panel X Velocity vs. Time	A-21
Figure No. 75.	Trunk Z Acceleration vs. Time	A-21
Figure No. 76.	Trunk Z Velocity vs. Time	A-21
Figure No. 77.	Barrier Force – Upper Left vs. Time	A-22
Figure No. 78.	Barrier Force – Upper Center vs. Time	A-22
Figure No. 79.	Barrier Force – Upper Right vs. Time	A-22
Figure No. 80.	Barrier Force – Lower Left vs. Time	A-23
Figure No. 81.	Barrier Force – Lower Center vs. Time	A-23
Figure No. 82.	Barrier Force – Lower Right vs. Time	A-23
Figure No. 83.	Barrier Force – Sum Left vs. Time	A-24
Figure No. 84.	Barrier Force – Sum Center vs. Time	A-24
Figure No. 85.	Barrier Force – Sum Right vs. Time	A-24
Figure No. 86.	Barrier Force – Sum All vs. Time	A-24




25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)

Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)







DRIVER HEAD X Velocity (kph) vs TIME (ms)



DRIVER HEAD Y Velocity (kph) vs TIME (ms)







DRIVER HEAD Z Velocity (kph) vs TIME (ms)





25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)





Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)





25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)





Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)





25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)

Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)







25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)

Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)


DRIVER CHEST X Velocity (kph) vs TIME (ms)




DRIVER CHEST Y Velocity (kph) vs TIME (ms)



DRIVER CHEST Z Velocity (kph) vs TIME (ms)




DRIVER CHEST DISPLACEMENT (mm) vs TIME (ms)





25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)





Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)





25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)

Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)







25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)

Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)


PASSENGER HEAD X Velocity (kph) vs TIME (ms)



PASSENGER HEAD Y Velocity (kph) vs TIME (ms)



PASSENGER HEAD Z Velocity (kph) vs TIME (ms)






25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)


Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)

PASSENGER NECK FX (N) vs TIME (ms)




Max: 1499.4 N
Tmax: 71.3 ms
Min: -140.8 N
Tmin: 173.4 ms
CFC 1000

PASSENGER NECK FY (N) vs TIME (ms)




Max: 362.5 N
Tmax: 94.9 ms
Min: -102.9 N
Tmin: 164.9 ms
CFC 1000

PASSENGER NECK FZ (N) vs TIME (ms)



Max: 507.3 N
Tmax: 41.0 ms
Min: -662.3 N
Tmin: 80.0 ms
CFC 1000

PASSENGER NECK FResultant (N) vs TIME (ms)







Max: 1616.3 N
Tmax: 72.9 ms
Min: 0.2 N
Tmin: 0.0 ms
CFC 1000



25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)

Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)







25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)

Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)


PASSENGER CHEST X (G's) vs TIME (ms)




PASSENGER CHEST Y (G's) vs TIME (ms)







PASSENGER CHEST Z (G's) vs TIME (ms)



PASSENGER CHEST Resultant (G's) vs TIME (ms)









25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)

Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)







25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)

Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)


Drv. nij (NTF) () vs TIME (ms)




Drv. nij (NTE) () vs TIME (ms)



Drv. nij (NCF) () vs TIME (ms)



Drv. nij (NCE) () vs TIME (ms)






25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)


Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)

Pass. nij (NTF) () vs TIME (ms)




Max: 0.2
Tmax: 53.9 ms
Min: 0.0
Tmin: 0.0 ms
CFC 600

Pass. nij (NTE) () vs TIME (ms)




Max: 0.1
Tmax: 41.1 ms
Min: 0.0
Tmin: 0.0 ms
CFC 600

Pass. nij (NCF) () vs TIME (ms)



Max: 0.7
Tmax: 72.8 ms
Min: 0.0
Tmin: 0.0 ms
CFC 600

Pass. nij (NCE) () vs TIME (ms)





Max: 0.2
Tmax: 117.3 ms
Min: 0.0
Tmin: 0.0 ms
CFC 600



25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)





Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)









25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)

Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)











25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)





Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)





25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)




Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)





25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)




Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)





25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)





Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)





25 MPH FRONTAL UNBELTED
2008 HONDA ACCORD (C85302)

Test Date: 07/31/2008
Speed: 24.7 mph (39.8 km/h)



APPENDIX B
LOW RISK TEST DATA

TABLE OF DATA PLOTS

	<u>Page No.</u>
Figure No. 1. 5 th Fem. P1 Driver Head X Acceleration vs. Time	B-1
Figure No. 2. 5 th Fem. P1 Driver Head Y Acceleration vs. Time	B-1
Figure No. 3. 5 th Fem. P1 Driver Head Z Acceleration vs. Time	B-1
Figure No. 4. 5 th Fem. P1 Driver Head Resultant Acceleration vs. Time	B-1
Figure No. 5. 5 th Fem. P1 Driver Head X Velocity vs. Time	B-2
Figure No. 6. 5 th Fem. P1 Driver Head Y Velocity vs. Time	B-2
Figure No. 7. 5 th Fem. P1 Driver Head Z Velocity vs. Time	B-2
Figure No. 8. 5 th Fem. P1 Driver Neck Force X vs. Time	B-3
Figure No. 9. 5 th Fem. P1 Driver Neck Force Y vs. Time	B-3
Figure No. 10. 5 th Fem. P1 Driver Neck Force Z vs. Time	B-3
Figure No. 11. 5 th Fem. P1 Driver Neck Force Resultant vs. Time	B-3
Figure No. 12. 5 th Fem. P1 Driver Neck Moment X vs. Time	B-4
Figure No. 13. 5 th Fem. P1 Driver Neck Moment Y vs. Time	B-4
Figure No. 14. 5 th Fem. P1 Driver Neck Moment Z vs. Time	B-4
Figure No. 15. 5 th Fem. P1 Driver Occipital Condyle Moment vs. Time	B-4
Figure No. 16. 5 th Fem. P1 Driver Chest X Acceleration vs. Time	B-5
Figure No. 17. 5 th Fem. P1 Driver Chest Y Acceleration vs. Time	B-5
Figure No. 18. 5 th Fem. P1 Driver Chest Z Acceleration vs. Time	B-5
Figure No. 19. 5 th Fem. P1 Driver Chest Resultant Acceleration vs. Time	B-5
Figure No. 20. 5 th Fem. P1 Driver Chest X Velocity vs. Time	B-6
Figure No. 21. 5 th Fem. P1 Driver Chest Y Velocity vs. Time	B-6
Figure No. 22. 5 th Fem. P1 Driver Chest Z Velocity vs. Time	B-6
Figure No. 23. 5 th Fem. P1 Driver Chest Displacement vs. Time	B-6
Figure No. 24. 5 th Fem. P1 Driver Left Femur Force vs. Time	B-7
Figure No. 25. 5 th Fem. P1 Driver Right Femur Force vs. Time	B-7
Figure No. 26. Fire Voltage #1 vs. Time	B-8
Figure No. 27. Fire Current #1 vs. Time	B-8
Figure No. 28. Fire Voltage #2 vs. Time	B-8
Figure No. 29. Fire Current #2 vs. Time	B-8

Figure No. 30.	5 th Fem. P1 Driver Nij (N_{TF}) vs. Time	B-9
Figure No. 31.	5 th Fem. P1 Driver Nij (N_{TE}) vs. Time	B-9
Figure No. 32.	5 th Fem. P1 Driver Nij (N_{CF}) vs. Time	B-9
Figure No. 33.	5 th Fem. P1 Driver Nij (N_{CE}) vs. Time	B-9
Figure No. 34.	5 th Fem. P2 Driver Head X Acceleration vs. Time	B-10
Figure No. 35.	5 th Fem. P2 Driver Head Y Acceleration vs. Time	B-10
Figure No. 36.	5 th Fem. P2 Driver Head Z Acceleration vs. Time	B-10
Figure No. 37.	5 th Fem. P2 Driver Head Resultant Acceleration vs. Time	B-10
Figure No. 38.	5 th Fem. P2 Driver Head X Velocity vs. Time	B-11
Figure No. 39.	5 th Fem. P2 Driver Head Y Velocity vs. Time	B-11
Figure No. 40.	5 th Fem. P2 Driver Head Z Velocity vs. Time	B-11
Figure No. 41.	5 th Fem. P2 Driver Neck Force X vs. Time	B-12
Figure No. 42.	5 th Fem. P2 Driver Neck Force Y vs. Time	B-12
Figure No. 43.	5 th Fem. P2 Driver Neck Force Z vs. Time	B-12
Figure No. 44.	5 th Fem. P2 Driver Neck Force Resultant vs. Time	B-12
Figure No. 45.	5 th Fem. P2 Driver Neck Moment X vs. Time	B-13
Figure No. 46.	5 th Fem. P2 Driver Neck Moment Y vs. Time	B-13
Figure No. 47.	5 th Fem. P2 Driver Neck Moment Z vs. Time	B-13
Figure No. 48.	5 th Fem. P2 Driver Occipital Condyle Moment vs. Time	B-13
Figure No. 49.	5 th Fem. P2 Driver Chest X Acceleration vs. Time	B-14
Figure No. 50.	5 th Fem. P2 Driver Chest Y Acceleration vs. Time	B-14
Figure No. 51.	5 th Fem. P2 Driver Chest Z Acceleration vs. Time	B-14
Figure No. 52.	5 th Fem. P2 Driver Chest Resultant Acceleration vs. Time	B-14
Figure No. 53.	5 th Fem. P2 Driver Chest X Velocity vs. Time	B-15
Figure No. 54.	5 th Fem. P2 Driver Chest Y Velocity vs. Time	B-15
Figure No. 55.	5 th Fem. P2 Driver Chest Z Velocity vs. Time	B-15
Figure No. 56.	5 th Fem. P2 Driver Chest Displacement vs. Time	B-15
Figure No. 57.	5 th Fem. P2 Driver Left Femur Force vs. Time	B-16
Figure No. 58.	5 th Fem. P2 Driver Right Femur Force vs. Time	B-16
Figure No. 59.	Fire Voltage #1 vs. Time	B-17

	<u>Page No.</u>
Figure No. 60. Fire Current #1 vs. Time	B-17
Figure No. 61. Fire Voltage #2 vs. Time	B-17
Figure No. 62. Fire Current #2 vs. Time	B-17
Figure No. 63. 5 th Fem. P2 Driver Nij (N_{TF}) vs. Time	B-18
Figure No. 64. 5 th Fem. P2 Driver Nij (N_{TE}) vs. Time	B-18
Figure No. 65. 5 th Fem. P2 Driver Nij (N_{CF}) vs. Time	B-18
Figure No. 66. 5 th Fem. P2 Driver Nij (N_{CE}) vs. Time	B-18
Figure No. 67. 6YO P1 Passenger Head X Acceleration vs. Time	B-19
Figure No. 68. 6YO P1 Passenger Head Y Acceleration vs. Time	B-19
Figure No. 69. 6YO P1 Passenger Head Z Acceleration vs. Time	B-19
Figure No. 70. 6YO P1 Passenger Head Resultant Acceleration vs. Time	B-19
Figure No. 71. 6YO P1 Passenger Head X Velocity vs. Time	B-20
Figure No. 72. 6YO P1 Passenger Head Y Velocity vs. Time	B-20
Figure No. 73. 6YO P1 Passenger Head Z Velocity vs. Time	B-20
Figure No. 74. 6YO P1 Passenger Neck Force X vs. Time	B-21
Figure No. 75. 6YO P1 Passenger Neck Force Y vs. Time	B-21
Figure No. 76. 6YO P1 Passenger Neck Force Z vs. Time	B-21
Figure No. 77. 6YO P1 Passenger Neck Force Resultant vs. Time	B-21
Figure No. 78. 6YO P1 Passenger Neck Moment X vs. Time	B-22
Figure No. 79. 6YO P1 Passenger Neck Moment Y vs. Time	B-22
Figure No. 80. 6YO P1 Passenger Neck Moment Z vs. Time	B-22
Figure No. 81. 6YO P1 Passenger Occipital Condyle Moment vs. Time	B-22
Figure No. 82. 6YO P1 Passenger Chest X Acceleration vs. Time	B-23
Figure No. 83. 6YO P1 Passenger Chest Y Acceleration vs. Time	B-23
Figure No. 84. 6YO P1 Passenger Chest Z Acceleration vs. Time	B-23
Figure No. 85. 6YO P1 Passenger Chest Resultant Acceleration vs. Time	B-23
Figure No. 86. 6YO P1 Passenger Chest X Velocity vs. Time	B-24
Figure No. 87. 6YO P1 Passenger Chest Y Velocity vs. Time	B-24
Figure No. 88. 6YO P1 Passenger Chest Z Velocity vs. Time	B-24
Figure No. 89. 6YO P1 Passenger Chest Displacement vs. Time	B-24

Figure No. 90.	Fire Voltage #1 vs. Time	B-25
Figure No. 91.	Fire Current #1 vs. Time	B-25
Figure No. 92.	Fire Voltage #2 vs. Time	B-25
Figure No. 93.	Fire Current #2 vs. Time	B-25
Figure No. 94.	6YO P1 Passenger Nij (N_{TF}) vs. Time	B-26
Figure No. 95.	6YO P1 Passenger Nij (N_{TE}) vs. Time	B-26
Figure No. 96.	6YO P1 Passenger Nij (N_{CF}) vs. Time	B-26
Figure No. 97.	6YO P1 Passenger Nij (N_{CE}) vs. Time	B-26
Figure No. 98.	6YO P2 Passenger Head X Acceleration vs. Time	B-27
Figure No. 99.	6YO P2 Passenger Head Y Acceleration vs. Time	B-27
Figure No. 100.	6YO P2 Passenger Head Z Acceleration vs. Time	B-27
Figure No. 101.	6YO P2 Passenger Head Resultant Acceleration vs. Time	B-27
Figure No. 102.	6YO P2 Passenger Head X Velocity vs. Time	B-28
Figure No. 103.	6YO P2 Passenger Head Y Velocity vs. Time	B-28
Figure No. 104.	6YO P2 Passenger Head Z Velocity vs. Time	B-28
Figure No. 105.	6YO P2 Passenger Neck Force X vs. Time	B-29
Figure No. 106.	6YO P2 Passenger Neck Force Y vs. Time	B-29
Figure No. 107.	6YO P2 Passenger Neck Force Z vs. Time	B-29
Figure No. 108.	6YO P2 Passenger Neck Force Resultant vs. Time	B-29
Figure No. 109.	6YO P2 Passenger Neck Moment X vs. Time	B-30
Figure No. 110.	6YO P2 Passenger Neck Moment Y vs. Time	B-30
Figure No. 111.	6YO P2 Passenger Neck Moment Z vs. Time	B-30
Figure No. 112.	6YO P2 Passenger Occipital Condyle Moment vs. Time	B-30
Figure No. 113.	6YO P2 Passenger Chest X Acceleration vs. Time	B-31
Figure No. 114.	6YO P2 Passenger Chest Y Acceleration vs. Time	B-31
Figure No. 115.	6YO P2 Passenger Chest Z Acceleration vs. Time	B-31
Figure No. 116.	6YO P2 Passenger Chest Resultant Acceleration vs. Time	B-31
Figure No. 117.	6YO P2 Passenger Chest X Velocity vs. Time	B-32
Figure No. 118.	6YO P2 Passenger Chest Y Velocity vs. Time	B-32
Figure No. 119.	6YO P2 Passenger Chest Z Velocity vs. Time	B-32

Page No.





Figure No. 120.	6YO P2 Passenger Chest Displacement vs. Time	B-32
Figure No. 121.	Fire Voltage #1 vs. Time	B-33
Figure No. 122.	Fire Current #1 vs. Time	B-33
Figure No. 123.	Fire Voltage #2 vs. Time	B-33
Figure No. 124.	Fire Current #2 vs. Time	B-33
Figure No. 125.	6YO P2 Passenger Nij (N_{TF}) vs. Time	B-34
Figure No. 126.	6YO P2 Passenger Nij (N_{TE}) vs. Time	B-34
Figure No. 127.	6YO P2 Passenger Nij (N_{CF}) vs. Time	B-34
Figure No. 128.	6YO P2 Passenger Nij (N_{CE}) vs. Time	B-34



LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (5th P1)




Test Date: 7/7/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 165ms






Injury Values Calculated between 0ms and 165ms






Injury Values Calculated between 0ms and 165ms


5TH FEM. DRIVER NECK FX (N) vs TIME (ms)




5TH FEM. DRIVER NECK FY (N) vs TIME (ms)



5TH FEM. DRIVER NECK FZ (N) vs TIME (ms)







5TH FEM. DRIVER NECK FResultant (N) vs TIME (ms)





Injury Values Calculated between 0ms and 165ms









LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (5th P1)





Test Date: 7/7/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 165ms







Injury Values Calculated between 0ms and 165ms






Injury Values Calculated between 0ms and 165ms






Injury Values Calculated between 0ms and 165ms


FIRE VOLTAGE #1 (Volts) vs TIME (ms)




FIRE CURRENT #1 (Amps) vs TIME (ms)



FIRE VOLTAGE #2 (Volts) vs TIME (ms)




FIRE CURRENT #2 (Amps) vs TIME (ms)







Drv. nij (NTF) () vs TIME SPECIAL CHS (ms)




Drv. nij (NTE) () vs TIME SPECIAL CHS (ms)



Drv. nij (NCF) () vs TIME SPECIAL CHS (ms)



Drv. nij (NCE) () vs TIME SPECIAL CHS (ms)









LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (5th P2)




Test Date: 7/7/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 165ms









Injury Values Calculated between 0ms and 165ms






Injury Values Calculated between 0ms and 165ms






Injury Values Calculated between 0ms and 165ms


5TH FEM. DRIVER NECK MX (Nm) vs TIME (ms)




5TH FEM. DRIVER NECK MY (Nm) vs TIME (ms)



5TH FEM. DRIVER NECK MZ (Nm) vs TIME (ms)







Drv. Occipital Condyle Moment (Nm) vs TIME (ms)









Injury Values Calculated between 0ms and 165ms







Injury Values Calculated between 0ms and 165ms






Injury Values Calculated between 0ms and 165ms






Injury Values Calculated between 0ms and 165ms


FIRE VOLTAGE #1 (Volts) vs TIME (ms)




FIRE CURRENT #1 (Amps) vs TIME (ms)







FIRE VOLTAGE #2 (Volts) vs TIME (ms)



FIRE CURRENT #2 (Amps) vs TIME (ms)











LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (6YO P1)




Test Date: 7/7/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 100ms





Injury Values Calculated between 0ms and 100ms






LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (6YO P1)


Test Date: 7/7/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 100ms


6YR OLD PASSENGER NECK FX (N) vs TIME (ms)




6YR OLD PASSENGER NECK FY (N) vs TIME (ms)



6YR OLD PASSENGER NECK FZ (N) vs TIME (ms)



6YR OLD PASSENGER NECK FResultant (N) vs TIME (ms)









LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (6YO P1)

Test Date: 7/7/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 100ms









LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (6YO P1)

Test Date: 7/7/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 100ms









LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (6YO P1)





Test Date: 7/7/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 100ms






Injury Values Calculated between 0ms and 100ms







PASS. nij (NTF) () vs TIME SPECIAL CHS (ms)




Pass. nij (NTE) () vs TIME SPECIAL CHS (ms)



Pass. nij (NCF) () vs TIME SPECIAL CHS (ms)



Pass. nij (NCE) () vs TIME SPECIAL CHS (ms)









LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (6YO P2)

Test Date: 7/8/08
Speed: 0.0 mph (0.0 km/h)


Injury Values Calculated between 0ms and 100ms






Injury Values Calculated between 0ms and 100ms


6YR OLD PASSENGER HEAD X Velocity (kph) vs TIME (ms)



6YR OLD PASSENGER HEAD Y Velocity (kph) vs TIME (ms)



6YR OLD PASSENGER HEAD Z Velocity (kph) vs TIME (ms)






LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (6YO P2)


Test Date: 7/8/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 100ms


6YR OLD PASSENGER NECK FX (N) vs TIME (ms)




6YR OLD PASSENGER NECK FY (N) vs TIME (ms)



6YR OLD PASSENGER NECK FZ (N) vs TIME (ms)



6YR OLD PASSENGER NECK FResultant (N) vs TIME (ms)






LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (6YO P2)


Test Date: 7/8/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 100ms


6YR OLD PASSENGER NECK MX (Nm) vs TIME (ms)




6YR OLD PASSENGER NECK MY (Nm) vs TIME (ms)



6YR OLD PASSENGER NECK MZ (Nm) vs TIME (ms)



Pass. Occipital Condyle Moment (Nm) vs TIME (ms)









LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (6YO P2)

Test Date: 7/8/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 100ms






LOW RISK DEPLOYMENT
2008 Honda Accord (C85302) (6YO P2)


Test Date: 7/8/08
Speed: 0.0 mph (0.0 km/h)

Injury Values Calculated between 0ms and 100ms


6YR OLD PASSENGER CHEST X Velocity (kph) vs TIME (ms)




6YR OLD PASSENGER CHEST Y Velocity (kph) vs TIME (ms)



6YR OLD PASSENGER CHEST Z Velocity (kph) vs TIME (ms)







6YR OLD PASSENGER CHEST DISPLACEMENT (mm) vs TIME (ms)






Injury Values Calculated between 0ms and 100ms







PASS. nij (NTF) () vs TIME SPECIAL CHS (ms)




Pass. nij (NTE) () vs TIME SPECIAL CHS (ms)



Pass. nij (NCF) () vs TIME SPECIAL CHS (ms)



Pass. nij (NCE) () vs TIME SPECIAL CHS (ms)




APPENDIX C
CRASH TEST PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

		<u>Page No.</u>
Photo No. 1.	Vehicle Certification Label	C-1
Photo No. 2.	Tire Placard	C-2
Photo No. 3.	Pre-Test Front View of Test Vehicle	C-3
Photo No. 4.	Post-Test Front View of Test Vehicle	C-4
Photo No. 5.	Pre-Test Left Side View of Test Vehicle	C-5
Photo No. 6.	Post-Test Left Side View of Test Vehicle	C-6
Photo No. 7.	Pre-Test Right Side View of Test Vehicle	C-7
Photo No. 8.	Post-Test Right Side View of Test Vehicle	C-8
Photo No. 9.	Pre-Test Right Front Three-Quarter View of Test Vehicle	C-9
Photo No. 10.	Post-Test Right Front Three-Quarter View of Test Vehicle	C-10
Photo No. 11.	Pre-Test Left Front Three-Quarter View of Test Vehicle	C-11
Photo No. 12.	Post-Test Left Front Three-Quarter View of Test Vehicle	C-12
Photo No. 13.	Pre-Test Right Rear Three-Quarter View of Test Vehicle	C-13
Photo No. 14.	Post-Test Right Rear Three-Quarter View of Test Vehicle	C-14
Photo No. 15.	Pre-Test Left Rear Three-Quarter View of Test Vehicle	C-15
Photo No. 16.	Post-Test Left Rear Three-Quarter View of Test Vehicle	C-16
Photo No. 17.	Pre-Test Rear View of Test Vehicle	C-17
Photo No. 18.	Post-Test Rear View of Test Vehicle	C-18
Photo No. 19.	Pre-Test Windshield View	C-19
Photo No. 20.	Post-Test Windshield View	C-20
Photo No. 21.	Pre-Test Engine Compartment View	C-21
Photo No. 22.	Post-Test Engine Compartment View	C-22
Photo No. 23.	Pre-Test Fuel Filler Cap View	C-23
Photo No. 24.	Post-Test Fuel Filler Cap View	C-24
Photo No. 25.	Pre-Test Front Underbody View	C-25

	<u>Page No.</u>
Photo No. 26. Post-Test Front Underbody View	C-26
Photo No. 27. Pre-Test Mid Underbody View	C-27
Photo No. 28. Post-Test Mid Underbody View	C-28
Photo No. 29. Pre-Test Rear Underbody View	C-29
Photo No. 30. Post-Test Rear Underbody View	C-30
Photo No. 31. Pre-Test Driver Dummy Front View (Head Position)	C-31
Photo No. 32. Post-Test Driver Dummy Front View (Head Position)	C-32
Photo No. 33. Pre-Test Driver Dummy Position Left Side View	C-33
Photo No. 34. Post-Test Driver Dummy Position Left Side View	C-34
Photo No. 35. Pre-Test Driver Dummy Position Left Side View (Door Open)	C-35
Photo No. 36. Post-Test Driver Dummy Position Left Side View (Door Open)	C-36
Photo No. 37. Pre-Test Driver Dummy Seat Position	C-37
Photo No. 38. Post-Test Driver Dummy Seat Position	C-38
Photo No. 39. Pre-Test Driver Dummy Feet Position	C-39
Photo No. 40. Post-Test Driver Dummy Feet Position	C-40
Photo No. 41. Pre-Test Driver Side Knee Bolster View	C-41
Photo No. 42. Post-Test Driver Side Knee Bolster View	C-42
Photo No. 43. Post-Test Driver Dummy Airbag Contact	C-43
Photo No. 44. Post-Test Driver Dummy Head Contact (Headrest)	C-44
Photo No. 45. Post-Test Driver Dummy Knee Contact	C-45
Photo No. 46. Pre-Test Passenger Dummy Front View (Head Position)	C-46
Photo No. 47. Post-Test Passenger Dummy Front View (Head Position)	C-47
Photo No. 48. Pre-Test Passenger Dummy Position Right Side View	C-48
Photo No. 49. Post-Test Passenger Dummy Position Right Side View	C-49
Photo No. 50. Pre-Test Passenger Dummy Position Right Side View (Door Open)	C-50
Photo No. 51. Post-Test Passenger Dummy Position Right Side View (Door Open)	C-51
Photo No. 52. Pre-Test Passenger Dummy Seat Position	C-52

	<u>Page No.</u>
Photo No. 53. Post-Test Passenger Dummy Seat Position	C-53
Photo No. 54. Pre-Test Passenger Dummy Feet Position	C-54
Photo No. 55. Post-Test Passenger Dummy Feet Position	C-55
Photo No. 56. Pre-Test Passenger Side Knee Bolster View	C-56
Photo No. 57. Post-Test Passenger Side Knee Bolster View	C-57
Photo No. 58. Post-Test Passenger Dummy Airbag Contact	C-58
Photo No. 59. Post-Test Passenger Dummy Head Contact (Headrest)	C-59
Photo No. 60. Post-Test Passenger Dummy Knee Contact	C-60
Photo No. 61. Rollover 90 Degrees	C-61
Photo No. 62. Rollover 180 Degrees	C-62
Photo No. 63. Rollover 270 Degrees	C-63
Photo No. 64. Rollover 360 Degrees	C-64
Photo No. 65. Temperature Plot	C-65
Photo No. 66. Vehicle in Relation to The Load Cell Grid	C-66



Vehicle Certification Label



Tire Placard



Pre-Test Front View of Test Vehicle



Post-Test Front View of Test Vehicle



Pre-Test Left Side View of Test Vehicle



Post-Test Left Side View of Test Vehicle



Pre-Test Right Side View of Test Vehicle



Post-Test Right Side View of Test Vehicle



Pre-Test Right Front Three-Quarter View of Test Vehicle



Post-Test Right Front Three-Quarter View of Test Vehicle



Pre-Test Left Front Three-Quarter View of Test Vehicle



Post-Test Left Front Three-Quarter View of Test Vehicle



Pre-Test Right Rear Three-Quarter View of Test Vehicle



Post-Test Right Rear Three-Quarter View of Test Vehicle



Pre-Test Left Rear Three-Quarter View of Test Vehicle



Post-Test Left Rear Three-Quarter View of Test Vehicle



Pre-Test Rear View of Test Vehicle



Post-Test Rear View of Test Vehicle



Pre-Test Windshield View




Post-Test Windshield View

C-21.



Pre-Test Engine Compartment View




Post-Test Engine Compartment View




Pre-Test Fuel Filler Cap View



Post-Test Fuel Filler Cap View



Pre-Test Front Underbody View




mga research corporation
POST-TEST
C85302
25 MPH FRONTAL
08073101
MGA RESEARCH CORP.
2006 HONDA ACCORD


Post-Test Front Underbody View




Pre-Test Mid Underbody View



Post-Test Mid Underbody View



Pre-Test Rear Underbody View



Post-Test Rear Underbody View



Pre-Test Driver Dummy Front View (Head Position)



Post-Test Driver Dummy Front View (Head Position)



Pre-Test Driver Dummy Position Left Side View

C-34.



Post-Test Driver Dummy Position Left Side View



Pre-Test Driver Dummy Position Left Side View (Door Open)



Post-Test Driver Dummy Position Left Side View (Door Open)



Pre-Test Driver Dummy Seat Position



Post-Test Driver Dummy Seat Position




Pre-Test Driver Dummy Feet Position




Post-Test Driver Dummy Feet Position

C-41.



Pre-Test Driver Side Knee Bolster View



Post-Test Driver Side Knee Bolster View



Post-Test Driver Dummy Airbag Contact



Post-Test Driver Dummy Head Contact (Headrest)

C-45.



Post-Test Driver Dummy Knee Contact



Pre-Test Passenger Dummy Front View (Head Position)



Post-Test Passenger Dummy Front View (Head Position)



Pre-Test Passenger Dummy Position Right Side View



Post-Test Passenger Dummy Position Right Side View



Pre-Test Passenger Dummy Position Right Side View (Door Open)



Post-Test Passenger Dummy Position Right Side View (Door Open)



Pre-Test Passenger Dummy Seat Position



Post-Test Passenger Dummy Seat Position



Pre-Test Passenger Dummy Feet Position



Post-Test Passenger Dummy Feet Position



Pre-Test Passenger Side Knee Bolster View



Post-Test Passenger Side Knee Bolster View



Post-Test Passenger Dummy Airbag Contact




Post-Test Passenger Dummy Head Contact (Headrest)

C-60.



Post-Test Passenger Dummy Knee Contact

C-61.



Rollover 90 Degrees

C-62.



Rollover 180 Degrees

C-63.




Rollover 270 Degrees

C-64.



Rollover 360 Degrees



Temperature Plot



Vehicle in Relation to The Load Cell Grid

APPENDIX D
LOW RISK PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

	<u>Page No.</u>
Photo No. 1. Pre-Test 5 th Fem. P1 Driver Dummy Left Side View	D-1
Photo No. 2. Post-Test 5 th Fem. P1 Driver Dummy Left Side View	D-2
Photo No. 3. Pre-Test 5 th Fem. P1 Driver Dummy Right Side View	D-3
Photo No. 4. Post-Test 5 th Fem. P1 Driver Dummy Right Side View	D-4
Photo No. 5. Post-Test 5 th Fem. P1 Driver Dummy Airbag Left Side View	D-5
Photo No. 6. Post-Test 5 th Fem. P1 Driver Dummy Airbag Right Side View	D-6
Photo No. 7. Pre-Test 5 th Fem. P2 Driver Dummy Left Side View	D-7
Photo No. 8. Post-Test 5 th Fem. P2 Driver Dummy Left Side View	D-8
Photo No. 9. Pre-Test 5 th Fem. P2 Driver Dummy Right Side View	D-9
Photo No. 10. Post-Test 5 th Fem. P2 Driver Dummy Right Side View	D-10
Photo No. 11. Post-Test 5 th Fem. P2 Driver Dummy Airbag Left Side View	D-11
Photo No. 12. Post-Test 5 th Fem. P2 Driver Dummy Airbag Right Side View	D-12
Photo No. 13. Pre-Test 6YO P1 Passenger Dummy Left Side View	D-13
Photo No. 14. Post-Test 6YO P1 Passenger Dummy Left Side View	D-14
Photo No. 15. Pre-Test 6YO P1 Passenger Dummy Right Side View	D-15
Photo No. 16. Post-Test 6YO P1 Passenger Dummy Right Side View	D-16
Photo No. 17. Post-Test 6YO P1 Passenger Dummy Airbag Left Side View	D-17
Photo No. 18. Post-Test 6YO P1 Passenger Dummy Airbag Right Side View	D-18
Photo No. 19. Pre-Test 6YO P2 Passenger Dummy Left Side View	D-19
Photo No. 20. Post-Test 6YO P2 Passenger Dummy Left Side View	D-20
Photo No. 21. Pre-Test 6YO P2 Passenger Dummy Right Side View	D-21
Photo No. 22. Post-Test 6YO P2 Passenger Dummy Right Side View	D-22
Photo No. 23. Post-Test 6YO P2 Passenger Dummy Airbag Left Side View	D-23
Photo No. 24. Post-Test 6YO P2 Passenger Dummy Airbag Right Side View	D-24
Photo No. 25. Passenger Geometric Center (2008 Honda Accord)	D-25

D-1.



Pre-Test 5th Fem. P1 Driver Dummy Left Side View



Post-Test 5th Fem. P1 Driver Dummy Left Side View



Pre-Test 5th Fem. P1 Driver Dummy Right Side View



Post-Test 5th Fem. P1 Driver Dummy Right Side View



Post-Test 5th Fem. P1 Driver Dummy Airbag Left Side View



Post-Test 5th Fem. P1 Driver Dummy Airbag Right Side View



Pre-Test 5th Fem. P2 Driver Dummy Left Side View



Post-Test 5th Fem. P2 Driver Dummy Left Side View



Pre-Test 5th Fem. P2 Driver Dummy Right Side View



Post-Test 5th Fem. P2 Driver Dummy Right Side View



Post-Test 5th Fem. P2 Driver Dummy Airbag Left Side View



Post-Test 5th Fem. P2 Driver Dummy Airbag Right Side View



Pre-Test 6YO P1 Passenger Dummy Left Side View

D-14.



Post-Test 6YO P1 Passenger Dummy Left Side View



Pre-Test 6YO P1 Passenger Dummy Right Side View



Post-Test 6YO P1 Passenger Dummy Right Side View



Post-Test 6YO P1 Passenger Dummy Airbag Left Side View



Post-Test 6YO P1 Passenger Dummy Airbag Right Side View



Pre-Test 6YO P2 Passenger Dummy Left Side View



Post-Test 6YO P2 Passenger Dummy Left Side View



Pre-Test 6YO P2 Passenger Dummy Right Side View




Post-Test 6YO P2 Passenger Dummy Right Side View



Post-Test 6YO P2 Passenger Dummy Airbag Left Side View



Post-Test 6YO P2 Passenger Dummy Airbag Right Side View



Passenger Geometric Center (2008 Honda Accord)

APPENDIX E
SUPPRESSION PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

	<u>Page #</u>
Photo No. 1. Cosco Dream Ride Car Bed Belted, Forward Seat Track	E-1
Photo No. 2. Cosco Dream Ride Car Bed Belted, Middle Seat Track	E-1
Photo No. 3. Cosco Dream Ride Car Bed Belted, Rearward Seat Track	E-1
Photo No. 4. Unbelted 5 th Percentile Female Dummy Reactivation, Forward Seat Track	E-1
Photo No. 5. Britax Handle With Care 191 Belted, Forward Seat Track	E-2
Photo No. 6. Britax Handle With Care 191 Belted, Middle Seat Track	E-2
Photo No. 7. Britax Handle With Care 191 Belted, Rearward Seat Track	E-2
Photo No. 8. Britax Handle With Care 191 Unbelted, Forward Seat Track	E-2
Photo No. 9. Britax Handle With Care 191 Unbelted, Middle Seat Track	E-3
Photo No. 10. Britax Handle With Care 191 Unbelted, Rearward Seat Track	E-3
Photo No. 11. Britax Handle With Care 191 Forward Facing Unbelted, Forward Seat Track	E-3
Photo No. 12. Britax Handle With Care 191 Forward Facing Unbelted, Middle Seat Track	E-3
Photo No. 13. Britax Handle With Care 191 Forward Facing Unbelted, Rearward Seat Track	E-4
Photo No. 14. Unbelted 5 th Percentile Female Dummy Reactivation, Forward Seat Track	E-4
Photo No. 15. Evenflo First Choice 204 Belted, Middle Seat Track	E-5
Photo No. 16. Evenflo First Choice 204 Belted, Rearward Seat Track	E-5
Photo No. 17. Evenflo First Choice 204 Unbelted, Middle Seat Track	E-5
Photo No. 18. Evenflo First Choice 204 Unbelted, Rearward Seat Track	E-5
Photo No. 19. Evenflo First Choice 204 Forward Facing Unbelted, Forward Seat Track	E-6
Photo No. 20. Evenflo First Choice 204 Forward Facing Unbelted, Middle Seat Track	E-6
Photo No. 21. Evenflo First Choice 204 Forward Facing Unbelted, Rearward Seat Track	E-6
Photo No. 22. Unbelted 5 th Percentile Female Dummy Reactivation, Middle Seat Track	E-6
Photo No. 23. Graco Infant W/ Base Belted, Forward Seat Track	E-7
Photo No. 24. Graco Infant W/ Base Belted, Middle Seat Track	E-7
Photo No. 25. Graco Infant W/ Base Belted, Rearward Seat Track	E-7
Photo No. 26. Graco Infant W/ Base Unbelted, Forward Seat Track	E-7
Photo No. 27. Graco Infant W/ Base Unbelted, Middle Seat Track	E-8
Photo No. 28. Graco Infant W/ Base Unbelted, Rearward Seat Track	E-8
Photo No. 29. Graco Infant W/ Base Forward Facing Unbelted, Forward Seat Track	E-8
Photo No. 30. Graco Infant W/ Base Forward Facing Unbelted, Middle Seat Track	E-8
Photo No. 31. Graco Infant W/ Base Forward Facing Unbelted, Rearward Seat Track	E-9
Photo No. 32. Graco Infant W/O Base Belted, Forward Seat Track	E-9
Photo No. 33. Graco Infant W/O Base Belted, Middle Seat Track	E-9

Photo No. 34.	Graco Infant W/O Base Belted, Rearward Seat Track	E-9
Photo No. 35.	Graco Infant W/O Base Unbelted, Middle Seat Track	E-10
Photo No. 36.	Graco Infant W/O Base Unbelted, Rearward Seat Track	E-10
Photo No. 37.	Graco Infant W/O Base Forward Facing Unbelted, Forward Seat Track	E-10
Photo No. 38.	Graco Infant W/O Base Forward Facing Unbelted, Middle Seat Track	E-10
Photo No. 39.	Graco Infant W/O Base Forward Facing Unbelted, Rearward Seat Track	E-11
Photo No. 40.	Unbelted 5 th Percentile Female Dummy Reactivation, Rearward Seat Track	E-11
Photo No. 41.	Britax Roundabout 161 Forward Facing Belted, Forward Seat Track	E-12
Photo No. 42.	Britax Roundabout 161 Forward Facing Belted, Middle Seat Track	E-12
Photo No. 43.	Britax Roundabout 161 Forward Facing Belted, Rearward Seat Track	E-12
Photo No. 44.	Britax Roundabout 161 Forward Facing Unbelted, Forward Seat Track	E-12
Photo No. 45.	Britax Roundabout 161 Forward Facing Unbelted, Middle Seat Track	E-13
Photo No. 46.	Britax Roundabout 161 Forward Facing Unbelted, Rearward Seat Track	E-13
Photo No. 47.	Britax Roundabout 161 Rear Facing Belted, Forward Seat Track	E-13
Photo No. 48.	Britax Roundabout 161 Rear Facing Belted, Middle Seat Track	E-13
Photo No. 49.	Britax Roundabout 161 Rear Facing Belted, Rearward Seat Track	E-14
Photo No. 50.	Britax Roundabout 161 Rear Facing Unbelted, Forward Seat Track	E-14
Photo No. 51.	Britax Roundabout 161 Rear Facing Unbelted, Middle Seat Track	E-14
Photo No. 52.	Britax Roundabout 161 Rear Facing Unbelted, Rearward Seat Track	E-14
Photo No. 53.	Unbelted 5 th Percentile Female Dummy Reactivation, Forward Seat Track	E-15
Photo No. 54.	Century Encore Forward Facing Belted, Forward Seat Track	E-16
Photo No. 55.	Century Encore Forward Facing Belted, Middle Seat Track	E-16
Photo No. 56.	Century Encore Forward Facing Belted, Rearward Seat Track	E-16
Photo No. 57.	Century Encore Forward Facing Unbelted, Forward Seat Track	E-16
Photo No. 58.	Century Encore Forward Facing Unbelted, Middle Seat Track	E-17
Photo No. 59.	Century Encore Forward Facing Unbelted, Rearward Seat Track	E-17
Photo No. 60.	Century Encore Rear Facing Belted, Forward Seat Track	E-17
Photo No. 61.	Century Encore Rear Facing Belted, Middle Seat Track	E-17
Photo No. 62.	Century Encore Rear Facing Belted, Rearward Seat Track	E-18
Photo No. 63.	Century Encore Rear Facing Unbelted, Forward Seat Track	E-18
Photo No. 64.	Century Encore Rear Facing Unbelted, Middle Seat Track	E-18
Photo No. 65.	Century Encore Rear Facing Unbelted, Rearward Seat Track	E-18
Photo No. 66.	Unbelted 5 th Percentile Female Dummy Reactivation, Middle Seat Track	E-19
Photo No. 67.	Evenflo Medallion 254 Forward Facing Belted, Forward Seat Track	E-20
Photo No. 68.	Evenflo Medallion 254 Forward Facing Belted, Middle Seat Track	E-20

		<u>Page #</u>
Photo No. 69.	Evenflo Medallion 254 Forward Facing Belted, Rearward Seat Track	E-20
Photo No. 70.	Evenflo Medallion 254 Forward Facing Unbelted, Forward Seat Track	E-20
Photo No. 71.	Evenflo Medallion 254 Forward Facing Unbelted, Middle Seat Track	E-21
Photo No. 72.	Evenflo Medallion 254 Forward Facing Unbelted, Rearward Seat Track	E-21
Photo No. 73.	Evenflo Medallion 254 Rear Facing Belted, Forward Seat Track	E-21
Photo No. 74.	Evenflo Medallion 254 Rear Facing Belted, Middle Seat Track	E-21
Photo No. 75.	Evenflo Medallion 254 Rear Facing Belted, Rearward Seat Track	E-22
Photo No. 76.	Evenflo Medallion 254 Rear Facing Unbelted, Forward Seat Track	E-22
Photo No. 77.	Evenflo Medallion 254 Rear Facing Unbelted, Middle Seat Track	E-22
Photo No. 78.	Evenflo Medallion 254 Rear Facing Unbelted, Rearward Seat Track	E-22
Photo No. 79.	Unbelted 5 th Percentile Female Dummy Reactivation, Rearward Seat Track	E-23
Photo No. 80.	3-Year-Old Forward Facing Britax Roundabout Belted, Forward Seat Track	E-24
Photo No. 81.	3-Year-Old Forward Facing Britax Roundabout Belted, Middle Seat Track	E-24
Photo No. 82.	3-Year-Old Forward Facing Britax Roundabout Belted, Rearward Seat Track	E-24
Photo No. 83.	Unbelted 5 th Percentile Female Dummy Reactivation, Middle Seat Track	E-24
Photo No. 84.	3-Year-Old Forward Facing Century Encore Belted, Forward Seat Track	E-25
Photo No. 85.	3-Year-Old Forward Facing Century Encore Belted, Middle Seat Track	E-25
Photo No. 86.	3-Year-Old Forward Facing Century Encore Belted, Rearward Seat Track	E-25
Photo No. 87.	Unbelted 5 th Percentile Female Dummy Reactivation, Middle Seat Track	E-25
Photo No. 88.	3-Year-Old Forward Facing Evenflo Medallion Belted, Forward Seat Track	E-26
Photo No. 89.	3-Year-Old Forward Facing Evenflo Medallion Belted, Middle Seat Track	E-26
Photo No. 90.	3-Year-Old Forward Facing Evenflo Medallion Belted, Rearward Seat Track	E-26
Photo No. 91.	Unbelted 5 th Percentile Female Dummy Reactivation, Rearward Seat Track	E-26
Photo No. 92.	3-Year-Old Century Next Step Belted, Forward Seat Track	E-27
Photo No. 93.	3-Year-Old Century Next Step Belted, Middle Seat Track	E-27
Photo No. 94.	3-Year-Old Century Next Step Belted, Rearward Seat Track	E-27
Photo No. 95.	3-Year-Old Century Next Step Cinched With Harness, Forward Seat Track	E-27
Photo No. 96.	3-Year-Old Century Next Step Cinched With Harness, Middle Seat Track	E-28
Photo No. 97.	3-Year-Old Century Next Step Cinched With Harness, Rearward Seat Track	E-28
Photo No. 98.	Unbelted 5 th Percentile Female Dummy Reactivation, Forward Seat Track	E-28
Photo No. 99.	3-Year-Old Cosco High Back Booster Belted, Forward Seat Track	E-29
Photo No. 100.	3-Year-Old Cosco High Back Booster Belted, Middle Seat Track	E-29
Photo No. 101.	3-Year-Old Cosco High Back Booster Belted, Rearward Seat Track	E-29
Photo No. 102.	3-Year-Old Cosco High Back Booster Cinched With Harness, Forward Seat Track	E-29
Photo No. 103.	3-Year-Old Cosco High Back Booster Cinched With Harness, Middle Seat Track	E-31

	<u>Page #</u>
Photo No. 104. 3-Year-Old Cosco High Back Booster Cinched With Harness, Rearward Seat Track	E-31
Photo No. 105. Unbelted 5 th Percentile Female Dummy Reactivation, Middle Seat Track	E-31
Photo No. 106. 3-Year-Old Unbelted, Forward Seat Track, Position 1	E-32
Photo No. 107. 3-Year-Old Unbelted, Forward Seat Track, Position 2	E-32
Photo No. 108. 3-Year-Old Unbelted, Forward Seat Track, Position 3	E-32
Photo No. 109. 3-Year-Old Unbelted, Forward Seat Track, Position 4	E-32
Photo No. 110. 3-Year-Old Unbelted, Forward Seat Track, Position 5	E-33
Photo No. 111. 3-Year-Old Unbelted, Forward Seat Track, Position 6	E-33
Photo No. 112. 3-Year-Old Unbelted, Forward Seat Track, Position 7	E-33
Photo No. 113. 3-Year-Old Unbelted, Middle Seat Track, Position 1	E-33
Photo No. 114. 3-Year-Old Unbelted, Middle Seat Track, Position 2	E-34
Photo No. 115. 3-Year-Old Unbelted, Middle Seat Track, Position 3	E-34
Photo No. 116. 3-Year-Old Unbelted, Middle Seat Track, Position 4	E-34
Photo No. 117. 3-Year-Old Unbelted, Middle Seat Track, Position 5	E-34
Photo No. 118. 3-Year-Old Unbelted, Middle Seat Track, Position 6	E-35
Photo No. 119. 3-Year-Old Unbelted, Middle Seat Track, Position 7	E-35
Photo No. 120. 3-Year-Old Unbelted, Rearward Seat Track, Position 1	E-35
Photo No. 121. 3-Year-Old Unbelted, Rearward Seat Track, Position 2	E-35
Photo No. 122. 3-Year-Old Unbelted, Rearward Seat Track, Position 3	E-36
Photo No. 123. 3-Year-Old Unbelted, Rearward Seat Track, Position 4	E-36
Photo No. 124. 3-Year-Old Unbelted, Rearward Seat Track, Position 5	E-36
Photo No. 125. 3-Year-Old Unbelted, Rearward Seat Track, Position 6	E-36
Photo No. 126. 3-Year-Old Unbelted, Rearward Seat Track, Position 7	E-37
Photo No. 127. Unbelted 5 th Percentile Female Dummy Reactivation, Rearward Seat Track	E-37

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

Newborn

Section A

Car Bed



Cosco Dream Ride Car Bed Belted, Forward Seat Track



Cosco Dream Ride Car Bed Belted, Middle Seat Track



Cosco Dream Ride Car Bed Belted, Rearward Seat Track



Unbelted 5th Percentile Female Dummy Reactivation,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section B

Rear Facing CRS



Britax Handle With Care 191 Belted, Forward Seat Track



Britax Handle With Care 191 Belted, Middle Seat Track



Britax Handle With Care 191 Belted, Rearward Seat Track



Britax Handle With Care 191 Unbelted, Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section B

Rear Facing CRS



Britax Handle With Care 191 Unbelted, Middle Seat Track



Britax Handle With Care 191 Unbelted, Rearward Seat Track



Britax Handle With Care 191 Forward Facing Unbelted,
Forward Seat Track



Britax Handle With Care 191 Forward Facing Unbelted,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section B

Rear Facing CRS



Britax Handle With Care 191 Forward Facing Unbelted,
Rearward Seat Track



Unbelteed 5th Percentile Female Dummy Reactivation,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section B

Rear Facing CRS



Evenflo First Choice 204 Belted, Middle Seat Track



Evenflo First Choice 204 Belted, Rearward Seat Track



Evenflo First Choice 204 Unbelted, Middle Seat Track



Evenflo First Choice 204 Unbelted, Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section B

Rear Facing CRS



Evenflo First Choice 204 Forward Facing Unbelted,
Forward Seat Track



Evenflo First Choice 204 Forward Facing Unbelted,
Middle Seat Track



Evenflo First Choice 204 Forward Facing Unbelted,
Rearward Seat Track



Unbelted 5th Percentile Female Dummy Reactivation,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section B

Rear Facing CRS



Graco Infant W/ Base Belted, Forward Seat Track



Graco Infant W/ Base Belted, Middle Seat Track



Graco Infant W/ Base Belted, Rearward Seat Track



Graco Infant W/ Base Unbelted, Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section B

Rear Facing CRS



Graco Infant W/ Base Unbelted, Middle Seat Track



Graco Infant W/ Base Unbelted, Rearward Seat Track



Graco Infant W/ Base Forward Facing Unbelted,
Forward Seat Track



Graco Infant W/ Base Forward Facing Unbelted,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section B

Rear Facing CRS



Graco Infant W/ Base Forward Facing Unbelted,
Rearward Seat Track



Graco Infant W/O Base Belted, Forward Seat Track



Graco Infant W/O Base Belted, Middle Seat Track



Graco Infant W/O Base Belted, Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section B

Rear Facing CRS



Graco Infant W/O Base Unbelted, Middle Seat Track



Graco Infant W/O Base Unbelted, Rearward Seat Track



Graco Infant W/O Base Forward Facing Unbelted,
Forward Seat Track



Graco Infant W/O Base Forward Facing Unbelted,
Middle Seat Track



Graco Infant W/O Base Forward Facing Unbelted,
Rearward Seat Track




Unbelted 5th Percentile Female Dummy Reactivation,
Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section C

Forward Facing Convertible CRS



Britax Roundabout 161 Forward Facing Belted,
Forward Seat Track



Britax Roundabout 161 Forward Facing Belted,
Middle Seat Track



Britax Roundabout 161 Forward Facing Belted,
Rearward Seat Track



Britax Roundabout 161 Forward Facing Unbelted,
Forward Seat Track



Britax Roundabout 161 Forward Facing Unbelted,
Middle Seat Track



Britax Roundabout 161 Forward Facing Unbelted,
Rearward Seat Track



Britax Roundabout 161 Rear Facing Belted,
Forward Seat Track



Britax Roundabout 161 Rear Facing Belted,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section C


Forward Facing Convertible CRS




Britax Roundabout 161 Rear Facing Belted,
Rearward Seat Track



Britax Roundabout 161 Rear Facing Unbelted,
Forward Seat Track



Britax Roundabout 161 Rear Facing Unbelted,
Middle Seat Track



Britax Roundabout 161 Rear Facing Unbelted,
Rearward Seat Track



Unbelted 5th Percentile Female Dummy Reactivation,
Forward Seat Track



Century Encore Forward Facing Belted, Forward Seat Track



Century Encore Forward Facing Belted, Middle Seat Track



Century Encore Forward Facing Belted, Rearward Seat Track



Century Encore Forward Facing Unbelted, Forward Seat Track



Century Encore Forward Facing Unbelted, Middle Seat Track



Century Encore Forward Facing Unbelted, Rearward Seat Track



Century Encore Rear Facing Belted, Forward Seat Track



Century Encore Rear Facing Belted, Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section C

Forward Facing Convertible CRS



Century Encore Rear Facing Belted, Rearward Seat Track



Century Encore Rear Facing Unbelted, Forward Seat Track



Century Encore Rear Facing Unbelted, Middle Seat Track



Century Encore Rear Facing Unbelted, Rearward Seat Track



Unbelted 5th Percentile Female Dummy Reactivation,
Middle Seat Track



Evenflo Medallion 254 Forward Facing Belted,
Forward Seat Track



Evenflo Medallion 254 Forward Facing Belted,
Middle Seat Track



Evenflo Medallion 254 Forward Facing Belted,
Rearward Seat Track



Evenflo Medallion 254 Forward Facing Unbelted,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section C

Forward Facing Convertible CRS



Evenflo Medallion 254 Forward Facing Unbelted,
Middle Seat Track



Evenflo Medallion 254 Forward Facing Unbelted,
Rearward Seat Track



Evenflo Medallion 254 Rear Facing Belted, Forward Seat Track



Evenflo Medallion 254 Rear Facing Belted, Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section C

Forward Facing Convertible CRS



Evenflo Medallion 254 Rear Facing Belted,
Rearward Seat Track



Evenflo Medallion 254 Rear Facing Unbelted,
Forward Seat Track



Evenflo Medallion 254 Rear Facing Unbelted,
Middle Seat Track



Evenflo Medallion 254 Rear Facing Unbelted,
Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

12 Month

Section C

Forward Facing Convertible CRS



Unbelted 5th Percentile Female Dummy Reactivation,
Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

3 Year Old

Section C

Forward Facing Convertible CRS




3-Year-Old Forward Facing Britax Roundabout Belted,
Forward Seat Track



3-Year-Old Forward Facing Britax Roundabout Belted,
Middle Seat Track



3-Year-Old Forward Facing Britax Roundabout Belted,
Rearward Seat Track



Unbelted 5th Percentile Female Dummy Reactivation,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

3 Year Old

Section C

Forward Facing Convertible CRS



3-Year-Old Forward Facing Century Encore Belted,
Forward Seat Track



3-Year-Old Forward Facing Century Encore Belted,
Middle Seat Track



3-Year-Old Forward Facing Century Encore Belted,
Rearward Seat Track



Unbelted 5th Percentile Female Dummy Reactivation,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

3 Year Old

Section C

Forward Facing Convertible CRS



3-Year-Old Forward Facing Evenflo Medallion Belted,
Forward Seat Track



3-Year-Old Forward Facing Evenflo Medallion Belted,
Middle Seat Track



3-Year-Old Forward Facing Evenflo Medallion Belted,
Rearward Seat Track



Unbelted 5th Percentile Female Dummy Reactivation,
Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



3-Year-Old Century Next Step Belted, Forward Seat Track



3-Year-Old Century Next Step Belted, Middle Seat Track



3-Year-Old Century Next Step Belted, Rearward Seat Track



3-Year-Old Century Next Step Cinched With Harness,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



3-Year-Old Century Next Step Cinched With Harness,
Middle Seat Track



3-Year-Old Century Next Step Cinched With Harness,
Rearward Seat Track



Unbelted 5th Percentile Female Dummy Reactivation,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



3-Year-Old Cosco High Back Booster Belted,
Forward Seat Track



3-Year-Old Cosco High Back Booster Belted,
Middle Seat Track



3-Year-Old Cosco High Back Booster Belted,
Rearward Seat Track



3-Year-Old Cosco High Back Booster Cinched With Harness,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



3-Year-Old Cosco High Back Booster Cinched With Harness,
Middle Seat Track



3-Year-Old Cosco High Back Booster Cinched With Harness,
Rearward Seat Track



Unbelted 5th Percentile Female Dummy Reactivation,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)
3 Year Old No CRS



3-Year-Old Unbelted, Forward Seat Track, Position 1



3-Year-Old Unbelted, Forward Seat Track, Position 2



3-Year-Old Unbelted, Forward Seat Track, Position 3



3-Year-Old Unbelted, Forward Seat Track, Position 4

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)
3 Year Old No CRS



3-Year-Old Unbelted, Forward Seat Track, Position 5



3-Year-Old Unbelted, Forward Seat Track, Position 6



3-Year-Old Unbelted, Forward Seat Track, Position 7




3-Year-Old Unbelted, Middle Seat Track, Position 1

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

3 Year Old

No CRS



3-Year-Old Unbelted, Middle Seat Track, Position 2



3-Year-Old Unbelted, Middle Seat Track, Position 3



3-Year-Old Unbelted, Middle Seat Track, Position 4



3-Year-Old Unbelted, Middle Seat Track, Position 5

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

3 Year Old

No CRS



3-Year-Old Unbelted, Middle Seat Track, Position 6



3-Year-Old Unbelted, Middle Seat Track, Position 7



3-Year-Old Unbelted, Rearward Seat Track, Position 1



3-Year-Old Unbelted, Rearward Seat Track, Position 2


DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)

3 Year Old

No CRS



3-Year-Old Unbelted, Rearward Seat Track, Position 3



3-Year-Old Unbelted, Rearward Seat Track, Position 4



3-Year-Old Unbelted, Rearward Seat Track, Position 5




3-Year-Old Unbelted, Rearward Seat Track, Position 6

DOT/NHTSA 208 Suppression Test – 2008 Honda Accord (C85302)
3 Year Old No CRS



3-Year-Old Unbelted, Rearward Seat Track, Position 7



Unbelted 5th Percentile Female Dummy Reactivation,
Rearward Seat Track

APPENDIX F
INSTRUMENTATION CALIBRATION

INSTRUMENTS FOR DRIVER DUMMY NO. 511

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	ET21246	Entran	02/21/08
Head Y	ET21255	Entran	02/21/08
Head Z	ET21245	Entran	02/21/08
Neck Load Cell	253	Denton	03/28/08
Chest X	ET21217	Entran	02/21/08
Chest Y	ET21196	Entran	02/21/08
Chest Z	ET21259	Entran	02/21/08
Chest Displacement	511	Servo	02/04/08
Left Femur Load Cell	83	Denton	04/15/08
Right Femur Load Cell	84	Denton	04/15/08

INSTRUMENTS FOR PASSENGER DUMMY NO. 516

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	G04-Z09	Entran	03/13/08
Head Y	G04-Z26	Entran	03/13/08
Head Z	J14-J20	Entran	03/13/08
Neck Load Cell	1748	Denton	05/22/08
Chest X	G16-Z03	Entran	03/13/08
Chest Y	A28-H02	Entran	03/13/08
Chest Z	J03-J09	Entran	03/13/08
Chest Displacement	516	Servo	02/04/08
Left Femur Load Cell	991	Denton	05/01/08
Right Femur Load Cell	995	Denton	05/01/08

INSTRUMENTS FOR LOW RISK 5TH FEMALE DUMMY NO. 511 (P1 & P2)

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	ET21246	Entran	02/21/08
Head Y	ET21255	Entran	02/21/08
Head Z	ET21245	Entran	02/21/08
Neck Load Cell	253	Denton	03/28/08
Neck MY	1748	Denton	05/22/08
Chest X	ET21217	Entran	02/21/08
Chest Y	ET21196	Entran	02/21/08
Chest Z	ET21259	Entran	02/21/08
Chest Displacement	511	Servo	02/04/08
Left Femur Load Cell	83	Denton	04/15/08
Right Femur Load Cell	84	Denton	04/15/08

INSTRUMENTS FOR LOW RISK 6 YEAR OLD CHILD DUMMY NO. 155 (P1 & P2)

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	P47894	Endevco	04/11/08
Head Y	P47895	Endevco	04/11/08
Head Z	P47896	Endevco	04/11/08
Neck Load Cell	252	Denton	03/17/08
Chest X	P52144	Endevco	01/15/08
Chest Y	G22-D16	Entran	01/15/08
Chest Z	G21-M14	Entran	01/15/08
Chest Displacement	155	Servo	02/08/08

VEHICLE INSTRUMENTS

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Left Rear Seat Crossmember X	F04-R22	Entran	03/07/08
Right Rear Seat Crossmember X	A07-R12	Entran	02/06/08
Top of Engine X	H10-L04	Entran	06/10/08
Bottom of Engine X	04J14-J11	Entran	04/23/08
Left Brake Caliper X	J23-J06	Entran	06/10/08
Right Brake Caliper X	F11-H19	Entran	06/10/08
Instrument Panel X	G22-L04	Entran	04/23/08
Trunk Z	A22-R02	Entran	04/11/08